



# Open Source MANO

SO REST API (OSM RELEASE ONE)

February 18, 2017

# CONTENTS

- REST API – Introduction** **3**
- Terminology<sup>1</sup> .....4
- Normal Operations .....6
- REST Examples .....9
- Additional JSON POST Examples.....19
- Event Streams and Notifications .....24
- YANG Node to JSON Conversion .....32
  
- Orchestration API** **48**
- NS Package Management (nsd:nsd) .....49
- NS Lifecycle Management (nsr:nsd) ..... 108
- VNF Package Management (vnfd:vnfd)..... 173
- VNF Lifecycle Management (vnfr:vnfr)..... 240
- API Examples ..... 369

# REST API – Introduction

This guide describes the client interface of the REST Application Programming Interface. This guide also provides examples on how to communicate with the REST server.

## Terminology<sup>1</sup>

- anyxml: A data node that can contain an unknown chunk of XML data.
- augment: Adds new schema nodes to a previously defined schema node. augment is useful for adding vendor-specific parameters to standard data models.
- base type: The type from which a derived type was derived, which may be either a built-in type or another derived type.
- built-in type: A YANG data type defined in the YANG language, such as uint32 or string.
- choice: A schema node where only one of a number of identified alternatives is valid.
- configuration data: The set of writable data that is required to transform a system from its initial default state into its current state [[RFC4741](#)].
- conformance: A measure of how accurately a device follows a data model.
- container: An interior data node that exists in at most one instance in the data tree. A container has no value, but rather a set of child nodes.
- data definition statement: A statement that defines new data nodes. One of container, leaf, leaf-list, list, choice, case, augment, uses, and anyxml.
- data model: A data model describes how data is represented and accessed.
- data node: A node in the schema tree that can be instantiated in a data tree. One of container, leaf, leaf-list, list, and anyxml.
- data tree: The instantiated tree of configuration and state data on a device.
- derived type: A type that is derived from a built-in type (such as uint32), or another derived type.
- device deviation: A failure of the device to implement the module faithfully.
- extension: An extension attaches non-YANG semantics to statements. The extension statement defines new statements to express these semantics.
- feature: A mechanism for marking a portion of the model as optional. Definitions can be tagged with a feature name and are only valid on devices that support that feature.
- grouping: A reusable set of schema nodes, which may be used locally in the module, in modules that include it, and by other modules that import from it. The grouping statement is not a data definition statement and, as such, does not define any nodes in the schema tree.
- identifier: Used to identify different kinds of YANG items by name.
- instance identifier: A mechanism for identifying a particular node in a data tree.
- interior node: Nodes within a hierarchy that are not leaf nodes.
- leaf: A data node that exists in at most one instance in the data tree. A leaf has a value but no child nodes.

- leaf-list: Like the leaf node but defines a set of uniquely identifiable nodes rather than a single node. Each node has a value but no child nodes.
- leaf node: Contains simple data like an integer or a string. It has exactly one value of a particular type and no child nodes.
- list: An interior data node that may exist in multiple instances in the data tree. A list has no value, but rather a set of child nodes.
- module: A YANG module defines a hierarchy of nodes that can be used for NETCONF-based operations. With its definitions and the definitions it imports or includes from elsewhere, a module is self-contained and "compilable".
- RPC: A Remote Procedure Call, as used within the NETCONF protocol.
- RPC operation: A specific Remote Procedure Call, as used within the NETCONF protocol. It is also called a protocol operation.
- schema node: A node in the schema tree. One of container, leaf, leaf-list, list, choice, case, rpc, input, output, notification, and anyxml.
- schema node identifier: A mechanism for identifying a particular node in the schema tree.
- schema tree: The definition hierarchy specified within a module.
- state data: The additional data on a system that is not configuration data such as read-only status information and collected statistics [[RFC4741](#)].
- submodule: A partial module definition that contributes derived types, groupings, data nodes, RPCs, and notifications to a module. A YANG module can be constructed from a number of submodules.
- top-level data node: A data node where there is no other data node between it and a module or submodule statement.
- uses: The "uses" statement is used to instantiate the set of schema nodes defined in a grouping statement. The instantiated nodes may be refined and augmented to tailor them to any specific needs.

---

<sup>1</sup>Resource: [YANG - A Data Modeling Language for the Network Configuration Protocol \(NETCONF\)](#)

# Normal Operations

## URL targets

REST URL targets can be one of the following:

URL Target	Description
<code>/api/config</code>	Targets the config data store.
<code>/api/operational</code>	Targets operational data.
<code>/api/operations</code>	Targets remote procedure calls (RPCs).
<code>/api/schema</code>	Converts YANG node described by the URL path into its JSON representation

The subsequent parts of the URL are used to select the YANG object. For example, to associate a cloud account with your Orchestrator instance, append target `/api/config` with the YANG object `cloud`:

```
https://<orchestrator_ip/fqdn>:8008/api/config/cloud
```

## Authentication

All requests to the REST API require you to authenticate.

Provide a username/password pair encoded using [HTTP basic auth](#) access in the request header.

## Query parameters

Optionally use the following query parameters with GET operations to filter the results of a REST API request:

- `deep` – Use to select an entire sub-tree. To retrieve all elements, use the deep query parameter.

For example, GET a top-level container with `?deep`:

```
/api/running/top-container-deep?deep
```

- `select` – Use to select specific leaves of a list or container.

## Mime types

The API supports the following MIME types:

MIME Type	Description
<code>application/vnd.yang.data+json</code>	Data being given or received is encoded in JSON.
<code>application/vnd.yang.collection+json</code>	Data being given or received is encoded in JSON, with a special element aggregating the top-level list objects.
<code>application/vnd.yang.data+xml</code>	Data being given or received is encoded in XML.
<code>application/vnd.yang.collection+xml</code>	Data being given or received is encoded in XML, with a special element aggregating the top-level list objects.

## Example request header

```
GET /api/running/misc/int-leaf HTTP/1.1
Host: example.example.com
Accept: application/yang.api+xml
```

## Operations

The API supports the following operations:

Operation	Description
GET	<p>Retrieves data.</p> <p>GET is equivalent to a NETCONF <code>get</code>, or <code>get_config</code> operation, depending on the target.</p> <hr/> <p><b>Note:</b> When you perform GET operations on containers, the results are pruned if the container is a top-level object in its module. The pruning removes all non-key leaves from the result.</p> <hr/>
POST	<p>Creates new data.</p> <p>POST is equivalent to a NETCONF <code>create</code> operation, or if the target is an RPC, they are a RPC dispatch.</p>
PUT	<p>Updates data.</p> <p>PUT is equivalent to a NETCONF <code>replace</code> operation.</p>
DELETE	<p>Deletes data.</p> <p>DELETE is equivalent to a NETCONF <code>delete</code> operation.</p>

*See also*

Netconf Central [Documentation](#) and [RPC Methods](#)



# REST Examples

This topic provides a sample YANG scheme and examples for common calls to the REST API.

## REST YANG Model

The YANG used for the examples in this guide is as follows.

### Module example

```
{
  namespace "http://example.com/ns/example";
  prefix "example";

  container top-container-shallow {
    leaf a {
      type string;
    }
  }

  list top-list-shallow {
    key "k";
    leaf k {
      type string;
    }
  }

  container top-container-deep {
    leaf a {
      type string;
    }

    list inner-list-shallow {
      key "k";
      leaf k {
        type string;
      }
    }
  }

  container inner-container {
    leaf a{
      type string;
    }
    list inner-list {
      key "k";
      leaf k {
        type string;
      }
    }
  }

  list inner-list-deep {
    key "k";
```

```

    leaf k {
      type string;
    }
    container inner-container-shallow {
      leaf a {
        type string;
      }
    }
    container inner-container-deep {
      list bottom-list-shallow {
        key "k";
        leaf k {
          type string;
        }
      }
    }
  }
}

list top-list-deep {
  key "k";
  leaf k {
    type string;
  }
  list inner-list {
    key "k";
    leaf k {
      type string;
    }
    leaf a {
      type string;
    }
    container inner-container {
      leaf a{
        type string;
      }
    }
  }
}

container inner-container-shallow {
  leaf a{
    type string;
  }
}
container inner-container-deep {
  list bottom-list-shallow {
    key "k";
    leaf k {
      type string;
    }
  }
}
}

list multi-key {

```

```
key "foo bar";
leaf foo {
  type string;
}
leaf bar {
  type string;
}

leaf treasure {
  type uint32;
}

}

rpc in-and-out {
  input {
    leaf in {
      type string;
    }
  }
  output {
    leaf out {
      type string;
    }
  }
}

rpc in-no-out {
  input {
    leaf in {
      type string;
    }
  }
}

identity identity-base {
  description "Testing base identity";
}

identity identity-sub {
  base "identity-base";
}

container misc {

  leaf binary-leaf {
    type binary {
      length "1..20";
    }
  }

  leaf bool-leaf {
    type boolean;
  }

  leaf decimal-leaf {
```

```
    type decimal64 {
      fraction-digits 2;
    }
  }

  leaf empty-leaf {
    type empty;
  }

  leaf enum-leaf {
    type enumeration {
      enum a;
      enum b;
    }
  }

  leaf identityref-leaf {
    type identityref {
      base "identity-base";
    }
  }

  leaf int-leaf {
    type int32;
  }

  leaf instance-identifier-leaf {
    type instance-identifier;
  }

  list list-a {
    key "id";
    leaf id {
      type uint8;
    }
    leaf foo {
      type string;
    }
  }

  list list-b {
    key "id";
    leaf id {
      type uint8;
    }
    leaf leafref-to-list-a {
      type leafref {
        path "../..../list-a[id=current()/../id]/foo";
      }
    }
  }
}
```

## GET examples

### GET a leaf

URL

```
/api/running/misc/int-leaf
```

JSON response

```
{
  "example:int-leaf": 42
}
```

XML response

```
<misc xmlns="http://example.com/ns/example"
      xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
  <int-leaf>42</int-leaf>
</misc>
```

### GET a top-level container

URL

```
/api/running/top-container-deep
```

JSON response

```
{
  "example:top-container-deep": {
    "inner-container": {
      "inner-list": [
        {
          "k": "another key thing"
        }
      ]
    }
  }
}
```

XML response

```
<top-container-deep xmlns="http://example.com/ns/example"
                    xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
  <inner-container>
    <inner-list>
      <k>another key thing</k>
    </inner-list>
  </inner-container>
</top-container-deep>
```

## GET a top-level container with ?deep

### URL

```
/api/running/top-container-deep?deep
```

### JSON response

```
{
  "example:top-container-deep": {
    "inner-container": {
      "inner-list": [
        {
          "k": "another key thing"
        }
      ],
      "a": "another string"
    }
  }
}
```

### XML response

```
<top-container-deep xmlns="http://example.com/ns/example"
  xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
  <inner-container>
    <a>another string</a>
    <inner-list>
      <k>another key thing</k>
    </inner-list>
  </inner-container>
</top-container-deep>
```

## GET a container

### URL

```
/api/running/top-container-deep/inner-container
```

### JSON response

```
{
  "inner-list": [
    {
      "k": "another key thing"
    }
  ],
  "a": "another string"
}
```

### XML response

```
<top-container-deep xmlns="http://example.com/ns/example"
  xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
  <inner-container>
```

```

    <a>another string</a>
    <inner-list>
      <k>another key thing</k>
    </inner-list>
  </inner-container>
</top-container-deep>

```

## GET a whole list

URL

```
/api/running/top-list-shallow
```

## JSON response

```

{
  "example:top-list-shallow": [
    {
      "k": "asdf"
    },
    {
      "k": "fdsa"
    }
  ]
}

```

## JSON collection response

```

{
  "collection": {
    "example:top-list-shallow": [
      {
        "k": "asdf"
      },
      {
        "k": "fdsa"
      }
    ]
  }
}

```

## XML response

```

<data xmlns="urn:ietf:params:xml:ns:netconf:base:1.0"
  xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
  <top-list-shallow xmlns="http://example.com/ns/example">
    <k>asdf</k>
  </top-list-shallow>
  <top-list-shallow xmlns="http://example.com/ns/example">
    <k>fdsa</k>
  </top-list-shallow>
</data>

```

## XML collection response

```
<collection>
  <top-list-shallow xmlns="http://example.com/ns/example"
    xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
    <k>asdf</k>
  </top-list-shallow>
  <top-list-shallow xmlns="http://example.com/ns/example"
    xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
    <k>fdsa</k>
  </top-list-shallow>
</collection>
```

## GET a specific list entry

### URL

```
/api/running/top-list-shallow/asdf
```

### JSON response

```
{
  "example:top-list-shallow": [
    {
      "k": "asdf"
    }
  ]
}
```

### JSON collection response

```
{
  "collection": {
    "example:top-list-shallow": [
      {
        "k": "asdf"
      }
    ]
  }
}
```

### XML response

```
<data xmlns="urn:ietf:params:xml:ns:netconf:base:1.0"
  xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">
  <top-list-shallow xmlns="http://example.com/ns/example">
    <k>asdf</k>
  </top-list-shallow>
</data>
```

### XML collection response

```
<collection>
  <k xmlns="http://example.com/ns/example"
    xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">asdf</k>
</collection>
```



## POST/PUT examples

### POST/PUT a leaf

URL

```
/api/running/top-container-shallow
```

JSON body

```
{
  "a" : "some leaf 0"
}
```

XML body

```
<example:top-container-shallow xmlns:example="http://example.com/ns/example">
  <a xmlns="http://example.com/ns/example">some leaf 0</a>
</example:top-container-shallow>
```

### POST/PUT a container

URL

```
/api/config/top-container-deep/inner-container
```

JSON body

```
{
  "a":"another string",
  "inner-list":[
    {
      "k":"another key thing"
    }
  ]
}
```

XML body

```
<example:inner-container xmlns:example="http://example.com/ns/example">
  <a xmlns="http://example.com/ns/example">another string</a>
  <inner-list >
    <k xmlns="http://example.com/ns/example">another key thing</k>
  </inner-list>
</example:inner-container>
```

### POST/PUT a list entry

URL

```
/api/running/top-list-shallow/asdf
```

### JSON body

```
{
  "top-list-shallow" :
  [
    {
      "k" : "asdf"
    }
  ]
}
```

### XML body

```
<top-list-shallow xmlns="http://example.com/ns/example">
  <k xmlns="http://example.com/ns/example">asdf</k>
</top-list-shallow>
```

## POST an RPC

### URL

```
/api/operations/in-no-out
```

### JSON body

```
{
  "input" : {
    "in" : "asdf"
  }
}
```

### XML body

```
<input>
  <in="http://example.com/ns/example">asdf</in>
</input>
```

## DELETE examples

The DELETE operation has the same URL structure as the GET operation. You cannot perform a DELETE operation on containers

## Additional JSON POST Examples

### URL

```
/api/config/top-container-shallow
```

### JSON response

```
{
  "a" : "some leaf 0"
}
```

### URL

```
/api/config/top-list-shallow/some%20key
```

### JSON response

```
{
  "top-list-shallow" :
  [
    {
      "k" : "some key"
    }
  ]
}
```

### URL

```
/api/config/top-container-deep
```

### JSON response

```
{
  "a":"some kind of string",
  "inner-list-shallow":[
    {
      "k":"some key thing"
    },
    {
      "k":"some other key thing"
    }
  ],
  "inner-container":{
    "a":"another string",
    "inner-list":[
      {
        "k":"another key thing"
      }
    ]
  },
  "inner-list-deep":[
    {
```

```
        "k":"inner key",
        "inner-container-shallow":{
            "a":"an inner string"
        },
        "inner-container-deep":{
            "bottom-list-shallow":[
                {
                    "k":"bottom key"
                }
            ]
        }
    ]
}
```

## URL

```
/api/config/top-list-deep
```

## JSON response

```
{
  "top-list-deep" :
  [
    {
      "k" : "some key",
      "inner-list" :
      [
        {
          "k" : "some other key",
          "a" : "some string",
          "inner-container" : {
            "a" : "some other string"
          }
        }
      ]
    },
    "inner-container-shallow" :
    {
      "a" : "yet a third string"
    },
    "inner-container-deep":
    {
      "bottom-list-shallow" :
      [
        {
          "k" : "yet a third key"
        }
      ]
    }
  ]
}
```

**URL**

```
/api/config/multi-key/foo,bar
```

**JSON response**

```
{
  "multi-key" :
  [
    {
      "foo" : "key part 1",
      "bar" : "key part 2",
      "treasure" : 32
    }
  ]
}
```

**URL**

```
/api/config/top-list-deep/key1/inner-list/some%20key%20thing
```

**JSON response**

```
{
  "inner-list-shallow": [
    {
      "k": "some key thing"
    }
  ]
}
```

**URL**

```
/api/config/top-container-deep/inner-list-shallow/some%20key
```

**JSON response**

```
{
  "inner-list-shallow": [
    {
      "k": "some key"
    }
  ]
}
```

**URL**

```
/api/config/top-list-deep/key1/inner-list/key2
```

**JSON response**

```
{
  "inner-list": [
    {
```

```
        "k": "key2"
      }
    ]
  }
}
```

## URL

```
/api/config/top-container-deep/inner-container
```

## JSON response

```
{
  "a": "another string",
  "inner-list": [
    {
      "k": "another key thing"
    }
  ]
}
```

## URL

```
/api/config/top-list-deep/some%20key/inner-container-shallow
```

## JSON response

```
{
  "a" : "yet a third string"
}
```

## URL

```
/api/config/misc
```

## JSON response

```
{
  "bool-leaf": true,
  "empty-leaf": [
    null
  ],
  "enum-leaf": "a",
  "int-leaf": 42,
  "list-a": [
    {
      "id": 0,
      "foo": "asdf"
    }
  ],
  "list-b": [
    {
      "id": 0
    }
  ],
  "numbers": [
```

```
{
  "int8-leaf":0,
  "int16-leaf":0,
  "int32-leaf":0,
  "int64-leaf":0,
  "uint8-leaf":0,
  "uint16-leaf":0,
  "uint32-leaf":0,
  "uint64-leaf":0,
  "decimal-leaf":0
},
{
  "int8-leaf":"1",
  "int16-leaf":"0",
  "int32-leaf":"0",
  "int64-leaf":"0",
  "uint8-leaf":"0",
  "uint16-leaf":"0",
  "uint32-leaf":"0",
  "uint64-leaf":"0",
  "decimal-leaf":"0"
}
]
```

## Event Streams and Notifications

NETCONF notifications are asynchronous, one-way message notifications that originate from the NETCONF server. Clients can subscribe to event-streams defined in the server using a subscription mechanism.

By default, the Management Agent implements a `uagent_notification` notification stream.

An event notification can be generated by a tasklet using the Distributed Transaction System (DTS). The MgmtAgent listens for all event notifications generated by DTS and publishes them to Confd. Confd then publishes the event through `uagent_notification` NETCONF event stream. The published notification can be consumed by a web application through REST using either a Websockets or HTTP event source.

**Note:** The REST notification is implemented based on the RESTCONF Protocol [draft-ietf-netconf-restconf-09](#). See also the Internet Engineering Task Force (IETF) YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF) [RFC6020](#).

The sections that follow describe an HTTP-based programmatic interface for accessing data defined in YANG, using the data stores defined in NETCONF.

### Terms used:

- **Element** — XML Element.
- **Subscription** — An agreement and method to receive event notifications over a NETCONF session. A concept related to the delivery of notifications (if there are any to send) involving destination and selection of notifications. A subscription is bound to the lifetime of a session.
- **Operation** — Refers to NETCONF protocol operations defined in support of NETCONF notifications.
- **Event** — Something that occurs that might be of interest, such as a configuration change, a fault, a change in status, crossing a threshold, or an external input to the system. An event often results in an asynchronous message, sometimes referred to as a notification or event notification. The message is sent to interested parties to notify them that this event has occurred.
- **Replay** — The ability to send/re-send previously-logged notifications, upon request. These notifications are sent asynchronously. This feature is implemented by the NETCONF server and invoked by the NETCONF client.
- **Stream** — A set of event notifications that matches some forwarding criteria and available to NETCONF clients for subscription.
- **Filter** — A parameter that indicates which subset of all possible events are of interest. A filter is defined as one or more filter elements [NETCONF], each of which identifies a portion of the overall filter.



## State

State is operational data provided by RESTCONF. The schema `ietf-restconf-monitoring` for this operational data is defined in the RESTCONF Protocol [draft-ietf-netconf-restconf-09](#).

GET operations that use `/api/operational/restconf-state` can be used to retrieve the streams and their properties.

### GET streams

#### URL

```
/api/operational/restconf-state/streams
```

Each stream can be accessed using the following methods.

Stream	Method
WebSocket access, streaming using XML messages	[wss://host:port/ws_streams/STREAM-NAME]
WebSocket access, streaming using JSON messages	[wss://host:port/ws_streams/STREAM-NAME-JSON]
HTTP event source access, streaming using XML data	[https://host:port/streams/STREAM-NAME]
HTTP event source access, streaming using JSON data	[https://host:port/streams/STREAM-NAME-JSON]

### JSON body example

```
{
  "ietf-restconf-monitoring:streams" : {
    "stream" : [
      {
        "access" : [
          {
            "encoding" : "ws_xml",
            "location" : "wss://10.0.1.7:8888/ws_streams/NETCONF"
          },
          {
            "encoding" : "ws_json",
            "location" : "wss://10.0.1.7:8888/ws_streams/NETCONF-JSON"
          }
        ]
      }
    ]
  }
}
```

```

    },
    {
      "encoding" : "xml",
      "location" : "https://10.0.1.7:8888/streams/NETCONF"
    },
    {
      "encoding" : "json",
      "location" : "https://10.0.1.7:8888/streams/NETCONF-JSON"
    }
  ],
  "description" : "default NETCONF event stream",
  "replay-support" : "false",
  "name" : "NETCONF"
},
{
  "access" : [
    {
      "encoding" : "ws_xml",
      "location" :
"wss://10.0.1.7:8888/ws_streams/uagent_notification"
    },
    {
      "encoding" : "ws_json",
      "location" :
"wss://10.0.1.7:8888/ws_streams/uagent_notification-JSON"
    },
    {
      "encoding" : "xml",
      "location" : "https://10.0.1.7:8888/streams/uagent_notification"
    },
    {
      "encoding" : "json",
      "location" : "https://10.0.1.7:8888/streams/uagent_notification-
JSON"
    }
  ],
  "description" : "RW Uagent notifications",
  "replay-support" : "true",
  "replay-log-creation-time" : "2016-03-02T10:02:42+00:00",
  "name" : "uagent_notification"
}
]
}
}
}

```

## XML body example

```

<data>
  <restconf-state xmlns="urn:ietf:params:xml:ns:yang:ietf-restconf-
monitoring">
    <streams>
      <stream>
        <name>NETCONF</name>
        <description>default NETCONF event stream</description>
        <replay-support>false</replay-support>
        <access>

```

```

    <encoding>ws_xml</encoding>
    <location>wss://10.0.1.7:8888/ws_streams/NETCONF</location>
  </access>
  <access>
    <encoding>ws_json</encoding>
    <location>wss://10.0.1.7:8888/ws_streams/NETCONF-JSON</location>
  </access>
  <access>
    <encoding>xml</encoding>
    <location>https://10.0.1.7:8888/streams/NETCONF</location>
  </access>
  <access>
    <encoding>json</encoding>
    <location>https://10.0.1.7:8888/streams/NETCONF-JSON</location>
  </access>
</stream>
<stream>
  <name>uagent_notification</name>
  <description>RW Uagent notifications</description>
  <replay-support>true</replay-support>
  <replay-log-creation-time>2016-03-02T10:02:42+00:00</replay-log-
creation-time>
  <access>
    <encoding>ws_xml</encoding>
  <location>wss://10.0.1.7:8888/ws_streams/uagent_notification</location>
  </access>
  <access>
    <encoding>ws_json</encoding>
    <location>wss://10.0.1.7:8888/ws_streams/uagent_notification-
JSON</location>
  </access>
  <access>
    <encoding>xml</encoding>
  <location>https://10.0.1.7:8888/streams/uagent_notification</location>
  </access>
  <access>
    <encoding>json</encoding>
    <location>https://10.0.1.7:8888/streams/uagent_notification-
JSON</location>
  </access>
</stream>
</streams>
</restconf-state>
</data>

```

## GET stream location

### URL

```
/api/operational/restconf-state/streams/stream/{stream-
name}/access/{encoding}/location
```

Encoding can be one of [ xml, json, ws\_xml, ws\_json ]

### URL example

```
/api/operational/restconf-  
state/streams/stream/NETCONF/access/ws_json/location
```

### JSON body example

```
{"ietf-restconf-monitoring:location" :  
"wss://10.0.1.7:8888/ws_streams/NETCONF-JSON"}
```

### XML body example

```
<data xmlns="urn:ietf:params:xml:ns:netconf:base:1.0"  
xmlns:nc="urn:ietf:params:xml:ns:netconf:base:1.0">  
  <restconf-state xmlns="urn:ietf:params:xml:ns:yang:ietf-restconf-  
monitoring">  
    <streams>  
      <stream>  
        <name>NETCONF</name>  
        <access>  
          <encoding>ws_json</encoding>  
          <location>wss://10.0.1.7:8888/ws_streams/NETCONF-JSON</location>  
        </access>  
      </stream>  
    </streams>  
  </restconf-state>  
</data>
```

## Event Source

The REST interface serves as an event source for NETCONF notifications.

### Query parameters

The following query parameters are optional in the GET URL for both WebSocket and HTTP calls.

Query parameter	Description
filter	Event content filter (based on <a href="#">XPath 1.0</a> )
start-time	Replay event start time
stop-time	Replay event stop time

### WebSocket event source

In a WebSocket event source, streaming occurs through WebSocket transport.

#### URL format

Opening the WebSocket with the following URL format enables subscription to events for the given stream.

```
wss://HOST:PORT/ws_streams/STREAM-NAME [ ?QUERY-PARAMS ]
```

If the *STREAM-NAME* value contains a `JSON` suffix (*STREAM-NAME-JSON*), notifications are reported in JSON format. Otherwise, notifications are reported in XML format.

#### JSON event format

```
{
  "notification": {
    "eventTime" : "YYYY-MM-DDThh:mm:ss.microsec[TZ-Offset]",
    "...." : {...}
  }
}
```

#### XML event format

```
<notification>
  <eventTime>YYYY-MM-DDThh:mm:ss.microsec[TZ-Offset]</eventTime>
  ... ..
</notification>
```

### JavaScript example

```
var client = new WebSocket('wss://localhost:8888/ws_streams/NETCONF-JSON');

client.onerror = function() {
    alert('Connection Error');
};

client.onopen = function() {
    alert('WebSocket Client Connected');
};

client.onclose = function() {
    alert('Websocket Client Closed');
};

client.onmessage = function(e) {
    if (typeof e.data === 'string') {
        alert("Received: '" + e.data + "'");
    }
};
```

### JSON stream example

The following notification is reported when a configuration is changed.

```
{
  "notification" : {
    "eventTime" : "2016-03-02T05:49:51.986098-05:00",
    "ietf-netconf-notifications:netconf-config-change" : {
      "datastore" : "running",
      "changed-by":{
        "username" : "admin",
        "source-host" : "127.0.0.1",
        "session-id" : 11
      },
      "edit" : [
        {
          "operation" : "replace",
          "target" : "/rwlog-mgmt:logging/rwlog-mgmt:console/rwlog-
mgmt:filter/rwlog-mgmt:category[rwlog-mgmt:name='rw-mgmttagt-log']/rwlog-
mgmt:severity"
        }
      ]
    }
  }
}
```

### XML stream example

The following notification is reported when a configuration is changed.

```
<notification xmlns="urn:ietf:params:xml:ns:netconf:notification:1.0">
  <eventTime>2016-03-02T05:49:51.986098-05:00</eventTime>
  <netconf-config-change xmlns="urn:ietf:params:xml:ns:yang:ietf-netconf-
notifications">
```

```

<changed-by>
  <username>admin</username>
  <session-id>11</session-id>
  <source-host>127.0.0.1</source-host>
</changed-by>
<datastore>running</datastore>
<edit>
  <target xmlns:rwlog-mgmt="http://example.com/ns/version-1.0/rwlog-
mgmt"/>/rwlog-mgmt:logging/rwlog-mgmt:console/rwlog-mgmt:filter/rwlog-
mgmt:category[rwlog-mgmt:name='rw-mgmtagt-log']/rwlog-mgmt:severity</target>
  <operation>replace</operation>
</edit>
</netconf-config-change>
</notification>

```

## HTTP event source

The HTTP event source is based on based on [W3C.CR-eventsource](#).

Run HTTP GET using the following URL format to subscribe to events for the given stream.

### URL format

```
https://HOST:PORT/streams/STREAM-NAME [ ?QUERY-PARAMS ]
```

If the *STREAM-NAME* value contains a `JSON` suffix (*STREAM-NAME-JSON*), notifications are reported in JSON format. Otherwise, notifications are reported in XML format.

### GET request headers

The following headers specify that the accepted content is an event stream and the connection must be persisted.

```

Accept: text/event-stream
Cache-Control: no-cache
Connection: keep-alive

```

In both JSON and XML event formats, the `data:` tag appears for each line in the response.

### JSON event format

```

data: {
  data: "notification": {
    data: "eventTime" : "YYYY-MM-DDThh:mm:ss.microsec[TZ-Offset]",
    data: "...." : {...}
  }
}

```

### XML event format

```

data: <notification>
  data: <eventTime>YYYY-MM-DDThh:mm:ss.microsec[TZ-Offset]</eventTime>
  data: ... ..
data: </notification>

```

## YANG Node to JSON Conversion

This section describes how to use the REST API to convert a YANG node, described by the URL path, into its JSON representation.

**Note:** Conversion works only for CONFIG nodes. All other node types are ignored by rwyanglib.

### URL target

Use the following target to convert a YANG node to JSON.

```
/api/schema/....
```

The following table describes the JSON representation of a particular node.

URL path	Description
/api/schema/X/Y/Z	Returns the JSON representation of YANG node Z
/api/schema	Returns the JSON representation of all the top-level nodes of the schema

### General examples

#### leaf

```
/api/schema/nd:nsd-catalog/nsd:nsd/nsd:id

{
  "id": {
    "name": "id",
    "type": "leaf",
    "description": "Identifier for the NSD.",
    "cardinality": "0..1",
    "data-type": "string"
  }
}
```

#### list

```
/api/schema/nsd:nsd-catalog/nsd:nsd/connection-point

{
  "connection-point": {
```



```

"name": "connection-point",
"type": "list",
"description": "...." // Not printing for doc brevity
"cardinality": "0..N",
"properties": [
  {
    "name": "name",
    "type": "leaf",
    "description": "Name of the NS connection point.",
    "cardinality": "0..1",
    "data-type": "string"
  },
  {
    "name": "type",
    "type": "leaf",
    "description": "Type of the connection point.",
    "cardinality": "0..1",
    "data-type": {
      "enumeration": {
        "enum": {
          "VPORT": {
            "value": 0
          }
        }
      }
    }
  }
]
}
}

```

## leafref

```
/api/schema/nsd:nsd-catalog/nsd:nsd/constituent-vnfd/vnfd-id-ref
```

```

{
  "vnfd-id-ref": {
    "name": "vnfd-id-ref",
    "type": "leaf",
    "description": "Identifier for the VNFD.",
    "cardinality": "0..1",
    "data-type": {
      "leafref": {
        "path": "/vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id"
      }
    }
  }
}
}

```

## enumeration

```
/api/schema/nd:nsd-catalog/nsd:nsd/monitoring-param/json-query-method
```

```

{
  "json-query-method": {
    "name": "json-query-method",

```

```

"type": "leaf",
"description": "",
"cardinality": "0..1",
"data-type": {
  "enumeration": {
    "enum": {
      "NAMEKEY": {
        "value": 0
      },
      "JSONPATH": {
        "value": 1
      },
      "OBJECTPATH": {
        "value": 2
      }
    }
  }
}
}
}
}

```

## Detailed mapping examples

### YANG module used

```

module test-yang-json
{
  namespace "http://example.com/ns/version-1.0/test-yang-json.yang";
  prefix "tyj";

  identity company {
    description "A company";
  }

  identity riftio {
    base company;
    description "";
  }

  container top {
    description "Top Container";

    leaf-list leaflist {
      type string;
    }

    leaf idrefex {
      type identityref { base "tyj:company"; }
    }

    leaf bin {
      type binary;
    }

    leaf leaf-1 {
      type string;
    }
  }
}

```

```

}
leaf leaf-2 {
  description "Leaf number 2";
  type uint32;
}

leaf linstid { type instance-identifier; }

leaf n1 {config true; type int8 {range "-12..14";} }

leaf leaf-4 {
  type enumeration {
    enum I_E_A { value 991; }
    enum I_E_B { value 992; }
    enum I_E_C { value 993; }
  }
}

list list-1 {
  description "List no. 1";
  key "id";

  leaf id {
    type uint16;
  }

  container list-cont {
    description
      "List 1 Container for the lack of good names";
    leaf yours-truly {
      type string;
    }
  }

  list int-list-1 {
    description "Internal list to list 1";
    key "item";
    leaf item {
      type string;
    }
    leaf name {
      type string;
    }
  }
}

leaf leaf-5 {
  description "Leafref example";
  type leafref {
    path "../tyj:leaf-2";
  }
}

container leaf_bin {
  description "for test RwYangDom.EmptyLeaf";
  leaf empty1 { type empty; }
}

```

```

leaf empty2 { type empty; }
leaf bool1 { type boolean; }
leaf bool2 { type boolean; }
leaf bool3 { type boolean; }
}

leaf bit-leaf {
  description "Bit leaf ";
  type bits {
    bit aggregate {
      position 0;
    }
    bit timeout {
      position 1;
    }
    bit sync {
      position 2;
    }
  }
}

leaf bindata {
  type binary;
}

}

augment /tyjab:base-cont/tyjab:person {
  list company-list {
    key "iref1";
    leaf iref1 { type identityref { base "company"; } }
    leaf iref2 { type identityref { base "product"; } }
  }
}
}

```

## JSON attributes

Attribute	Description
"name"	Name of the YANG node.
"type"	YANG data type, such as leaf, list, leaf-list, and leafref.
"description"	Text description provided in the YANG module for that node.
"cardinality"	Number of elements contained by the node. Cardinality is set to 0..n for list and leaf list and 0..1 for all other nodes.

Attribute	Description
"mandatory"	True if the YANG node is marked mandatory in the YANG specification.
"keys"	Key name for the list node (present in list node only). Keys have cardinality of 1.
"properties"	List describing the YANG node with regard to the composite data type.
"data-type"	Enumerates a YANG data type.

## Mapping a simple leaf

### YANG node

```
leaf leaf-2 {
  description "Leaf number 2";
  type uint32;
}
```

### JSON node

```
{
  "name": "leaf-2",
  "type": "leaf",
  "description": "Leaf number 2",
  "cardinality": "0..1",
  "data-type": "uint32"
  "properties": []
}
```

## Mapping an empty leaf

### YANG node

```
leaf empty1 { type empty; }
```

### JSON node

```
{
  "name": "empty1",
  "type": "leaf",
  "description": "",
  "cardinality": "0..1",
  "data-type": "empty"
  "properties": []
}
```

## Mapping a leaf range

### YANG node

```
leaf n1 {type int8 {range "-12..14";} }
```

### JSON node

```
{
  "name": "n1",
  "type": "leaf",
  "description": "",
  "cardinality": "0..1",
  "data-type": "int8"
  "properties": []
}
```

**Note:** Currently the range is not shown in the corresponding JSON representation.

## Mapping a binary leaf

### YANG node

```
leaf bindata {
  type binary;
}
```

### JSON node

```
{
  "name": "bindata",
  "type": "leaf",
  "description": "",
  "cardinality": "0..1",
  "data-type": "binary"
  "properties": []
}
```

## Mapping leaf bits

### YANG node

```
leaf bit-leaf {
  description "Bit leaf ";
  type bits {
    bit aggregate {
      position 0;
    }
    bit timeout {
      position 1;
    }
    bit sync {
      position 2;
    }
  }
}
```

```

    }
  }
}

```

**JSON node**

```

{
  "name": "bit-leaf",
  "type": "leaf",
  "description": "Bit leaf ",
  "cardinality": "0..1",
  "data-type": {
    "bits": {
      "bit": {
        "aggregate": {
          "position": 0
        },
        "timeout": {
          "position": 1
        },
        "sync": {
          "position": 2
        }
      }
    }
  }
  "properties": []
}

```

**Mapping a leaf list****YANG node**

```

leaf-list leaflist {
  type string;
}

```

**JSON node**

```

{
  "name": "leaflist",
  "type": "leaf_list",
  "description": "",
  "cardinality": "0..N",
  "data-type": "string"
  "properties": []
}

```

## Mapping a leafref

### YANG node

```
leaf leaf-2 {
    description "Leaf number 2";
    type uint32;
}

leaf leaf-5 {
    description "Leafref example";
    type leafref {
        path "../tyj:leaf-2";
    }
}
```

### JSON node

```
{
  "name": "leaf-5",
  "type": "leaf",
  "description": "Leafref example",
  "cardinality": "0..1",
  "data-type": {
    "leafref": {
      "path": "../tyj:leaf-2"
    }
  }
  "properties": []
}
```

## Mapping a list

### YANG node

```
list list-1 {
    description "List no. 1";
    key "id name";

    leaf id {
        type uint16;
        mandatory "false";
    }

    leaf name {
        type string;
        mandatory "false";
    }

    container list-cont {
        description
            "List 1 Container for the lack of good names";
        leaf yours-truly {
            type string;
        }
    }
}
```



```

list int-list-1 {
  description "Internal list to list 1";
  key "item";
  leaf item {
    type string;
  }
  leaf name {
    type string;
  }
}

```

**JSON node**

```

{
  "name": "list-1",
  "type": "list",
  "description": "List no. 1",
  "cardinality": "0..N",
  "keys": [
    {
      "value": "id"
    },
    {
      "value": "name"
    }
  ],
  "properties": [
    {
      "name": "id",
      "type": "leaf",
      "description": "",
      "cardinality": "0..1",
      "mandatory": "true",
      "data-type": "uint16"
      "properties": []
    },
    {
      "name": "name",
      "type": "leaf",
      "description": "",
      "cardinality": "0..1",
      "mandatory": "true",
      "data-type": "string"
      "properties": []
    },
    {
      "name": "list-cont",
      "type": "container",
      "description": "List 1 Container for the lack of good names",
      "cardinality": "0..1",
      "properties": [
        {
          "name": "yours-truly",
          "type": "leaf",

```

```

        "description": "",
        "cardinality": "0..1",
        "data-type": "string"
        "properties": []
    }
]
},
{
    "name": "int-list-1",
    "type": "list",
    "description": "Internal list to list 1",
    "cardinality": "0..N",
    "keys": [
        {
            "value": "item"
        }
    ],
    "properties": [
        {
            "name": "item",
            "type": "leaf",
            "description": "",
            "cardinality": "0..1",
            "mandatory": "true",
            "data-type": "string"
            "properties": []
        },
        {
            "name": "name",
            "type": "leaf",
            "description": "",
            "cardinality": "0..1",
            "data-type": "string"
            "properties": []
        }
    ]
}
]
}
}

```

## Mapping a container

### YANG node

```

container leaf_bin {
    description "for test RwYangDom.EmptyLeaf";
    leaf empty1 { type empty; }
    leaf empty2 { type empty; }
    leaf bool1 { type boolean; }
    leaf bool2 { type boolean; }
    leaf bool3 { type boolean; }
}

```

**JSON node**

The "properties" attribute is a list of JSON nodes that represents the types that the list will hold.

```
{
  "name": "leaf_bin",
  "type": "container",
  "description": "for test RwYangDom.EmptyLeaf",
  "cardinality": "0..1",
  "properties": [
    {
      "name": "empty1",
      "type": "leaf",
      "description": "",
      "cardinality": "0..1",
      "data-type": "empty"
      "properties": []
    },
    {
      "name": "empty2",
      "type": "leaf",
      "description": "",
      "cardinality": "0..1",
      "data-type": "empty"
      "properties": []
    },
    {
      "name": "bool1",
      "type": "leaf",
      "description": "",
      "cardinality": "0..1",
      "data-type": "boolean"
      "properties": []
    },
    {
      "name": "bool2",
      "type": "leaf",
      "description": "",
      "cardinality": "0..1",
      "data-type": "boolean"
      "properties": []
    },
    {
      "name": "bool3",
      "type": "leaf",
      "description": "",
      "cardinality": "0..1",
      "data-type": "boolean"
      "properties": []
    }
  ]
}
```

## Mapping an identity ref

### YANG node

```
identity company {
  description "A company";
}

leaf idrefex {
  type identityref { base "tyj:company"; }
}
```

### JSON node

```
{
  "name": "idrefex",
  "type": "leaf",
  "description": "",
  "cardinality": "0..1",
  "data-type": {
    "idref": {
      "base": "tyj:rftio"
    }
  }
  "properties": []
}
```

## Mapping an enumeration

### YANG node

```
leaf leaf-4 {
  type enumeration {
    enum I_E_A { value 991; }
    enum I_E_B { value 992; }
    enum I_E_C { value 993; }
  }
}
```

### JSON node

```
{
  "name": "leaf-4",
  "type": "leaf",
  "description": "",
  "cardinality": "0..1",
  "data-type": {
    "enumeration": {
      "enum": {
        "I_E_A": {
          "value": 991
        },
        "I_E_B": {
          "value": 992
        },
        "I_E_C": {
          "value": 993
        }
      }
    }
  }
}
```

```

    }
  }
}
"properties": []
}

```

## Mapping an instance identifier

### YANG node

```
leaf linstid { type instance-identifier; }
```

### JSON node

```

{
  "name": "linstid",
  "type": "leaf",
  "description": "",
  "cardinality": "0..1",
  "data-type": "instance_id"
  "properties": []
}

```

## Mapping augmented nodes

### YANG node

```

container base-cont {
  list person {
    key "name";

    leaf name {
      description
        "Name of the person";
      type string;
    }

    leaf phone-no {
      description
        "Phone number of the person";
      type string;
    }
  }
}

// Augmented node
augment /tyjab:base-cont/tyjab:person {
  list company-list {
    key "iref1";
    leaf iref1 { type identityref { base "company"; } }
    leaf iref2 { type identityref { base "product"; } }
  }
}

```

**JSON node**

```

{
  "person": {
    "name": "person",
    "type": "list",
    "description": "",
    "cardinality": "0..N",
    "keys": [
      {
        "value": "name"
      }
    ],
    "properties": [
      {
        "name": "name",
        "type": "leaf",
        "description": "Name of the person",
        "cardinality": "0..1",
        "mandatory": "true",
        "data-type": "string"
        "properties": []
      },
      {
        "name": "phone-no",
        "type": "leaf",
        "description": "Phone number of the person",
        "cardinality": "0..1",
        "data-type": "string"
        "properties": []
      },
      {
        "name": "test-yang-json:company-list",
        "type": "list",
        "description": "",
        "cardinality": "0..N",
        "keys": [
          {
            "value": "iref1"
          }
        ],
        "properties": [
          {
            "name": "iref1",
            "type": "leaf",
            "description": "",
            "cardinality": "0..1",
            "mandatory": "true",
            "data-type": {
              "idref": {
                "base": "tyj:rftio"
              }
            }
          }
        ]
        "properties": []
      },
      {

```

```
"name": "iref2",
"type": "leaf",
"description": "",
"cardinality": "0..1",
"data-type": {
  "idref": {
    "base": "tyj:cloud-platform"
  }
}
"properties": []
}
]
}
]
}
}
```

## Notes and limitations

- Union and choice-case are not currently supported.
- In the JSON output, node names are not prefixed.

# Orchestration API

The Orchestration API is your interface to network service lifecycle management functions and service instantiation functions. The **resource orchestrator** interfaces with the Network Service Orchestrator and resource orchestration engines through secured REST interfaces.

Use the open northbound APIs for service management and orchestration:

- Onboard, instantiate, and terminate network services (**NFVO** MANO `Os-Ma-nfvo` reference point)
- Onboard, instantiate, update, and delete virtual network functions (**VNFM** MANO `Or-Vnfm` reference point)



## NS Package Management (nsd:nsd)

REST wrapper for the **NSD** service (nsd:nsd-catalog). Provides methods for onboarding, updating, querying, and deleting a network service descriptor.

### Methods and relative URLs

#### nsd:nsd

Method	Relative URL	Description
POST	/api/running/nsd-catalog	<p>Onboard a network service descriptor package to the catalog.</p> <p>When you send a POST request, validates the checksum.txt file and validates the presence of:</p> <ul style="list-style-type: none"> <li>• VNF packages for the list of VNFs in the network service</li> <li>• Mandatory elements</li> <li>• Eternal connection points required by the NS in the VNF descriptor</li> </ul> <p>Use the same POST call to import to the catalog. The only difference is the input <code>tgz</code> file contains and onboards multiple NSDs in a single operation.</p>
GET	/api/running/nsd-catalog/nsd/{UUID}	Query a network service descriptor.
GET	/api/running/nsd-catalog/nsd	Retrieve a list of all network descriptors in the catalog.
PUT	/api/running/nsd-catalog/nsd/{UUID}	<p>Update a network service descriptor.</p> <p>The orchestrator verifies that NSD or its constituent VNFDs are not in use by a running instances of either the VNF or network service.</p>

Method	Relative URL	Description
DELETE	/api/running/nsd-catalog/nsd/{UUID}	<p>Delete a network service descriptor.</p> <p>When you send a DELETE request, the orchestrator verifies that the specified NSD is not in use by a running instance of the network service.</p>

### nsd:vnffg

Method	Relative URL	Description
GET	/api/running/vnffgd-catalog/vnffgd{UUID}	Query a VNF forwarding graph (VNFFG).
GET	/api/running/vnffgd-catalog/vnffgg	Retrieve a list of all VNFFGs in the catalog.
POST	/api/running/vnffgd-catalog/vnffgd	Create a VNFFG.
PUT	/api/running/vnffgd-catalog/vnffgd{UUID}	Update a VNFFG.
DELETE	/api/running/vnffgd-catalog/vnffgd{UUID}	Delete a VNFFG.

### nsd:vld

Method	Relative URL	Description
GET		Retrieve a list of a virtual links from the catalog

## Fields

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the Network Service Descriptor (NSD).
name	string	1	NSD name.
short-name	string	1	NSD short name to use as a label in the UI.
vendor	string	1	Vendor of the NSD.
logo	string	1	<p>File path of the vendor-specific logo. For example, icons/mylogo.png</p> <p>The logo should be part of the network service package.</p> <p>SVG format is preferred, but PNG is supported.</p> <p>Although there is no hard limit on size and dimension, a square image under 200px by 200px is preferred.</p>
description	string	1	Description of the NSD.
version	string	1	Version of the NSD.
connection-point	list	0..n	<p>A list of references to network service connection points.</p> <p>See <a href="#">"nsd:connection-point" on page 71</a>.</p>
vld	list	0..n	<p>List of Virtual Link Descriptors (VLDs).</p> <p>See <a href="#">"nsd:vld" on page 72</a>.</p>

ID	Type	Cardinality	Description
constituent-vnfd	list	0..n	List of Virtual Network Function Descriptors (VNFDs) that are part of this network service. See <a href="#">"nsd:constituent-vnfd" on page 76.</a>
config-parameter-map	list	0..n	A mapping of VNF configuration parameter requests and sources within this network service. See <a href="#">"nsd:config-parameter-map" on page 77.</a>
scaling-group-descriptor	list	0..n	Scaling group descriptor within this network service. See <a href="#">"nsd:scaling-group-descriptor" on page 79.</a>
placement-groups	list	0..n	List of placement groups at the NS level. See <a href="#">"nsd:placement-groups" on page 83.</a>
ip-profiles-list	list	0..n	List of IP profiles. See <a href="#">"nsd:ip-profiles" on page 85.</a>
vnf-dependency	list	0..n	List of VNF dependencies. See <a href="#">"nsd:vnf-dependency" on page 86.</a>
vnffgd	list	0..n	List of VNF forwarding graph descriptor (VNFFGD). See <a href="#">"nsd:vnffgd" on page 88.</a>
monitoring-param	list	0..n	List of monitoring parameters at the network service level. See <a href="#">"nsd:monitoring-param" on page 93.</a>
input-parameter-xpath	list	0..n	List of XPath to parameters inside the NSD that can be customized during instantiation. See <a href="#">"nsd:input-parameter-xpath" on page 97.</a>

ID	Type	Cardinality	Description
parameter-pool	list	0..n	Pool of parameter values that must be pulled from during configuration. See <a href="#">"nsd:parameter-pool" on page 98.</a>
service-primitive	list	0..n	Network service level configuration primitives. See <a href="#">"nsd:service-primitive" on page 99.</a>
initial-config-primitive	list	0..n	Set of configuration primitives to be executed when the network service comes up. See <a href="#">"nsd:initial-config-primitive" on page 104.</a>
terminate-config-primitive	list	0..n	Set of configuration primitives to be executed before during termination of the network service. See <a href="#">"nsd:terminate-config-primitive" on page 105.</a>
key-pair	list	0..n	Used to configure the list of public keys to be injected as part of network service instantiation. See <a href="#">"nsd:key-pair" on page 106.</a>
user	list	0..n	List of users to be added through cloud-config. See <a href="#">"nsd:user" on page 107.</a>

## MANO reference points

Os-Ma-nfvo

### Schema

```

module nsd
{
  namespace "urn:ietf:params:xml:ns:yang:nfvo:nsd";
  prefix "nsd";

  import rw-pb-ext {
    prefix "rwpb";
  }
}

```

```
}

import vld {
  prefix "vld";
}

import vnfd {
  prefix "vnfd";
}

import ietf-inet-types {
  prefix "inet";
}

import ietf-yang-types {
  prefix "yang";
}

import mano-types {
  prefix "manotypes";
}

revision 2014-10-27 {
  description
    "Initial revision. This YANG file defines
    the Network Service Descriptor (NSD)";
  reference
    "Derived from earlier versions of base YANG files";
}

typedef scaling-trigger {
  type enumeration {
    enum pre-scale-in {
      value 1;
    }
    enum post-scale-in {
      value 2;
    }
    enum pre-scale-out {
      value 3;
    }
    enum post-scale-out {
      value 4;
    }
  }
}

typedef scaling-policy-type {
  type enumeration {
    enum manual {
      value 1;
    }
    enum automatic {
      value 2;
    }
  }
}
```

```
}

typedef scaling-criteria-operation {
  type enumeration {
    enum AND {
      value 1;
    }
    enum OR {
      value 2;
    }
  }
}

grouping primitive-parameter {
  leaf name {
    description
      "Name of the parameter.";
    type string;
  }

  leaf data-type {
    description
      "Data type associated with the name.";
    type manotypes:parameter-data-type;
  }

  leaf mandatory {
    description "Is this field mandatory";
    type boolean;
    default false;
  }

  leaf default-value {
    description "The default value for this field";
    type string;
  }

  leaf parameter-pool {
    description "NSD Parameter pool name to use for this parameter";
    type string;
  }
}

grouping nsd-descriptor {
  leaf id {
    description "Identifier for the NSD.";
    type string;
  }

  leaf name {
    description "NSD name.";
    mandatory true;
    type string;
  }

  leaf short-name {
```

```
    description "NSD short name.";
    type string;
}

leaf vendor {
    description "Vendor of the NSD.";
    type string;
}

leaf logo {
    description
        "File path for the vendor specific logo. For example
icons/mylogo.png.
        The logo should be part of the network service";
    type string;
}

leaf description {
    description "Description of the NSD.";
    type string;
}

leaf version {
    description "Version of the NSD";
    type string;
}

list connection-point {
    description
        "List for external connection points.
        Each NS has one or more external connection
        points. As the name implies that external
        connection points are used for connecting
        the NS to other NS or to external networks.
        Each NS exposes these connection points to
        the orchestrator. The orchestrator can
        construct network service chains by
        connecting the connection points between
        different NS.";

    key "name";
    leaf name {
        description
            "Name of the NS connection point.";
        type string;
    }

    leaf type {
        description
            "Type of the connection point.";
        type manotypes:connection-point-type;
    }
}

/* Model limitation,
    see the comments under vnf-d-connection-point-ref
```



```
*/
list vld {
  description
    "List of Virtual Link Descriptors.";

  key "id";

  leaf id {
    description
      "Identifier for the VLD.";
    type string;
  }

  leaf name {
    description
      "Virtual Link Descriptor (VLD) name.";
    type string;
  }

  leaf short-name {
    description
      "Short name for VLD for UI";
    type string;
  }

  leaf vendor {
    description "Provider of the VLD.";
    type string;
  }

  leaf description {
    description "Description of the VLD.";
    type string;
  }

  leaf version {
    description "Version of the VLD";
    type string;
  }

  leaf type {
    type manotypes:virtual-link-type;
  }

  leaf root-bandwidth {
    description
      "For ELAN this is the aggregate bandwidth.";
    type uint64;
  }

  leaf leaf-bandwidth {
    description
      "For ELAN this is the bandwidth of branches.";
    type uint64;
  }
}
```

```

list vnfd-connection-point-ref {
  description
    "A list of references to connection points.";
  key "member-vnf-index-ref vnfd-connection-point-ref";

  leaf member-vnf-index-ref {
    description "Reference to member-vnf within constituent-vnfds";
    type leafref {
      path "../..../constituent-vnfd/member-vnf-index";
    }
  }

  leaf vnfd-id-ref {
    description
      "A reference to a vnfd. This is a
      leafref to path:
        ../..../nsd:constituent-vnfd
        + [nsd:id = current()../..../nsd:id-ref]
        + /nsd:vnfd-id-ref
      NOTE: An issue with confd is preventing the
      use of xpath. Seems to be an issue with leafref
      to leafref, whose target is in a different module.
      Once that is resolved this will switched to use
      leafref";
    type leafref {
      path "../..../constituent-vnfd" +
        "[member-vnf-index = current()../..../member-vnf-index-ref]" +
        "/vnfd-id-ref";
    }
  }

  leaf vnfd-connection-point-ref {
    description
      "A reference to a connection point name
      in a vnfd. This is a leafref to path:
        /vnfd:vnfd-catalog/vnfd:vnfd
        + [vnfd:id = current()../..../nsd:vnfd-id-ref]
        + /vnfd:connection-point/vnfd:name
      NOTE: An issue with confd is preventing the
      use of xpath. Seems to be an issue with leafref
      to leafref, whose target is in a different module.
      Once that is resolved this will switched to use
      leafref";
    type string;
  }
}

// replicate for pnfd container here
uses manotypes:provider-network;

leaf mgmt-network {
  description "Flag indicating whether this network is a VIM
management network";
  type boolean;
  default false;
}

```

```
choice init-params {
  description "Extra parameters for VLD instantiation";

  case vim-network-ref {
    leaf vim-network-name {
      description
        "Name of network in VIM account. This is used to indicate
        pre-provisioned network name in cloud account.";
      type string;
    }
  }

  case vim-network-profile {
    leaf ip-profile-ref {
      description "Named reference to IP-profile object";
      type string;
    }
  }
}

list constituent-vnfd {
  description
    "List of VNFDs that are part of this
    network service.";

  key "member-vnf-index";

  leaf member-vnf-index {
    description
      "Identifier/index for the VNFD. This separate id
      is required to ensure that multiple VNFs can be
      part of single NS";
    type uint64;
  }

  leaf vnfd-id-ref {
    description
      "Identifier for the VNFD.";
    type leafref {
      path "/vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id";
    }
  }

  leaf start-by-default {
    description
      "VNFD is started as part of the NS instantiation";
    type boolean;
    default true;
  }
}

list scaling-group-descriptor {
  description
```

```
    "scaling group descriptor within this network service.
    The scaling group defines a group of VNFs,
    and the ratio of VNFs in the network service
    that is used as target for scaling action";

key "name";

leaf name {
    description "Name of this scaling group.";
    type string;
}

list scaling-policy {

    key "name";

    leaf name {
        description
            "Name of the scaling policy";
        type string;
    }

    leaf scaling-type {
        description
            "Type of scaling";
        type scaling-policy-type;
    }

    leaf enabled {
        description
            "Specifies if the scaling policy can be applied";
        type boolean;
        default true;
    }

    leaf scale-in-operation-type {
        description
            "Operation to be applied to check between scaling criteria to
            check if the scale in threshold condition has been met.
            Defaults to AND";
        type scaling-criteria-operation;
        default AND;
    }

    leaf scale-out-operation-type {
        description
            "Operation to be applied to check between scaling criteria to
            check if the scale out threshold condition has been met.
            Defaults to OR";
        type scaling-criteria-operation;
        default OR;
    }

    leaf threshold-time {
        description
            "The duration for which the criteria must hold true";
```

```
    type uint32;
    mandatory true;
  }

  leaf cooldown-time {
    description
      "The duration after a scaling-in/scaling-out action has been
      triggered, for which there will be no further optional";
    type uint32;
    mandatory true;
  }

  list scaling-criteria {
    description
      "list of conditions to be met for generating scaling
      requests";
    key "name";

    leaf name {
      type string;
    }

    leaf scale-in-threshold {
      description
        "Value below which scale-in requests are generated";
      type uint64;
    }

    leaf scale-out-threshold {
      description
        "Value above which scale-out requests are generated";
      type uint64;
    }

    leaf ns-monitoring-param-ref {
      description
        "Reference to the NS level monitoring parameter
        that is aggregated";
      type leafref {
        path "../..../monitoring-param/id";
      }
    }
  }
}

list vnfd-member {
  description "List of VNFs in this scaling group";
  key "member-vnf-index-ref";

  leaf member-vnf-index-ref {
    description "member VNF index of this member VNF";
    type leafref {
      path "../..../constituent-vnfd/member-vnf-index";
    }
  }
}
```

```
    leaf count {
      description
        "count of this member VNF within this scaling group.
        The count allows to define the number of instances
        when a scaling action targets this scaling group";
      type uint32;
      default 1;
    }
  }

  leaf min-instance-count {
    description
      "Minimum instances of the scaling group which are allowed.
      These instances are created by default when the network service
      is instantiated.";
    type uint32;
    default 0;
  }

  leaf max-instance-count {
    description
      "Maximum instances of this scaling group that are allowed
      in a single network service. The network service scaling
      will fail, when the number of service group instances
      exceed the max-instance-count specified.";
    type uint32;
    default 10;
  }

  list scaling-config-action {
    description "List of scaling config actions";
    key "trigger";

    leaf trigger {
      description "scaling trigger";
      type scaling-trigger;
    }

    leaf ns-config-primitive-name-ref {
      description "Reference to the NS config name primitive";
      type leafref {
        path "../.../.../service-primitive/name";
      }
    }
  }
}

list placement-groups {
  description "List of placement groups at NS level";

  key "name";
  uses manotypes:placement-group-info;

  list member-vnfd {
    description
      "List of VNFDs that are part of this placement group";
```

```

    key "member-vnf-index-ref";

    leaf member-vnf-index-ref {
      description "member VNF index of this member VNF";
      type leafref {
        path "../.../constituent-vnfd/member-vnf-index";
      }
    }

    leaf vnfd-id-ref {
      description
        "Identifier for the VNFD.";
      type leafref {
        path "../.../constituent-vnfd" +
          "[member-vnf-index = current()/../member-vnf-index-ref]" +
          "/vnfd-id-ref";
      }
    }
  }
}

uses manotypes:ip-profile-list;

list vnf-dependency {
  description
    "List of VNF dependencies.";
  key vnf-source-ref;
  leaf vnf-source-ref {
    type leafref {
      path "../.../constituent-vnfd/vnfd-id-ref";
    }
  }
  leaf vnf-depends-on-ref {
    description
      "Reference to VNF that source VNF depends.";
    type leafref {
      path "../.../constituent-vnfd/vnfd-id-ref";
    }
  }
}

list vnffgd {
  description
    "List of VNF Forwarding Graph Descriptors (VNFFGD).";

  key "id";

  leaf id {
    description
      "Identifier for the VNFFGD.";
    type string;
  }

  leaf name {
    description

```

```
        "VNFFGD name.";
    type string;
}

leaf short-name {
    description
        "Short name for VNFFGD for UI";
    type string;
}

leaf vendor {
    description "Provider of the VNFFGD.";
    type string;
}

leaf description {
    description "Description of the VNFFGD.";
    type string;
}

leaf version {
    description "Version of the VNFFGD";
    type string;
}

list rsp {
    description
        "List of Rendered Service Paths (RSP).";

    key "id";

    leaf id {
        description
            "Identifier for the RSP.";
        type string;
    }

    leaf name {
        description
            "RSP name.";
        type string;
    }

    list vnfd-connection-point-ref {
        description
            "A list of references to connection points.";
        key "member-vnf-index-ref vnfd-connection-point-ref";

        leaf member-vnf-index-ref {
            description "Reference to member-vnf within constituent-vnfd";
            type leafref {
                path "../../../constituent-vnfd/member-vnf-index";
            }
        }
    }

    leaf order {
```



```

    type uint8;
    description
        "A number that denotes the order of a VNF in a chain";
}

leaf vnfd-id-ref {
    description
        "A reference to a vnfd. This is a
        leafref to path:
            ../../../../nsd:constituent-vnfd
            + [nsd:id = current()/../../nsd:id-ref]
            + /nsd:vnfd-id-ref
        NOTE: An issue with confd is preventing the
        use of xpath. Seems to be an issue with leafref
        to leafref, whose target is in a different module.
        Once that is resolved this will switched to use
        leafref";
    type leafref {
        path "../../../../constituent-vnfd" +
            "[member-vnf-index = current()/../../member-vnf-index-
ref]" +
            "/vnfd-id-ref";
    }
}

leaf vnfd-connection-point-ref {
    description
        "A reference to a connection point name
        in a vnfd. This is a leafref to path:
            /vnfd:vnfd-catalog/vnfd:vnfd
            + [vnfd:id = current()/../../nsd:vnfd-id-ref]
            + /vnfd:connection-point/vnfd:name
        NOTE: An issue with confd is preventing the
        use of xpath. Seems to be an issue with leafref
        to leafref, whose target is in a different module.
        Once that is resolved this will switched to use
        leafref";
    type leafref {
        path "/vnfd:vnfd-catalog/vnfd:vnfd" +
            "[vnfd:id = current()/../../vnfd-id-ref]/" +
            "vnfd:connection-point/vnfd:name";
    }
}
} //rsp

list classifier {
    description
        "List of classifier rules.";

    key "id";

    leaf id {
        description
            "Identifier for the classifier rule.";
        type string;
    }
}

```

```

}

leaf name {
  description
    "Name of the classifier.";
  type string;
}

leaf rsp-id-ref {
  description
    "A reference to the RSP.";
  type leafref {
    path "../..//rsp/id";
  }
}

leaf member-vnf-index-ref {
  description "Reference to member-vnf within constituent-vnfd";
  type leafref {
    path "../..//..//constituent-vnfd/member-vnf-index";
  }
}

leaf vnfd-id-ref {
  description
    "A reference to a vnfd. This is a
    leafref to path:
      ../..//..//nsd:constituent-vnfd
      + [nsd:id = current()//..//nsd:id-ref]
      + /nsd:vnfd-id-ref
    NOTE: An issue with confd is preventing the
    use of xpath. Seems to be an issue with leafref
    to leafref, whose target is in a different module.
    Once that is resolved this will switched to use
    leafref";
  type leafref {
    path "../..//..//constituent-vnfd" +
      "[member-vnf-index = current()//..//member-vnf-index-ref]"
+
      "/vnfd-id-ref";
  }
}

leaf vnfd-connection-point-ref {
  description
    "A reference to a connection point name
    in a vnfd. This is a leafref to path:
      /vnfd:vnfd-catalog/vnfd:vnfd
      + [vnfd:id = current()//..//nsd:vnfd-id-ref]
      + /vnfd:connection-point/vnfd:name
    NOTE: An issue with confd is preventing the
    use of xpath. Seems to be an issue with leafref
    to leafref, whose target is in a different module.
    Once that is resolved this will switched to use
    leafref";
  type leafref {

```

```
        path "/vnfd:vnfd-catalog/vnfd:vnfd" +
            "[vnfd:id = current()/../vnfd-id-ref]/" +
            "vnfd:connection-point/vnfd:name";
    }
}

list match-attributes {
    description
        "List of match attributes.";

    key "id";

    leaf id {
        description
            "Identifier for the classifier match attribute rule.";
        type string;
    }

    leaf ip-proto {
        description
            "IP Protocol.";
        type uint8;
    }

    leaf source-ip-address {
        description
            "Source IP address.";
        type inet:ip-address;
    }

    leaf destination-ip-address {
        description
            "Destination IP address.";
        type inet:ip-address;
    }

    leaf source-port {
        description
            "Source port number.";
        type inet:port-number;
    }

    leaf destination-port {
        description
            "Destination port number.";
        type inet:port-number;
    }
} //match-attributes
} // classifier
} // vnffgd

list monitoring-param {
    description
        "List of monitoring parameters from VNFs that should be
        propagated up into NSR";
    key "id";
```

```

leaf id {
  type string;
}

leaf name {
  type string;
}

uses manotypes:monitoring-param-value;
uses manotypes:monitoring-param-ui-data;
uses manotypes:monitoring-param-aggregation;

list vnfd-monitoring-param {
  description "A list of VNFD monitoring params";
  key "member-vnf-index-ref vnfd-monitoring-param-ref";

  leaf vnfd-id-ref {
    description
      "A reference to a vnfd. This is a
      leafref to path:
      ../../../../nsd:constituent-vnfd
      + [nsd:id = current()/../../nsd:id-ref]
      + /nsd:vnfd-id-ref
      NOTE: An issue with confd is preventing the
      use of xpath. Seems to be an issue with leafref
      to leafref, whose target is in a different module.
      Once that is resolved this will switched to use
      leafref";
    type leafref {
      path "../../../../constituent-vnfd" +
        "[member-vnf-index = current()/../../member-vnf-index-ref]" +
        "/vnfd-id-ref";
    }
  }

  leaf vnfd-monitoring-param-ref {
    description "A reference to the VNFD monitoring param";
    type leafref {
      path "/vnfd:vnfd-catalog/vnfd:vnfd"
        + "[vnfd:id = current()/../../vnfd-id-ref]"
        + "/vnfd:monitoring-param/vnfd:id";
    }
  }

  leaf member-vnf-index-ref {
    description
      "Mandatory reference to member-vnf within constituent-vnfds";
    type leafref {
      path "../../../../constituent-vnfd/member-vnf-index";
    }
  }
}

uses manotypes:input-parameter-xpath;

```

```
list parameter-pool {
  description
    "Pool of parameter values which must be
    pulled from during configuration";
  key "name";

  leaf name {
    description
      "Name of the configuration value pool";
    type string;
  }

  container range {
    description
      "Create a range of values to populate the pool with";

    leaf start-value {
      description
        "Generated pool values start at this value";
      type uint32;
      mandatory true;
    }

    leaf end-value {
      description
        "Generated pool values stop at this value";
      type uint32;
      mandatory true;
    }
  }
}

uses manotypes:ns-service-primitive;

list initial-config-primitive {
  rwpb:msg-new NsdInitialConfigPrimitive;
  description
    "Initial set of configuration primitives for NSD.";
  key "seq";

  uses manotypes:initial-config;
}

list terminate-config-primitive {
  rwpb:msg-new NsdTerminateConfigPrimitive;
  description
    "Set of configuration primitives during
    termination for NSD.";
  key "seq";

  uses manotypes:event-config;
}

uses manotypes:cloud-config;
```

```
}  
  
container nsd-catalog {  
    list nsd {  
        key "id";  
        uses nsd-descriptor;  
    }  
}  
}
```

## Examples

See ["API Examples" on page 369](#)

## nsd:connection-point

A list of references to network service connection points.

Each network service (NS):

- Has one or more external connection points used to link the NS to other NS or to external networks.
- Exposes these connection points to the orchestrator.

The orchestrator can construct network service chains by joining the connection points between different network services.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/connection-point/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the NS external connection point.
type	enum	1	Type of connection point. <b>Supported types:</b> VPORT: Virtual Port

## nsd:vld

### List of Virtual Link Descriptors (VLDs)

Network connections are defined by connection points and virtual links. There are three types of connection points:

- Connect a network service to the outside world, such as the network service endpoint, described in the NSD
- Connect between **VNFs** within a network service, such as the external interface of the VNF, described in the VNFD
- Connect between VMs, described in the **VNFC**

There are also two types of virtual links:

- External virtual links, which can be connected to network service endpoints and external VNF interfaces
- Internal virtual links, which can be connected to external VNF interfaces and VNFCs

Virtual links also follow the Metro Ethernet Forum **E-LINE**, **E-TREE**, and **E-LAN** services. Virtual link descriptors (VLDs) contain the **bandwidth** and **QoS** requirements of the interconnection.

VLDs are required for a functioning NSD.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/vld/STRING

### Fields

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the VLD.
name	string	1	VLD name.
short-name	string	1	<b>NSD</b> short name to use as label in the UI.
vendor	string	1	Provider of the VLD.
description	string	1	Description of the VLD.



ID	Type	Cardinality	Description
version	string	1	Version of the VLD.
type	enum	1	Type of the virtual link.  <b>Supported values:</b> <b>ELAN:</b> A multipoint service connecting a set of VNFs.
root-bandwidth	uint64	1	For ELAN this is the aggregate bandwidth.
leaf-bandwidth	uint64	1	For ELAN this is the bandwidth of branches.
vnfd-connection-point-ref	list	0..n	A list of references to connection points. See <a href="#">"nsd:vnfd-connection-point-ref" on page 74.</a>
provider-network	container	1	Container for the provider network. See <a href="#">"nsd:provider-network " on page 75.</a>
mgmt-network	boolean	1	[Default <i>true</i> ] Denotes whether this network is a <b>VIM</b> management network.
vim-network-name	string		Name of network in VIM account. This field indicates pre-provisioned network name in cloud account.
ip-profile-ref	string	1	Named reference to IP-profile object.

**nsd:vnfd-connection-point-ref**

/nsd:nsd-catalog/nsd/STRING/vld/STRING/vnfd-connection-point-ref/0,STRING

ID	Type	Cardinality	Description
member-vnf-index-ref	reference	1	Reference to member-vnf within constituent units.  This is a leafref to path: ../..../nsd:constituent-vnfd/nsd:member-vnf-index
vnfd-id-ref	string	1	Reference to a VNFD.  This is a leafref to path: ../..../nsd:constituent-vnfd + [nsd:id = current()]/../nsd:id-ref + /nsd:vnfd-id-ref
vnfd-connection-point-ref	string	1	Reference to a connection point name in a VNFD.  This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd + [vnfd:id = current()]/../nsd:vnfd-id-ref + /vnfd:connection-point/vnfd:name

**nsd:provider-network**

/nsd:nsd-catalog/nsd/STRING/vld/STRING/provider-network

ID	Type	Cardinality	Description
physical-network	string	1	Name of the physical network on which the provider network is built.
overlay-type	enum	0..1	<p>Identifies the type of the overlay network, which is a virtual network that is built on top of an existing network and is supported by its infrastructure.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• LOCAL — A network that can be realized on a single host only.</li> <li>• FLAT — The simplest networking environment in which each instance receives a fixed IP from the pool. All instances are attached to the same bridges.</li> <li>• VLAN — A network of computers in which the computers behaves as if they are connected to the same wire. However, the computers might be physically located on different segments of a LAN.</li> <li>• VXLAN — A proposed encapsulation protocol for running an overlay network on existing <b>Layer 3</b> infrastructure</li> <li>• GRE — GRE tunnels encapsulate isolated <b>Layer 2</b> network traffic in IP packets. Packets are routed between compute and networking nodes using the hosts' network connectivity and routing tables.</li> </ul>
segmentation-id	uint32	1	Segmentation ID.

**nsd:constituent-vnfd**

A list of Virtual Network Function Descriptors (VNFDs) that are part of this network service.

**REST URI path**

/nsd:nsd-catalog/nsd/STRING/constituent-vnfd/0

**Fields**

ID	Type	Cardinality	Description
member-vnfd-index	uint64	1	[Required] Identifier/index for the VNFD.  Note: This separate ID is required so that multiple VNFDs can be part of a single network service.
vnfd-id-ref	leafref	1	Identifier for the VNFD. This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id
start-by-default	boolean	1	[Default <i>true</i> ] VNFD is started as part of network service instantiation.

## nsd:config-parameter-map

A mapping of VNF configuration parameter requests and sources within this network service.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/config-parameter-map/STRING

### Fields

ID	Type	Cardinality	Description
id	string	1	Identifier for the VNF map.
config-parameter-request	container	1	See " <a href="#">nsd:config-parameter-request</a> " on page 77.
config-parameter-source	container	1	See " <a href="#">nsd:config-parameter-source</a> " on page 78.

## nsd:config-parameter-request

/nsd:nsd-catalog/nsd/STRING/config-parameter-map/STRING/config-parameter-request

ID	Type	Cardinality	Description
member-vnf-index-ref	leafref	1	Reference to member-vnf within constituent-vnfds.
vnfd-id-ref	leafref	1	A reference to a VNFD. This is a leafref to path: ../..//nsd:constituent-vnfd + [nsd:id = current()../..//nsd:id-ref] + /nsd:vnfd-id-ref

ID	Type	Cardinality	Description
config-parameter-request-ref	leafref	1	Reference to the request in the VNF with the specified member-vnf-index.

### nsd:config-parameter-source

/nsd:nsd-catalog/nsd/STRING/config-parameter-map/STRING/config-parameter-source

ID	Type	Cardinality	Description
member-vnf-index-ref	leafref	1	Reference to member-vnf within constituent-vnfd.
vnfd-id-ref	leafref	1	A reference to a VNFD. This is a leafref to path: ../..//nsd:constituent-vnfd + [nsd:id = current()]/../nsd:id-ref + /nsd:vnfd-id-ref
config-parameter-request-ref	leafref	1	Reference to the source in the VNF with the specified member-vnf-index.

## nsd:scaling-group-descriptor

Scaling group descriptor within this network service. A scaling group defines a group of VNFs and the ratio of VNFs in the network service that is used as the target for scaling action.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/scaling-group-descriptor/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the scaling group.
scaling-policy	list	0..n	List of scaling policy items. See " <a href="#">nsd:scaling-policy</a> " on page 80.
vnfd-member	list	0..n	List of the VNFs in this scaling group. See " <a href="#">nsd:vnfd-member</a> " on page 82.
min-instance-count	uint32	1	[Default 0] Minimum instances of the scaling group allowed in a single network service.  Note: These instances are created by default when the network service is instantiated.
max-instance-count	uint32	1	[Default 10] Maximum instance of this scaling group that are allowed in a single network service.  The network service scaling will fail when the number of service group instances exceeds the max-instance-count specified.
scaling-config-action	list	0..n	List of conditions to be met for generating scaling requests. See " <a href="#">nsd:scaling-config-action</a> " on page 82.

**nsd:scaling-policy**

/nsd:nsd-catalog/nsd/STRING/scaling-group-descriptor/STRING/scaling-policy/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the scaling policy.
scaling-type	enum	1	The scaling type.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• 1 — manual</li> <li>• 2 — automatic</li> </ul>
enabled	boolean	1	[Default <i>true</i> ] Specifies if the scaling policy can be applied.
scale-in-operation-type	enum	1	Operation to apply to check between scaling criteria and verify if the scale-in threshold condition has been met.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• AND [Default]</li> <li>• OR</li> </ul>
scale-out-operation-type	enum	1	Operation to apply to check between scaling criteria and verify if the scale-out threshold condition has been met.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• AND</li> <li>• OR [Default]</li> </ul>
threshold-time	uint32	1	[Required] The duration for which the criteria must hold true.



ID	Type	Cardinality	Description
cooldown-time	uint32	1	[Required] The duration after a scaling-in/scaling-out action has been triggered, for which there will be no further optional
scaling-criteria	list	0..n	List of conditions to be met for generating scaling requests. See " <a href="#">nsd:scaling-criteria</a> " on page 81.

### nsd:scaling-criteria

/nsd:nsd-catalog/nsd/STRING/scaling-group-descriptor/STRING/scaling-policy/STRING/scaling-criteria/STRING

ID	Type	Cardinality	Description
name	string	1	
scale-in-threshold	uint64	1	Value below which scale-in requests are generated.
scale-out-threshold	uint64	1	Value above which scale-in requests are generated.
ns-monitoring-param-ref	leafref	1	Reference to the network service level monitoring parameter that is aggregated. This is a leafref to path: ../..../monitoring-param/id

**nsd:vnfd-member**

/nsd:nsd-catalog/nsd/STRING/scaling-group-descriptor/STRING/vnfd-member/0

ID	Type	Cardinality	Description
member-vnf-index-ref	leafref	1	Member VNF index of this member VNF. This is a leafref to path: ../../constituent-vnfd-member-vnfd-index
count	uint32	1	[Default 1] Count of this member VNF within this scaling group.  Note: Use count to define the number of instances when a scaling action targets this scaling group.

**nsd:scaling-config-action**

/nsd:nsd-catalog/nsd/STRING/scaling-group-descriptor/STRING/scaling-config-action/pre-scale-in

ID	Type	Cardinality	Description
trigger	enum	1	Scaling trigger type.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>1 — pre-scale-in</li> <li>2 — post-scale-in</li> <li>3 — pre-scale-out</li> <li>4 — post-scale-out</li> </ul>
ns-config-primitive-name-ref	leafref	1	Reference to the network service configuration primitive name. This is a leafref to path: ../../service-primitive/name

## nsd:placement-groups

A list of placement groups at the network service level.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/placement-groups/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Place group construct to define the compute resource placement strategy in cloud environment.
requirement	string	1	Describes the intent/rationale behind this placement group. <hr/> <b>Note: This free-text field is for human consumption only</b> <hr/>
strategy	enum	1	Strategy associated with this placement group.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• COLOCATION: [Default] Share the physical infrastructure (hypervisor/network) among all members of this group.</li> <li>• ISOLATION: Do not share the physical infrastructure (hypervisor/network) among the members of this group</li> </ul>
member-vnfd	list	0..n	List of VNFDs that are part of this placement group. See " <a href="#">nsd:member-vnfd</a> " on page 84.

**nsd:member-vnfd**

/nsd:nsd-catalog/nsd/STRING/placement-groups/STRING/member-vnfd/0

ID	Type	Cardinality	Description
member-vnf-index-ref	leafref	1	Member VNF index of this member VNF. This is a leafref to path: ../../constituent-vnfd/member-vnf-index
vnfd-id-ref	leafref	1	Identifier for the VNFD. This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id

## nsd:ip-profiles

List of IP profiles. IP profiles describe the IP characteristics for the virtual link.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/ip-profiles/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the IP profile.
description	string	1	Description of the IP profile.
ip-profile-params	container	1	Information about the IP profile. See " <a href="#">nsd:ip-profile-params</a> " on page 85.

## nsd:ip-profile-params

/nsd:nsd-catalog/nsd/STRING/ip-profiles/STRING/ip-profile-params

ID	Type	Cardinality	Description
ip-version	enum	1	[Default IPv4] Version of the Internet Protocol used.
subnet-address	union	1	Subnet IP prefix associated with this IP profile.
gateway-address	union	1	IP address of the default gateway associated with this IP profile.
security-group	string	1	Name of the security group.
dns-server	list	0..n	List of DNS servers associated with this IP profile. See " <a href="#">nsd:dns-server</a> " on page 86.

ID	Type	Cardinality	Description
dhcp-params	container	1	Container for DHCP parameters. See " <a href="#">nsd:ip-profile-params</a> " on page 85.
subnet-prefix-pool	string	1	VIM-specific reference to pre-created subnet prefix.

### nsd:dns-server

/nsd:nsd-catalog/nsd/STRING/ip-profiles/STRING/ip-profile-params/dns-server/UNION\_VALUE

ID	Type	Cardinality	Description
address	union	1	List of DNS servers associated with this IP profile.

### nsd:dhcp-params

/nsd:nsd-catalog/nsd/STRING/ip-profiles/STRING/ip-profile-params/dhcp-params

ID	Type	Cardinality	Description
enabled	boolean	1	[Default <i>true</i> ] Indicates if DHCP is enabled.
start-address	union	1	Start IP address of the IP address range associated with DHCP domain.
count	uint32	1	Size of the DHCP pool associated with DHCP domain.

### nsd:vnf-dependency

List of VNF dependencies in the Network Service Descriptor.

#### REST URI path

/nsd:nsd-catalog/nsd/STRING/vnf-dependency/STRING

**Fields**

ID	Type	Cardinality	Description
vnf-dependency	leafref	1	List of VNF dependencies. This is a leafref to path: ../ ../vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id
vnf-dependson-ref	leafref	1	Reference to VNFD that on which the source VNF depends. This is a leafref to path: ../ ../vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id

## nsd:vnffgd

List of VNF Forwarding Graph Descriptors.

A Virtual Network Function Forwarding Graph (VNFFG) is a graph, specified by a Network Service Provider, of bi-directional logical links that connect network function nodes, where at least one node is a VNF through which network traffic is directed.

The VNFFG descriptor contains metadata about the VNF forwarding graph itself, as well as references to VNs, VNFs and PNFs, and network forwarding path elements. These elements include policies, such as MAC forwarding rules and routing entries, and references to connection points, such as virtual ports and virtual NIC addresses.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/vnffgd/STRING

### Fields

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the VNFFGD.
name	string	1	VNFFGD name.
short-name	string	1	VNFFGD short name to use as label in the UI.
vendor	string	1	Provider of the VNFFGD.
description	string	1	Description of the VNFFGD.
version	string	1	Version of the VNFFGD.
rsp	list	0..n	List of the Rendered Service Paths (RSP) for the VNFFGD. See " <a href="#">nsd:rsp</a> " on page 89
classifier	list	0..n	List of classifier rules for the VNFFGD. See " <a href="#">nsd:classifier</a> " on page 90.



**nsd:rsp**

/nsd:nsd-catalog/nsd/STRING/vnffgd/STRING/rsp/STRING

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the RSP.
name	string	1	RSP name.
vnfd-connection-point-ref	list	0..n	A list of references to connection points. See " <a href="#">nsd:vnfd-connection-point-ref</a> " on page 89.

**nsd:vnfd-connection-point-ref**

/nsd:nsd-catalog/nsd/STRING/vnffgd/STRING/rsp/STRING/vnfd-connection-point-ref/0,STRING

ID	Type	Cardinality	Description
member-vnf-index-ref	leafref	1	Reference to member VNF within constituent VNFDs.  This is a leafref to path: ../..../nsd:constituent-vnfd-nsd_member-vnf-index
order	uint8	1	A number that denotes the VNF in a chain.
vnfd-id-ref	leafref	1	A reference to a VNFD.  This is a leafref to path: ../..../nsd:constituent-vnfd + [nsd:id = current()/../nsd:id-ref] + /nsd:vnfd-id-ref

ID	Type	Cardinality	Description
vnfd-connection-point-ref	leafref	1	A reference to a connection point name in a VNFD. This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd + [vnfd:id = current()/../nsd:vnfd-id-ref] + /vnfd:connection-point/vnfd:name

**nsd:classifier**

/nsd:nsd-catalog/nsd/STRING/vnffgd/STRING/classifier/STRING

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the classifier rule.
name	string	1	Name of the classifier.
rsp-id-ref	leafref	1	A reference to the RSP. This is a leafref to path: ../..//nsd:rsp/nsd:id
member-vnf-index-ref	leafref	1	Reference to member-vnf within constituent-vndfs. This is a leafref to path: ../..//nsd:constituent-vnfd/nsd:member-vnf-index

ID	Type	Cardinality	Description
vnfd-id-ref	leafref	1	A reference to a VNFD. This is a leafref to path: ../..../nsd:constituent-vnfd + [nsd:id = current()../nsd:id-ref] + /nsd:vnfd-id-ref
vnfd-connection-point-ref	leafref	1	A reference to a connection point name in a VNFD. This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd + [vnfd:id = current()../nsd:vnfd-id-ref] + /vnfd:connection-point/vnfd:name
match-attributes	list	0..n	List of match attributes. See " <a href="#">nsd:match-attributes</a> " on page 91

### nsd:match-attributes

/nsd:nsd-catalog/nsd/STRING/vnffgd/STRING/classifier/STRING/match-attributes/STRING

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the classifier match-attribute rule.
ip-proto	uint8	1	IP protocol.
source-ip-address	union	1	Source IP address.

ID	Type	Cardinality	Description
destination-ip-address	union	1	Destination IP address.
source-port	uint16	1	Source port number.
destination-port	uint16	1	Destination port number.

## nsd:monitoring-param

List of monitoring parameters from VNFs to propagate to the Network Service Record (NSR).

### REST URI path

/nsd:nsd-catalog/nsd/STRING/monitoring-param/STRING

### Fields

ID	Type	Cardinality	Description
id	string	1	Identifier for the parameter.
name	string	1	Name of the monitoring parameter
value-type	enum	1	The type of the parameter value.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• INT (default)</li> <li>• DECIMAL</li> <li>• STRING</li> </ul>
value-type	enum	1	The type of the parameter value.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• INT (default)</li> <li>• DECIMAL</li> <li>• STRING</li> </ul>
numeric-constraints	container	1	Constraints for the numbers.  See <a href="#">"nsd:numeric-constraints" on page 95</a> .
text-constraints	container	1	Constraints for the string.  See <a href="#">"nsd:text-constraints" on page 95</a> .

ID	Type	Cardinality	Description
value-integer	int64	1	Current value for integer parameter.
value-decimal	decimal164	1	Current value for decimal parameter.
value-string	string	1	Current value for the string parameter.
description	string	1	
group-tag	string	1	A simple tag to group monitoring parameters
widget-type	enum	1	Type of the widget, typically used by the UI.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• HISTOGRAM</li> <li>• BAR</li> <li>• GAUGE</li> <li>• SLIDER</li> <li>• COUNTER</li> <li>• TEXTBOX</li> </ul>
aggregation-type	enum	1	Aggregation type for the monitoring parameter.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• AVERAGE</li> <li>• MINIMUM</li> <li>• MAXIMUM</li> <li>• COUNT</li> <li>• SUM</li> </ul>

ID	Type	Cardinality	Description
vnfd-monitoring-param	list	0..n	A list of VNFD monitoring parameters. See " <a href="#">nsd:vnfd-monitoring-param</a> " on page 96.

### nsd:numeric-constraints

/nsd:nsd-catalog/nsd/STRING/monitoring-param/STRING/numeric-constraints

ID	Type	Cardinality	Description
min-value	uint64	1	Minimum value for the parameter.
max-value	uint64	1	Maximum value for the parameter.

### nsd:text-constraints

/nsd:nsd-catalog/nsd/STRING/monitoring-param/STRING/text-constraints

ID	Type	Cardinality	Description
min-length	uint8	1	Minimum string length for the parameter.
max-length	uint8	1	Maximum string length for the parameter.

**nsd:vnfd-monitoring-param**

/nsd:nsd-catalog/nsd/STRING/monitoring-param/STRING/vnfd-monitoring-param/0,STRING

ID	Type	Cardinality	Description
vnfd-id-ref	leafref	1	A reference to a VNFD. This is a leafref to path: ../..../nsd:constituent-vnfd + [nsd:id = current()../nsd:id-ref] + /nsd:vnfd-id-ref
vnfd-monitoring-param-ref	leafref	1	A reference to the VNFD monitoring parameter. This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd + [vnfd:id = current()../vnfd-id-ref] + /vnfd:monitoring-param/vnfd:id
member-vnf-index-ref	leafref	1	Optional reference to member-vnf within constituent-vnfds.



## nsd:input-parameter-xpath

List of XPath to parameters inside the Network Service Descriptor that can be customized during instantiation.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/input-parameter-xpath/STRING

### Fields

ID	Type	Cardinality	Description
xpath	string	1	An xpath that specifies the element in a descriptor.
label	string	1	A descriptive string.
default-value	string	1	A default value for this input parameter.

**nsd:parameter-pool**

Pool of parameter values from which to pull during configuration.

**REST URI path**

/nsd:nsd-catalog/nsd/STRING/parameter-pool/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the configuration value pool.
range	container	1	Create a range of values from which to populate the pool. See " <a href="#">nsd:range</a> " on page 98.

**nsd:range**

/nsd:nsd-catalog/nsd/STRING/parameter-pool/STRING/range

ID	Type	Cardinality	Description
start-value	uint32	1	[Required] Generated pool values start at this value.
end-value	uint32	1	[Required] Generated pool values end at this value.

## nsd:service-primitive

Network service-level service primitives for the Network Service Descriptor.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/service-primitive/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the service primitive.
parameter	list	0..n	List of parameters for the service primitive. See " <a href="#">nsd:parameter</a> " on page 99.
parameter-group	list	0..n	Grouping of parameters that are logically grouped in UI. See " <a href="#">nsd:parameter-group</a> " on page 100.
vnf-primitive-group	list	0..n	List of service primitives grouped by the VNF. See " <a href="#">nsd:vnf-primitive-group</a> " on page 102.
used-defined-script	string	1	A user-defined script.

## nsd:parameter

/nsd:nsd-catalog/nsd/STRING/service-primitive/STRING/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of parameter.

ID	Type	Cardinality	Description
data-type	enum	1	Data type associated with the name.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• STRING</li> <li>• INTEGER</li> <li>• BOOLEAN</li> </ul>
mandatory	boolean	1	[Default is <i>false</i> ] Specifies whether this field is mandatory.
default-value	string	1	The default value for the field.
parameter-pool	string	1	NSD parameter pool name to use for this parameter.
read-only	boolean	1	The value should be dimmed by the UI. Applies only to parameters with default values.
hidden	boolean	1	The value should be hidden by the UI. Applies only to parameters with default values
out	boolean	1	[Default is <i>false</i> ] Specifies if this is an output of the primitive execution

### nsd:parameter-group

/nsd:nsd-catalog/nsd/STRING/service-primitive/STRING/parameter-group/STRING

ID	Type	Cardinality	Description
name	string	1	Name of parameter group.

ID	Type	Cardinality	Description
parameter	list	0..n	List of parameters to the service primitive. See " <a href="#">nsd:parameter-group:parameter</a> " on page 101.
mandatory	boolean	1	[Default <i>true</i> ] Specifies whether this group mandatory.

### nsd:parameter-group:parameter

/nsd:nsd-catalog/nsd/STRING/service-primitive/STRING/parameter-group/STRING/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of parameter.
data-type	enum	1	Data type associated with the name. <b>Supported values:</b> <ul style="list-style-type: none"> <li>• STRING</li> <li>• INTEGER</li> <li>• BOOLEAN</li> </ul>
mandatory	boolean	1	[Default is <i>false</i> ] Specifies whether this field is mandatory.
default-value	string	1	The default value for the field.
parameter-pool	string	1	NSD parameter pool name to use for this parameter.
read-only	boolean	1	The value should be dimmed by the UI. Applies only to parameters with default values.

ID	Type	Cardinality	Description
hidden	boolean	1	The value should be hidden by the UI. Applies only to parameters with default values
out	boolean	1	[Default is <i>false</i> ] Specifies if this is an output of the primitive execution

### nsd:vnf-primitive-group

/nsd:nsd-catalog/nsd/STRING/service-primitive/STRING/vnf-primitive-group/0

ID	Type	Cardinality	Description
member-vnf-index-ref	uint64	1	Reference to member-vnf within constituent-vnfs.
vnfd-id-ref	string	1	A reference to a VNFD. This is a leafref to path: ../..../nsd:constituent-vnfd + [nsd:id = current()/../nsd:id-ref] + /nsd:vnfd-id-ref
vnfd-name	string	1	Name of the VNFD.
primitive	list	1	A list of VNF primitives. See " <a href="#">nsd:vnf-primitive-group:primitive</a> " on page 103

**nsd:vnf-primitive-group:primitive**

/nsd:nsd-catalog/nsd/STRING/service-primitive/STRING/vnf-primitive-group/0/primitive/0

ID	Type	Cardinality	Description
index	uint32	1	Index of this primitive.
name	string	1	Name of the primitive in the VNF primitive.

## nsd:initial-config-primitive

Initial set of configuration primitives for the NSD, that are to be executed when the network service comes up.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/initial-config-primitive/0

### Fields

ID	Type	Cardinality	Description
seq	uint64	1	Sequence number for the configuration primitive.
name	string	1	[Required] Name of the configuration primitive.
user-defined-script	string	1	A user-defined script.
parameter	list	0..n	List of parameters to the initial-config-primitive. See " <a href="#">nsd:parameter</a> " on page 104.

## nsd:parameter

/nsd:nsd-catalog/nsd/STRING/initial-config-primitive/0/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the parameter.
value	string	1	Value of the parameter.



## nsd:terminate-config-primitive

Set of configuration primitives to be executed before tearing down the network service.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/terminate-config-primitive/0

### Fields

ID	Type	Cardinality	Description
seq	uint64	1	Sequence number for the configuration primitive.
name	string	1	[Required] Name of the configuration primitive.
user-defined-script	string	1	A user-defined script.
parameter	list	0..n	List of parameters to the primitive. See " <a href="#">nsd:parameter</a> " on page 105.

## nsd:parameter

/nsd:nsd-catalog/nsd/STRING/terminate-config-primitive/0/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the parameter.
value	string	1	Value of the parameter.

## nsd:key-pair

Used to configure the list of public keys to be injected as part of network service instantiation.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/key-pair/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of this key pair.
key	string	1	Key associated with this key pair.

## nsd:user

List of users to be added through cloud-config.

### REST URI path

/nsd:nsd-catalog/nsd/STRING/user/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the user.
user-info	string	1	The user name's real name.
key-pair	string	1	Used to configure the list of public keys to be injected as part of network service instantiation. See " <a href="#">nsd:key-pair</a> " on page 107.

## nsd:key-pair

/nsd:nsd-catalog/nsd/STRING/user/STRING/key-pair/STRING

ID	Type	Cardinality	Description
name	string	1	Name of this key pair.
key	string	1	Key associated with this key pair.

## NS Lifecycle Management (nsr:nsd)

REST wrapper for network service lifecycle management (nsr:ns-instance-config). Provides methods for instantiating, updating, finding, and terminating a network service (NS). Also provides methods for creating, updating, listing, and deleting or VNF forwarding graph (VNFFG).

### Methods and relative URLs

Method	Relative URL	Description
POST	/api/running/ns-instance-config	Instantiate a network service
PUT	/api/running/ns-instance-config/{UUID}	Update a network service
GET	/api/running/ns-instance-config/{UUID}	Query a network service
GET	/api/running/ns-instance-config	Retrieve a list of all network instances saved to the catalog
DELETE	/api/running/ns-instance-config/nsr{UUID}	Terminate a network service record

### Fields

ID	Type	Cardinality	Description
id	string	1	Identifier of the network service record (NSR).
name	string	1	NSR name.
short-name	string	1	NSR short name (for display on UI).

ID	Type	Cardinality	Description
description	string	1	Description of the NSR.
admin-status	enum	1	Administrative status of the NS instance. Value can be: <ul style="list-style-type: none"> <li>ENABLED (default)</li> <li>DISABLED</li> </ul>
nsd	container	1	Network service descriptor used to instantiate this network service. See <a href="#">"nsr:nsd" on page 122.</a>
input-parameter	list	0..n	List of XPath input parameters. See <a href="#">"nsr:input-parameter" on page 163.</a>
scaling-group	list	0..n	List of network service scaling group instances. See <a href="#">"nsr:scaling-group" on page 164.</a>
nsd-placement-group-maps	list	0..n	Mapping from mano-placement groups construct from NSD to cloud platform placement group construct. See <a href="#">"nsr:nsd-placement-group-maps" on page 165.</a>
vnfd-placement-group-maps	list	0..n	Mapping from mano-placement groups construct from VNFD to cloud platform placement group construct. See <a href="#">"nsr:vnfd-placement-group-maps" on page 168.</a>
ssh-authorized-key	list	0..n	List of authorized ssh keys as part of cloud-config. See <a href="#">"nsr:ssh-authorized-key" on page 171.</a>

ID	Type	Cardinality	Description
user	list	0..n	List of users to be added through cloud-config. See " <a href="#">nsr:user</a> " on page 172.

## MANO reference points

Os-Ma-nfvo

### Schema

```
module nsr
{
  namespace "urn:ietf:params:xml:ns:yang:nfvo:nsr";
  prefix "nsr";

  import rw-pb-ext {
    prefix "rwpb";
  }

  import vlr {
    prefix "vlr";
  }

  import vld {
    prefix "vld";
  }

  import nsd {
    prefix "nsd";
  }

  import vnfd {
    prefix "vnfd";
  }

  import vnfr {
    prefix "vnfr";
  }

  import ietf-inet-types {
    prefix "inet";
  }

  import ietf-yang-types {
    prefix "yang";
  }

  import mano-types {
    prefix "manotypes";
  }
}
```

```
}

import rw-sdn {
  prefix "rwsdn";
}

revision 2015-09-10 {
  description
    "Initial revision. This YANG file defines
    the Network Service Record (NSR)";
  reference
    "Derived from earlier versions of base YANG files";
}

typedef config-states {
  type enumeration {
    enum init;
    enum configuring;
    enum config_not_needed;
    enum configured;
    enum failed;
    enum terminate;
  }
}

typedef trigger-type {
  type enumeration {
    enum ns-primitive;
    enum vnf-primitive;
  }
}

grouping cloud-config {
  description "List of cloud config parameters";

  list ssh-authorized-key {
    key "key-pair-ref";

    description "List of authorized ssh keys as part of cloud-config";

    leaf key-pair-ref {
      description "A reference to the key pair entry in the global key
pair table";
      type leafref {
        path "/nsr:key-pair/nsr:name";
      }
    }
  }
  list user {
    key "name";

    description "List of users to be added through cloud-config";
    leaf name {
      description "Name of the user ";
      type string;
    }
  }
}
```

```
leaf user-info {
  description "The user name's real name";
  type string;
}
list ssh-authorized-key {
  key "key-pair-ref";

  description "Used to configure the list of public keys to be
injected as part
                of ns instantiation";

  leaf key-pair-ref {
    description "A reference to the key pair entry in the global key
pair table";
    type leafref {
      path "/nsr:key-pair/nsr:name";
    }
  }
}

list key-pair {
  key "name";
  description "Used to configure the list of public keys to be injected as
part
                of ns instantiation";
  leaf name {
    description "Name of this key pair";
    type string;
  }

  leaf key {
    description "Key associated with this key pair";
    type string;
  }
}

grouping event-config-primitive {
  leaf seq {
    description
      "Sequence number for the configuration primitive.";
    type uint64;
  }

  leaf name {
    description
      "Name of the configuration primitive.";
    type string;
    mandatory "true";
  }

  leaf user-defined-script {
    description
      "A user defined script.";
    type string;
  }
}
```



```
}

list parameter {
  key "name";
  leaf name {
    type string;
  }

  leaf value {
    type string;
  }
}

rpc start-network-service {
  description "Start the network service";
  input {
    leaf name {
      mandatory true;
      description "Name of the Network Service";
      type string;
    }
    leaf nsd-ref {
      description "Reference to NSR ID ref";
      mandatory true;
      type leafref {
        path "/nsd:nsd-catalog/nsd:nsd/nsd:id";
      }
    }
    uses ns-instance-config-params;
  }

  output {
    leaf nsr-id {
      description "Automatically generated parameter";
      type yang:uuid;
    }
  }
}

container ns-instance-config {

  list nsr {
    key "id";
    unique "name";

    leaf id {
      description "Identifier for the NSR.";
      type yang:uuid;
    }

    leaf name {
      description "NSR name.";
      type string;
    }
  }
}
```

```
    }

    leaf short-name {
      description "NSR short name.";
      type string;
    }

    leaf description {
      description "NSR description.";
      type string;
    }

    leaf admin-status {
      description
        "This is the administrative status of the NS instance";

      type enumeration {
        enum ENABLED;
        enum DISABLED;
      }
    }

    container nsd {
      description "NS descriptor used to instantiate this NS";
      uses nsd:nsd-descriptor;
    }

    uses ns-instance-config-params;
  }
}

grouping ns-instance-config-params {
  uses manotypes:input-parameter;

  list scaling-group {
    description "List of ns scaling group instances";
    key "scaling-group-name-ref";

    leaf scaling-group-name-ref {
      description "name of the scaling group";
      leafref path ../nsd/scaling-group-descriptor/name";
      type string;
    }
  }

  list instance {
    description "The instance of the scaling group";
    key "id";
    leaf id {
      description "Scaling group instance uuid";
      type uint16;
    }
  }
}

list nsd-placement-group-maps {
  description
```

```

        "Mapping from mano-placement groups construct from NSD to cloud
        platform placement group construct";

    key "placement-group-ref";

    leaf placement-group-ref {
        description
            "Reference for NSD placement group";
        // type leafref {
        //     path "../..//nsd/placement-groups/name";
        // }
        type string;
    }
    uses manotypes:placement-group-input;
}

list vnfd-placement-group-maps {
    description
        "Mapping from mano-placement groups construct from VNFD to cloud
        platform placement group construct";

    key "placement-group-ref vnfd-id-ref";

    leaf vnfd-id-ref {
        description
            "A reference to a vnfd. This is a
            leafref to path:
            ../../../../nsd:constituent-vnfd
            + [nsr:id = current()../../nsd:id-ref]
            + /nsd:vnfd-id-ref
            NOTE: An issue with confd is preventing the
            use of xpath. Seems to be an issue with leafref
            to leafref, whose target is in a different module.
            Once that is resolved this will be switched to use
            leafref";
        type yang:uuid;
    }

    leaf placement-group-ref {
        description
            "A reference to VNFD placement group";
        type leafref {
            path "/vnfd:vnfd-catalog/vnfd:vnfd[vnfd:id = current()/" +
                "../nsr:vnfd-id-ref]/vnfd:placement-groups/vnfd:name";
        }
    }

    uses manotypes:placement-group-input;
}

uses cloud-config;
}

grouping vnffgr {

    list vnffgr {

```

```

key "id";

leaf id {
  description "Identifier for the VNFFGR.";
  type yang:uuid;
}

leaf vnffgd-id-ref {
  description "VNFFG descriptor id reference";
  type leafref {
    path "/nsr:ns-instance-config/nsr:nsr"
      + "[nsr:id=current()/../../../../ns-instance-config-ref]"
      + "/nsr:nsd/nsr:vnffgd/nsr:id";
  }
}

leaf vnffgd-name-ref {
  description "VNFFG descriptor name reference";
  type leafref {
    path "/ns-instance-config/nsr"
      + "[id=current()/../../../../ns-instance-config-ref]"
      + "/nsd/vnffgd[nsr:id = current()/../vnffgd-id-ref]"
      + "/name";
  }
}

leaf sdn-account {
  description
    "The SDN account to use when requesting resources for
    this vnffgr";
  type leafref {
    path "/rwsdn:sdn/rwsdn:account/rwsdn:name";
  }
}

leaf cloud-account {
  description "Cloud Account in which NSR is instantiated";
  type string;
}

leaf operational-status {
  description
    "The operational status of the VNFFGR instance
    init           : The VNFFGR has just started.
    running        : The VNFFGR is in running state.
    terminate      : The VNFFGR is being terminated.
    terminated     : The VNFFGR is in the terminated state.
    failed         : The VNFFGR instantiation failed
    ";

  type enumeration {
    rwpb:enum-type "VnffgrOperationalStatus";
    enum init;
    enum running;
    enum terminate;
    enum terminated;
  }
}

```

```

    enum failed;
  }
}

list rsp {
  key "id";

  leaf id {
    description
      "Identifier for the RSP.";
    type yang:uuid;
  }

  leaf name {
    description
      "Name for the RSP";
    type string;
  }

  leaf rsp-id {
    description
      "Returned Identifier for the RSP.";
    type yang:uuid;
  }

  leaf vnffgd-rsp-id-ref {
    description
      "Identifier for the VNFFGD Descriptor RSP reference";
    type leafref {
      path "/ns-instance-config/nsr"
        + "[id=current()/../../../../ns-instance-config-ref]"
        + "/nsd/vnffgd"
        + "[id=current()/../../../../vnffgd-id-ref]"
        + "/rsp/id";
    }
  }

  leaf vnffgd-rsp-name-ref {
    description
      "Name for the VNFFGD Descriptor RSP reference";
    type leafref {
      path "/ns-instance-config/nsr:nsr"
        + "[id=current()/../../../../ns-instance-config-ref]"
        + "/nsd/vnffgd"
        + "[id=current()/../../../../vnffgd-id-ref]"
        + "/rsp[id=current()/../../vnffgd-rsp-id-ref]"
        + "/name";
    }
  }

  leaf classifier-name {
    type string;
  }

  leaf path-id {
    description

```

```

        "Unique Identifier for the service path";
        type uint32;
    }

    list vnfr-connection-point-ref {
        key "hop-number";
        leaf hop-number {
            description
                "Monotonically increasing number to show service path hop
                order";
            type uint8;
        }
        leaf service-function-type {
            description
                "Type of Service Function.
                NOTE: This needs to map with Service Function Type in ODL to
                support VNFFG. Service Function Type is mandatory param in
                SFC. This is temporarily set to string for ease of use";
            type string;
        }

        leaf member-vnf-index-ref {
            type uint64;
        }
        leaf vnfd-id-ref {
            description
                "Reference to VNF Descriptor Id";
            type string;
        }
        leaf vnfr-id-ref {
            description
                "A reference to a vnfr id";
            type leafref {
                path "/vnfr:vnfr-catalog/vnfr:vnfr/vnfr:id";
            }
        }
        leaf vnfr-name-ref {
            description
                "A reference to a vnfr name";
            type leafref {
                path "/vnfr:vnfr-catalog/vnfr:vnfr/vnfr:name";
            }
        }
        leaf vnfr-connection-point-ref {
            description
                "A reference to a vnfr connection point.";
            type leafref {
                path "/vnfr:vnfr-catalog/vnfr:vnfr"
                    + "[vnfr:id = current()/../nsr:vnfr-id-ref]"
                    + "/vnfr:connection-point/vnfr:name";
            }
        }
        leaf service-index {
            description
                "Location within the service path";

```

```
    type uint8;
  }
  container connection-point-params {
    leaf mgmt-address {
      type inet:ip-address;
    }
    leaf name {
      type string;
    }
    leaf port-id {
      rwpb:field-inline "true";
      rwpb:field-string-max 64;
      type string;
    }
    leaf vm-id {
      rwpb:field-inline "true";
      rwpb:field-string-max 64;
      type string;
    }
    leaf address {
      type inet:ip-address;
    }
    leaf port {
      type inet:port-number;
    }
  }
}

container service-function-forwarder {
  leaf name {
    description
      "Service Function Forwarder name";
    type string;
  }
  leaf ip-address {
    description
      "Data Plane IP Address of the SFF";
    type inet:ip-address;
  }
  leaf port {
    description
      "Data Plane Port of the SFF";
    type inet:port-number;
  }
}
}
}

list classifier {
  key "id";

  leaf id {
    description
      "Identifier for the classifier rule.";
    type yang:uuid;
  }
  leaf name {
```

```
    description
      "Name of the classifier.";
    type string;
  }
  leaf-list classifier-id {
    description
      "Returned Identifier for the classifier rule.";
    type yang:uuid;
  }
  leaf rsp-id-ref {
    description
      "A reference to the RSP.";
    type leafref {
      path "../..//nsr:rsp/nsr:id";
    }
  }
  leaf rsp-name {
    description
      "Name for the RSP";
    type string;
  }
  leaf vnfr-id-ref {
    description
      "A reference to a vnfr id";
    type leafref {
      path "/vnfr:vnfr-catalog/vnfr:vnfr/vnfr:id";
    }
  }
  leaf vnfr-name-ref {
    description
      "A reference to a vnfr name";
    type leafref {
      path "/vnfr:vnfr-catalog/vnfr:vnfr/vnfr:name";
    }
  }
  leaf vnfr-connection-point-ref {
    description
      "A reference to a vnfr connection point.";
    type leafref {
      path "/vnfr:vnfr-catalog/vnfr:vnfr"
        + "[vnfr:id = current()../../nsr:vnfr-id-ref]"
        + "/vnfr:connection-point/vnfr:name";
    }
  }
  leaf port-id {
    rwpb:field-inline "true";
    rwpb:field-string-max 64;
    type string;
  }
  leaf vm-id {
    rwpb:field-inline "true";
    rwpb:field-string-max 64;
    type string;
  }
  leaf ip-address {
    type string;
  }
```



```
    }  
    leaf sff-name {  
      type string;  
    }  
  }  
}
```

## Examples

See ["API Examples" on page 369](#)

**nsr:nsd**

Network service descriptor (NSD) used to instantiate this network service (NS).

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd

**Fields**

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the NSD.
name	string	1	NSD name.
short-name	string	1	NSD short name to use as a label in the UI.
vendor	string	1	Vendor of the NSD.
logo	string	1	<p>File path of the vendor-specific logo. For example, icons/mylogo.png</p> <p>The logo should be part of the network service package.</p> <p>SVG format is preferred, but PNG is supported.</p> <p>Although there is no hard limit on size and dimension, a square image under 200px by 200px is preferred.</p>
description	string	1	Description of the NSD.
version	string	1	Version of the NSD.
connection-point	list	0..n	<p>A list of references to network service connection points.</p> <p>See "<a href="#">nsr:connection-point</a>" on page 125.</p>

ID	Type	Cardinality	Description
vld	list	0..n	List of Virtual Link Descriptors (VLDs). See <a href="#">"nsr:vld" on page 126.</a>
constituent-vnfd	list	0..n	List of Virtual Network Function Descriptors (VNFDs) that are part of this network service. See <a href="#">"nsr:constituent-vnfd" on page 130.</a>
config-parameter-map	list	0..n	A mapping of VNF configuration parameter requests and sources within this network service. See <a href="#">"nsr:config-parameter-map" on page 131.</a>
scaling-group-descriptor	list	0..n	Scaling group descriptor within this network service. See <a href="#">"nsr:scaling-group-descriptor" on page 134.</a>
placement-groups	list	0..n	List of placement groups at the NS level. See <a href="#">"nsr:placement-groups" on page 138.</a>
ip-profiles-list	list	0..n	List of IP profiles. See <a href="#">"nsr:ip-profiles" on page 140.</a>
vnf-dependency	list	0..n	List of VNF dependencies. See <a href="#">"nsr:vnf-dependency" on page 142.</a>
vnffgd	list	0..n	List of VNF forwarding graph descriptor (VNFFGD). See <a href="#">"nsr:vnffgd" on page 143.</a>
monitoring-param	list	0..n	List of monitoring parameters at the network service level. See <a href="#">"nsr:monitoring-param" on page 148.</a>

ID	Type	Cardinality	Description
input-parameter-xpath	list	0..n	List of XPath to parameters inside the NSD that can be customized during instantiation. See " <a href="#">nsr:input-parameter-xpath</a> " on page 152
parameter-pool	list	0..n	Pool of parameter values that must be pulled from during configuration. See " <a href="#">nsr:parameter-pool</a> " on page 153.
service-primitive	list	0..n	Network service level configuration primitives. See " <a href="#">nsr:service-primitive</a> " on page 154.
initial-config-primitive	list	0..n	Set of configuration primitives to be executed when the network service comes up. See " <a href="#">nsr:initial-config-primitive</a> " on page 159
terminate-config-primitive	list	0..n	Set of configuration primitives to be executed before during termination of the network service. See " <a href="#">nsr:terminate-config-primitive</a> " on page 160.
key-pair	list	0..n	Used to configure the list of public keys to be injected as part of network service instantiation. See " <a href="#">nsr:key-pair</a> " on page 161.
<a href="#">user</a>	list	0..n	List of users to be added through cloud-config. See " <a href="#">nsr:user</a> " on page 162.

## nsr:connection-point

A list of references to network service connection points.

Each network service (NS):

- Has one or more external connection points used to link the NS to other NS or to external networks.
- Exposes these connection points to the orchestrator.

The orchestrator can construct network service chains by joining the connection points between different network services.

### REST URI path

/nsr:ns-instance-config/nsr/STRING/nsd/connection-point/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the NS external connection point.
type	enum	1	Type of connection point. <b>Supported types:</b> VPORT: Virtual Port

**nsr:vld**

## List of Virtual Link Descriptors (VLDs)

Network connections are defined by connection points and virtual links. There are three types of connection points:

- Connect a network service to the outside world, such as the network service endpoint, described in the NSD
- Connect between **VNFs** within a network service, such as the external interface of the VNF, described in the VNFD
- Connect between VMs, described in the **VNFC**

There are also two types of virtual links:

- External virtual links, which can be connected to network service endpoints and external VNF interfaces
- Internal virtual links, which can be connected to external VNF interfaces and VNFCs

Virtual links also follow the Metro Ethernet Forum E-LINE, E-TREE, and E-LAN services. Virtual link descriptors (VLDs) contain the bandwidth and QoS requirements of the interconnection.

VLDs are required for a functioning NSD.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/vld/STRING

**Fields**

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the VLD.
name	string	1	VLD name.
short-name	string	1	NSD short name to use as label in the UI.
vendor	string	1	Provider of the VLD.
description	string	1	Description of the VLD.

ID	Type	Cardinality	Description
version	string	1	Version of the VLD.
type	enum	1	Type of the virtual link.  <b>Supported values:</b> ELAN: A multipoint service connecting a set of VNFs.
root-bandwidth	uint64	1	For ELAN this is the aggregate bandwidth.
leaf-bandwidth	uint64	1	For ELAN this is the bandwidth of branches.
vnfd-connection-point-ref	list	0..n	A list of references to connection points. See <a href="#">"nsr:vnfd-connection-point-ref" on page 128.</a>
provider-network	container	1	Container for the provider network. See <a href="#">"nsr:provider-network " on page 129.</a>
mgmt-network	boolean	1	[Default <i>true</i> ] Denotes whether this network is a VIM management network.
vim-network-name	string		Name of network in VIM account. This field indicates pre-provisioned network name in cloud account.
ip-profile-ref	string	1	Named reference to IP-profile object.

**nsr:vnfd-connection-point-ref**

/nsr:ns-instance-config/nsr/STRING/nsd/vld/STRING/vnfd-connection-point-ref/0,STRING

ID	Type	Cardinality	Description
member-vnf-index-ref	reference	1	Reference to member-vnf within constituent units.  This is a leafref to path:  ../..../nsd:constituent-vndf/nsd:member-vnf-index
vnfd-id-ref	string	1	Reference to a VNFD.  This is a leafref to path:  ../..../nsd:constituent-vnfd + [nsd:id = current()]/../nsd:id-ref + /nsd:vnfd-id-ref
vnfd-connection-point-ref	string	1	Reference to a connection point name in a VNFD.  This is a leafref to path:  /vnfd:vnfd-catalog/vnfd:vnfd + [vnfd:id = current()]/../nsd:vnfd-id-ref + /vnfd:connection-point/vnfd:name



**nsr:provider-network**

/nsr:ns-instance-config/nsr/STRING/nsd/vld/STRING/provider-network

ID	Type	Cardinality	Description
physical-network	string	1	Name of the physical network on which the provider network is built.
overlay-type	enum	0..1	<p>Identifies the type of the overlay network, which is a virtual network that is built on top of an existing network and is supported by its infrastructure.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• LOCAL — A network that can be realized on a single host only.</li> <li>• FLAT — The simplest networking environment in which each instance receives a fixed IP from the pool. All instances are attached to the same bridges.</li> <li>• VLAN — A network of computers in which the computers behaves as if they are connected to the same wire. However, the computers might be physically located on different segments of a LAN.</li> <li>• VXLAN — A proposed encapsulation protocol for running an overlay network on existing Layer 3 infrastructure</li> <li>• GRE — GRE tunnels encapsulate isolated Layer 2 network traffic in IP packets. Packets are routed between compute and networking nodes using the hosts' network connectivity and routing tables.</li> </ul>
segmentation-id	uint32	1	Segmentation ID.

**nsr:constituent-vnfd**

A list of Virtual Network Function Descriptors (VNFDs) that are part of this network service.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/constituent-vnfd/0

**Fields**

ID	Type	Cardinality	Description
member-vnfd-index	uint64	1	<p>[Required] Identifier/index for the VNFD.</p> <p>.....</p> <p>Note: This separate ID is required so that multiple VNFs can be part of a single network service.</p> <p>.....</p>
vnfd-id-ref	leafref	1	<p>Identifier for the VNFD.</p> <p>This is a leafref to path:</p> <p>/vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id</p>
start-by-default	boolean	1	<p>[Default <i>true</i>] VNFD is started as part of network service instantiation.</p>

## nsr:config-parameter-map

A mapping of VNF configuration parameter requests and sources within this network service.

### REST URI path

/nsr:ns-instance-config/nsr/STRING/nsd/config-parameter-map/STRING

### Fields

ID	Type	Cardinality	Description
id	string	1	Identifier for the VNF map.
config-parameter-request	container	1	See " <a href="#">nsr:config-parameter-request</a> " on page 132.
config-parameter-source	container	1	See " <a href="#">nsr:config-parameter-source</a> " on page 133.

**nsr:config-parameter-request**

/nsr:ns-instance-config/nsr/STRING/nsd/config-parameter-map/STRING/config-parameter-request

ID	Type	Cardinality	Description
member-vnf-index-ref	leafref	1	Reference to member-vnf within constituent-vnfds.
vnfd-id-ref	leafref	1	A reference to a VNFD. This is a leafref to path: ../../nsd:constituent-vnfd + [nsd:id = current()../nsd:id-ref] + /nsd:vnfd-id-ref
config-parameter-request-ref	leafref	1	Reference to the request in the VNF with the specified member-vnf-index.

**nsr:config-parameter-source**

/nsr:ns-instance-config/nsr/STRING/nsd/config-parameter-map/STRING/config-parameter-source

ID	Type	Cardinality	Description
member-vnf-index-ref	leafref	1	Reference to member-vnf within constituent-vnfds.
vnfd-id-ref	leafref	1	A reference to a VNFD. This is a leafref to path: ../..//nsd:constituent-vnfd + [nsd:id = current()]/../nsd:id-ref + /nsd:vnfd-id-ref
config-parameter-request-ref	leafref	1	Reference to the source in the VNF with the specified member-vnf-index.

## nsr:scaling-group-descriptor

Scaling group descriptor within this network service. A scaling group defines a group of VNFs and the ratio of VNFs in the network service that is used as the target for scaling action.

### REST URI path

/nsr:ns-instance-config/nsr/STRING/nsd/scaling-group-descriptor/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the scaling group.
scaling-policy	list	0..n	List of scaling policy items. See <a href="#">"nsr:scaling-policy" on page 135.</a>
vnfd-member	list	0..n	List of the VNFs in this scaling group. See <a href="#">"nsr:vnfd-member" on page 137.</a>
min-instance-count	uint32	1	[Default 0] Minimum instances of the scaling group allowed in a single network service.  <b>Note:</b> These instances are created by default when the network service is instantiated.
max-instance-count	uint32	1	[Default 10] Maximum instance of this scaling group that are allowed in a single network service.  The network service scaling will fail when the number of service group instances exceeds the max-instance-count specified.
scaling-config-action	list	0..n	List of conditions to be met for generating scaling requests. See <a href="#">"nsr:scaling-config-action" on page 137.</a>

**nsr:scaling-policy**

/nsr:ns-instance-config/nsr/STRING/nsd/scaling-group-descriptor/STRING/scaling-policy/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the scaling policy.
scaling-type	enum	1	The scaling type.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>1 — manual</li> <li>2 — automatic</li> </ul>
enabled	boolean	1	[Default <i>true</i> ] Specifies if the scaling policy can be applied.
scale-in-operation-type	enum	1	Operation to apply to check between scaling criteria and verify if the scale-in threshold condition has been met.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>AND [Default]</li> <li>OR</li> </ul>
scale-out-operation-type	enum	1	Operation to apply to check between scaling criteria and verify if the scale-out threshold condition has been met.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>AND</li> <li>OR [Default]</li> </ul>
threshold-time	uint32	1	[Required] The duration for which the criteria must hold true.

ID	Type	Cardinality	Description
cooldown-time	uint32	1	[Required] The duration after a scaling-in/scaling-out action has been triggered, for which there will be no further optional
scaling-criteria	list	0..n	List of conditions to be met for generating scaling requests. See " <a href="#">nsr:scaling-criteria</a> " on page 136.

### nsr:scaling-criteria

/nsr:ns-instance-config/nsr/STRING/nsd/scaling-group-descriptor/STRING/scaling-policy/STRING/scaling-criteria/STRING

ID	Type	Cardinality	Description
name	string	1	
scale-in-threshold	uint64	1	Value below which scale-in requests are generated.
scale-out-threshold	uint64	1	Value above which scale-in requests are generated.
ns-monitoring-param-ref	leafref	1	Reference to the network service level monitoring parameter that is aggregated. This is a leafref to path: ../..../monitoring-param/id



**nsr:vnfd-member**

/nsr:ns-instance-config/nsr/STRING/nsd/scaling-group-descriptor/STRING/vnfd-member/0

ID	Type	Cardinality	Description
member-vnf-index-ref	leafref	1	Member VNF index of this member VNF. This is a leafref to path: ../..../constituent-vnfd-member-vnfd-index
count	uint32	1	[Default 1] Count of this member VNF within this scaling group.  Note: Use count to define the number of instances when a scaling action targets this scaling group.

**nsr:scaling-config-action**

/nsr:ns-instance-config/nsr/STRING/nsd/scaling-group-descriptor/STRING/scaling-config-action/pre-scale-in

ID	Type	Cardinality	Description
trigger	enum	1	Scaling trigger type.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• 1 — pre-scale-in</li> <li>• 2 — post-scale-in</li> <li>• 3 — pre-scale-out</li> <li>• 4 — post-scale-out</li> </ul>
ns-config-primitive-name-ref	leafref	1	Reference to the network service configuration primitive name. This is a leafref to path: ../..../service-primitive/name

**nsr:placement-groups**

A list of placement groups at the network service level.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/placement-groups/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Place group construct to define the compute resource placement strategy in cloud environment.
requirement	string	1	Describes the intent/rationale behind this placement group. <hr/> <b>Note:</b> This free-text field is for human consumption only <hr/>
strategy	enum	1	Strategy associated with this placement group.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• COLOCATION: [Default] Share the physical infrastructure (hypervisor/network) among all members of this group.</li> <li>• ISOLATION: Do not share the physical infrastructure (hypervisor/network) among the members of this group</li> </ul>
member-vnfd	list	0..n	List of VNFDs that are part of this placement group. See " <a href="#">nsr:member-vnfd</a> " on page 139.

**nsr:member-vnfd**

/nsr:ns-instance-config/nsr/STRING/nsd/placement-groups/STRING/member-vnfd/0

ID	Type	Cardinality	Description
member-vnf-index-ref	leafref	1	Member VNF index of this member VNF. This is a leafref to path: ../../constituent-vnfd/member-vnf-index
vnfd-id-ref	leafref	1	Identifier for the VNFD. This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id

**nsr:ip-profiles**

List of IP profiles. IP profiles describe the IP characteristics for the virtual link.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/ip-profiles/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the IP profile.
description	string	1	Description of the IP profile.
ip-profile-params	container	1	Information about the IP profile. See " <a href="#">nsr:ip-profile-params</a> " on page 140.

**nsr:ip-profile-params**

/nsr:ns-instance-config/nsr/STRING/nsd/ip-profiles/STRING/ip-profile-params

ID	Type	Cardinality	Description
ip-version	enum	1	[Default IPv4] Version of the Internet Protocol used.
subnet-address	union	1	Subnet IP prefix associated with this IP profile.
gateway-address	union	1	IP address of the default gateway associated with this IP profile.
security-group	string	1	Name of the security group.

ID	Type	Cardinality	Description
dns-server	list	0..n	List of DNS servers associated with this IP profile. See " <a href="#">nsr:dns-server</a> " on page 141.
dhcp-params	container	1	Container for DHCP parameters. See " <a href="#">nsr:ip-profile-params</a> " on page 140.
subnet-prefix-pool	string	1	VIM-specific reference to pre-created subnet prefix.

### nsr:dns-server

/nsr:ns-instance-config/nsr/STRING/nsd/ip-profiles/STRING/ip-profile-params/dns-server/UNION\_VALUE

ID	Type	Cardinality	Description
address	union	1	List of DNS servers associated with this IP profile.

### nsr:dhcp-params

/nsr:ns-instance-config/nsr/STRING/nsd/ip-profiles/STRING/ip-profile-params/dhcp-params

ID	Type	Cardinality	Description
enabled	boolean	1	[Default <i>true</i> ] Indicates if DHCP is enabled.
start-address	union	1	Start IP address of the IP address range associated with DHCP domain.
count	uint32	1	Size of the DHCP pool associated with DHCP domain.

**nsr:vnf-dependency**

List of VNF dependencies in the Network Service Descriptor.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/vnf-dependency/STRING

**Fields**

ID	Type	Cardinality	Description
vnf-dependency	leafref	1	List of VNF dependencies. This is a leafref to path: ../..../vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id
vnf-dependson-ref	leafref	1	Reference to VNFD that on which the source VNF depends. This is a leafref to path: ../..../vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id

**nsr:vnffgd**

List of VNF Forwarding Graph Descriptors.

A Virtual Network Function Forwarding Graph (VNFFG) is a graph, specified by a Network Service Provider, of bi-directional logical links that connect network function nodes, where at least one node is a VNF through which network traffic is directed.

The VNFFG descriptor contains metadata about the VNF forwarding graph itself, as well as references to VNs, VNFs and PNFs, and network forwarding path elements. These elements include policies, such as MAC forwarding rules and routing entries, and references to connection points, such as virtual ports and virtual NIC addresses.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/vnffgd/STRING

**Fields**

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the VNFFGD.
name	string	1	VNFFGD name.
short-name	string	1	VNFFGD short name to use as label in the UI.
vendor	string	1	Provider of the VNFFGD.
description	string	1	Description of the VNFFGD.
version	string	1	Version of the VNFFGD.
rsp	list	0..n	List of the Rendered Service Paths (RSP) for the VNFFGD. See <a href="#">"nsr:rsp" on page 144</a>
classifier	list	0..n	List of classifier rules for the VNFFGD. See <a href="#">"nsr:classifier" on page 145</a> .

**nsr:rsp**

/nsr:ns-instance-config/nsr/STRING/nsd/vnffgd/STRING/rsp/STRING

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the RSP.
name	string	1	RSP name.
vnfd-connection-point-ref	list	0..n	A list of references to connection points. See " <a href="#">nsr:vnfd-connection-point-ref</a> " on page 144.

**nsr:vnfd-connection-point-ref**

/nsr:ns-instance-config/nsr/STRING/nsd/vnffgd/STRING/rsp/STRING/vnfd-connection-point-ref/0,STRING

ID	Type	Cardinality	Description
member-vnf-index-ref	leafref	1	Reference to member VNF within constituent VNFDs.  This is a leafref to path: ../..../nsd:constituent-vnfd-nsd_member-vnf-index
order	uint8	1	A number that denotes the VNF in a chain.
vnfd-id-ref	leafref	1	A reference to a VNFD.  This is a leafref to path: ../..../nsd:constituent-vnfd + [nsd:id = current()/../nsd:id-ref] + /nsd:vnfd-id-ref



ID	Type	Cardinality	Description
vnfd-connection-point-ref	leafref	1	A reference to a connection point name in a VNFD. This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd + [vnfd:id = current()/../nsd:vnfd-id-ref] + /vnfd:connection-point/vnfd:name

**nsr:classifier**

/nsr:ns-instance-config/nsr/STRING/nsd/vnffgd/STRING/classifier/STRING

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the classifier rule.
name	string	1	Name of the classifier.
rsp-id-ref	leafref	1	A reference to the RSP. This is a leafref to path: ../..//nsd:rsp/nsd:id
member-vnf-index-ref	leafref	1	Reference to member-vnf within constituent-vndfs. This is a leafref to path: ../..//nsd:constituent-vnfd/nsd:member-vnf-index

ID	Type	Cardinality	Description
vnfd-id-ref	leafref	1	A reference to a VNFD. This is a leafref to path: ../..../nsd:constituent-vnfd + [nsd:id = current()/../nsd:id-ref] + /nsd:vnfd-id-ref
vnfd-connection-point-ref	leafref	1	A reference to a connection point name in a VNFD. This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd + [vnfd:id = current()/../nsd:vnfd-id-ref] + /vnfd:connection-point/vnfd:name
match-attributes	list	0..n	List of match attributes. See " <a href="#">nsr:match-attributes</a> " on page 146

### nsr:match-attributes

/nsr:ns-instance-config/nsr/STRING/nsd/vnffgd/STRING/classifier/STRING/match-attributes/STRING

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the classifier match-attribute rule.
ip-proto	uint8	1	IP protocol.
source-ip-address	union	1	Source IP address.

ID	Type	Cardinality	Description
destination-ip-address	union	1	Destination IP address.
source-port	uint16	1	Source port number.
destination-port	uint16	1	Destination port number.

**nsr:monitoring-param**

List of monitoring parameters from VNFs to propagate to the Network Service Record (NSR).

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/monitoring-param/STRING

**Fields**

ID	Type	Cardinality	Description
id	string	1	Identifier for the parameter.
name	string	1	Name of the monitoring parameter
value-type	enum	1	The type of the parameter value.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• INT (default)</li> <li>• DECIMAL</li> <li>• STRING</li> </ul>
value-type	enum	1	The type of the parameter value.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• INT (default)</li> <li>• DECIMAL</li> <li>• STRING</li> </ul>
numeric-constraints	container	1	Constraints for the numbers.  See <a href="#">"nsr:numeric-constraints" on page 150.</a>
text-constraints	container	1	Constraints for the string.  See <a href="#">"nsr:text-constraints" on page 150.</a>

ID	Type	Cardinality	Description
value-integer	int64	1	Current value for integer parameter.
value-decimal	decimal164	1	Current value for decimal parameter.
value-string	string	1	Current value for the string parameter.
description	string	1	
group-tag	string	1	A simple tag to group monitoring parameters
widget-type	enum	1	Type of the widget, typically used by the UI.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• HISTOGRAM</li> <li>• BAR</li> <li>• GAUGE</li> <li>• SLIDER</li> <li>• COUNTER</li> <li>• TEXTBOX</li> </ul>
aggregation-type	enum	1	Aggregation type for the monitoring parameter.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• AVERAGE</li> <li>• MINIMUM</li> <li>• MAXIMUM</li> <li>• COUNT</li> <li>• SUM</li> </ul>

ID	Type	Cardinality	Description
vnfd-monitoring-param	list	0..n	A list of VNFD monitoring parameters. See " <a href="#">nsr:vnfd-monitoring-param</a> " on page 151.

### nsr:numeric-constraints

/nsr:ns-instance-config/nsr/STRING/nsd/monitoring-param/STRING/numeric-constraints

ID	Type	Cardinality	Description
min-value	uint64	1	Minimum value for the parameter.
max-value	uint64	1	Maximum value for the parameter.

### nsr:text-constraints

/nsr:ns-instance-config/nsr/STRING/nsd/monitoring-param/STRING/text-constraints

ID	Type	Cardinality	Description
min-length	uint8	1	Minimum string length for the parameter.
max-length	uint8	1	Maximum string length for the parameter.

**nsr:vnfd-monitoring-param**

/nsr:ns-instance-config/nsr/STRING/nsd/monitoring-param/STRING/vnfd-monitoring-param/0,STRING

ID	Type	Cardinality	Description
vnfd-id-ref	leafref	1	A reference to a VNFD. This is a leafref to path: ../..../nsd:constituent-vnfd + [nsd:id = current()../nsd:id-ref] + /nsd:vnfd-id-ref
vnfd-monitoring-param-ref	leafref	1	A reference to the VNFD monitoring parameter. This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd + [vnfd:id = current()../vnfd-id-ref] + /vnfd:monitoring-param/vnfd:id
member-vnf-index-ref	leafref	1	Optional reference to member-vnf within constituent-vnfds.

## nsr:input-parameter-xpath

List of XPathS to parameters inside the Network Service Descriptor that can be customized during instantiation.

### REST URI path

/nsr:ns-instance-config/nsr/STRING/nsd/input-parameter-xpath/STRING

### Fields

ID	Type	Cardinality	Description
xpath	string	1	An xpath that specifies the element in a descriptor.
label	string	1	A descriptive string.
default-value	string	1	A default value for this input parameter.



**nsr:parameter-pool**

Pool of parameter values from which to pull during configuration.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/parameter-pool/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the configuration value pool.
range	container	1	Create a range of values from which to populate the pool. See " <a href="#">nsr:range</a> " on page 153.

**nsr:range**

/nsr:ns-instance-config/nsr/STRING/nsd/parameter-pool/STRING/range

ID	Type	Cardinality	Description
start-value	uint32	1	[Required] Generated pool values start at this value.
end-value	uint32	1	[Required] Generated pool values end at this value.

**nsr:service-primitive**

Network service-level service primitives for the Network Service Descriptor.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/service-primitive/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the service primitive.
parameter	list	0..n	List of parameters for the service primitive. See " <a href="#">nsr:parameter</a> " on page 154.
parameter-group	list	0..n	Grouping of parameters that are logically grouped in UI. See " <a href="#">nsr:parameter-group</a> " on page 155.
vnf-primitive-group	list	0..n	List of service primitives grouped by the VNF. See " <a href="#">nsr:vnf-primitive-group</a> " on page 157.
used-defined-script	string	1	A user-defined script.

**nsr:parameter**

/nsr:ns-instance-config/nsr/STRING/nsd/service-primitive/STRING/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of parameter.

ID	Type	Cardinality	Description
data-type	enum	1	Data type associated with the name.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• STRING</li> <li>• INTEGER</li> <li>• BOOLEAN</li> </ul>
mandatory	boolean	1	[Default is <i>false</i> ] Specifies whether this field is mandatory.
default-value	string	1	The default value for the field.
parameter-pool	string	1	NSD parameter pool name to use for this parameter.
read-only	boolean	1	The value should be dimmed by the UI. Applies only to parameters with default values.
hidden	boolean	1	The value should be hidden by the UI. Applies only to parameters with default values
out	boolean	1	[Default is <i>false</i> ] Specifies if this is an output of the primitive execution

### nsr:parameter-group

/nsr:ns-instance-config/nsr/STRING/nsd/service-primitive/STRING/parameter-group/STRING

ID	Type	Cardinality	Description
name	string	1	Name of parameter group.

ID	Type	Cardinality	Description
parameter	list	0..n	List of parameters to the service primitive. See " <a href="#">nsr:parameter-group:parameter</a> " on page 156.
mandatory	boolean	1	[Default <i>true</i> ] Specifies whether this group mandatory.

### nsr:parameter-group:parameter

/nsr:ns-instance-config/nsr/STRING/nsd/service-primitive/STRING/parameter-group/STRING/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of parameter.
data-type	enum	1	Data type associated with the name. <b>Supported values:</b> <ul style="list-style-type: none"> <li>• STRING</li> <li>• INTEGER</li> <li>• BOOLEAN</li> </ul>
mandatory	boolean	1	[Default is <i>false</i> ] Specifies whether this field is mandatory.
default-value	string	1	The default value for the field.
parameter-pool	string	1	NSD parameter pool name to use for this parameter.
read-only	boolean	1	The value should be dimmed by the UI. Applies only to parameters with default values.

ID	Type	Cardinality	Description
hidden	boolean	1	The value should be hidden by the UI. Applies only to parameters with default values
out	boolean	1	[Default is <i>false</i> ] Specifies if this is an output of the primitive execution

### nsr:vnf-primitive-group

/nsr:ns-instance-config/nsr/STRING/nsd/service-primitive/STRING/vnf-primitive-group/0

ID	Type	Cardinality	Description
member-vnf-index-ref	uint64	1	Reference to member-vnf within constituent-vnfs.
vnfd-id-ref	string	1	A reference to a VNFD. This is a leafref to path: ../..../nsd:constituent-vnfd + [nsd:id = current()/../nsd:id-ref] + /nsd:vnfd-id-ref
vnfd-name	string	1	Name of the VNFD.
primitive	list	1	A list of VNF primitives. See " <a href="#">nsr:vnf-primitive-group:primitive</a> " on page 158

**nsr:vnf-primitive-group:primitive**

/nsr:ns-instance-config/nsr/STRING/nsd/service-primitive/STRING/vnf-primitive-group/0/primitive/0

ID	Type	Cardinality	Description
index	uint32	1	Index of this primitive.
name	string	1	Name of the primitive in the VNF primitive.

**nsr:initial-config-primitive**

Initial set of configuration primitives for the NSD, that are to be executed when the network service comes up.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/initial-config-primitive/0

**Fields**

ID	Type	Cardinality	Description
seq	uint64	1	Sequence number for the configuration primitive.
name	string	1	[Required] Name of the configuration primitive.
user-defined-script	string	1	A user-defined script.
parameter	list	0..n	List of parameters to the initial-config-primitive. See " <a href="#">nsr:parameter</a> " on page 159.

**nsr:parameter**

/nsr:ns-instance-config/nsr/STRING/nsd/initial-config-primitive/0/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the parameter.
value	string	1	Value of the parameter.

**nsr:terminate-config-primitive**

Set of configuration primitives to be executed before tearing down the network service.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/terminate-config-primitive/0

**Fields**

ID	Type	Cardinality	Description
seq	uint64	1	Sequence number for the configuration primitive.
name	string	1	[Required] Name of the configuration primitive.
user-defined-script	string	1	A user-defined script.
parameter	list	0..n	List of parameters to the primitive. See " <a href="#">nsr:parameter</a> " on page 160.

**nsr:parameter**

/nsr:ns-instance-config/nsr/STRING/nsd/terminate-config-primitive/0/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the parameter.
value	string	1	Value of the parameter.



**nsr:key-pair**

Used to configure the list of public keys to be injected as part of network service instantiation.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/key-pair/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of this key pair.
key	string	1	Key associated with this key pair.

**nsr:user**

List of users to be added through cloud-config.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/nsd/user/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the user.
user-info	string	1	The user name's real name.
key-pair	list	0..n	Used to configure the list of public keys to be injected as part of network service instantiation. See " <a href="#">nsr:key-pair</a> " on page 162.

**nsr:key-pair**

/nsr:ns-instance-config/nsr/STRING/user/STRING/ssh-authorized-key/STRING

/nsr:ns-instance-config/nsr/STRING/nsd/user/STRING/key-pair/STRING

ID	Type	Cardinality	Description
key-pair-ref	leafref	1	A reference to the key-pair entry in the global key pair table.

## nsr:input-parameter

List of XPath's input parameters.

### REST URI path

/nsr:ns-instance-config/nsr/STRING/input-parameter/STRING

### Fields

ID	Type	Cardinality	Description
xpath	string	1	An XPath that specifies which element in a descriptor is to be modified.
value	string	1	The value that the element specified by the XPath should take when a record is created.

## nsr:scaling-group

List of network service scaling group instances.

### REST URI path

/nsr:ns-instance-config/nsr/STRING/scaling-group/STRING

### Fields

ID	Type	Cardinality	Description
scaling-group-name-ref	string	1	Name of the scaling group leafref path: ../nsd/scaling-group-descriptor/name
instance	list	0..n	The instance of the scaling group. See " <a href="#">nsr:instance</a> " on page 164.

## nsr:instance

/nsr:ns-instance-config/nsr/STRING/scaling-group/STRING/instance/0

ID	Type	Cardinality	Description
id	uint16	1	Scaling group instance uuid.

## nsr:nsd-placement-group-maps

Mapping from mano-placement groups construct from NSD to cloud platform placement group construct .

### REST URI path

/nsr:ns-instance-config/nsr/STRING/nsd-placement-group-maps/STRING

### Fields

ID	Type	Cardinality	Description
placement-group-ref	string	1	Reference for the NSD placement group.
cloud-type	enum	1	Cloud account type: <ul style="list-style-type: none"> <li>• aws</li> <li>• cloudsim</li> <li>• cloudsim_proxy</li> <li>• mock</li> <li>• openmano</li> <li>• openstack</li> <li>• vsphere</li> <li>• openvim</li> <li>• prop_cloud1</li> </ul>
availability-zone	container	1	Name of the availability zone. See <a href="#">"nsr:availability-zone" on page 166.</a>
server-group	container	1	Name of the affinity/anti-affinity server group. See <a href="#">"nsr:server-group" on page 166.</a>
host-aggregate	list	0..n	Name of the host aggregate. See <a href="#">"nsr:host-aggregate" on page 167.</a>

ID	Type	Cardinality	Description
aws-construct	empty		
openmano-construct	empty		
vsphere-construct	empty		
mock-construct	empty		
cloudsim-construct	empty		

### nsr:availability-zone

/nsr:ns-instance-config/nsr/STRING/nsd-placement-group-maps/STRING/availability-zone

ID	Type	Cardinality	Description
name	string	1	Name of the availability zone.

### nsr:server-group

/nsr:ns-instance-config/nsr/STRING/nsd-placement-group-maps/STRING/server-group

ID	Type	Cardinality	Description
name	string	1	Name of the affinity/anti-affinity server group.

**nsr:host-aggregate**

/nsr:ns-instance-config/nsr/STRING/nsd-placement-group-maps/STRING/host-aggregate/STRING

ID	Type	Cardinality	Description
metadata-key	string	1	
metadata-value	string	1	

## nsr:vnfd-placement-group-maps

Mapping from mano-placement groups construct from VNFD to cloud platform placement group construct.

### REST URI path

/nsr:ns-instance-config/nsr/STRING/vnfd-placement-group-maps/STRING,STRING

### Fields

ID	Type	Cardinality	Description
vnfd-id-ref	string	1	A reference to a vnfd. This is a leafref to path: ../../../../nsd:constituent-vnfd + [nsr:id = current()../../nsd:id-ref] + /nsd:vnfd-id-ref
placement-group-ref	leafref	1	A reference to VNFD placement group.
cloud-type	enum	1	Cloud account type: <ul style="list-style-type: none"> <li>• aws</li> <li>• cloudsim</li> <li>• cloudsim_proxy</li> <li>• mock</li> <li>• openmano</li> <li>• openstack</li> <li>• vsphere</li> <li>• openvim</li> <li>• prop_cloud1</li> </ul>
availability-zone	container	1	Name of the availability zone. See " <a href="#">nsr:availability-zone</a> " on page 169.



ID	Type	Cardinality	Description
server-group	container	1	Name of the affinity/anti-affinity server group. See " <a href="#">nsr:server-group</a> " on page 170.
host-aggregate	list	0..n	Name of the host aggregate. See " <a href="#">nsr:host-aggregate</a> " on page 170.
aws-construct	empty		
openmano-construct	empty		
vsphere-construct	empty		
mock-construct	empty		
cloudsim-construct	empty		

### nsr:availability-zone

/nsr:ns-instance-config/nsr/STRING/vnfd-placement-group-maps/STRING,STRING/availability-zone

ID	Type	Cardinality	Description
name	string	1	Name of the availability zone.

**nsr:server-group**

/nsr:ns-instance-config/nsr/STRING/vnfd-placement-group-maps/STRING,STRING/server-group

ID	Type	Cardinality	Description
name	string	1	Name of the affinity/anti-affinity server group.

**nsr:host-aggregate**

/nsr:ns-instance-config/nsr/STRING/vnfd-placement-group-maps/STRING,STRING/host-aggregate/STRING

ID	Type	Cardinality	Description
metadata-key	string	1	
metadata-value	string	1	

## nsr:ssh-authorized-key

List of authorized SSH keys as part of cloud-config.

### REST URI path

/nsr:ns-instance-config/nsr/STRING/ssh-authorized-key/STRING

### Fields

ID	Type	Cardinality	Description
key-pair-ref	leafref	1	A reference to the key-pair entry in the global key pair table.

**nsr:user**

List of users to be added through cloud-config.

**REST URI path**

/nsr:ns-instance-config/nsr/STRING/user/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the user.
user-info	string	1	The user name's real name.
ssh-authorized-key	list	0..n	Used to configure the list of public keys to be injected as part of network service instantiation. See " <a href="#">nsr:ssh-authorized-key</a> " on page 172

**nsr:ssh-authorized-key**

/nsr:ns-instance-config/nsr/STRING/user/STRING/ssh-authorized-key/STRING

ID	Type	Cardinality	Description
key-pair-ref	leafref	1	A reference to the key-pair entry in the global key pair table.

## VNF Package Management (vnfd:vnfd)

REST wrapper for VNFD package management provides methods for onboarding, updating, querying, and deleting a VNF package through the vnfd:vnfd-catalog.

A VNF package, saved as a `tar.gz` archive, contains the VNF descriptor, images, and `checksum.txt` file.

The VNF includes one or more VDUs (the VM that hosts the network function), virtual links, and connection points. Each of these components (called nodes) has specific requirements, attributes, and capabilities, such as computational properties, that are defined in the VNF descriptor.

### Methods and relative URLs

Method	Relative URL	Description
GET	<code>/api/running/vnfd-catalog/vnfd/{trans-id}</code>	Query VNFD package onboarding status.
GET	<code>/api/running/vnfd-catalog/vnfd/{UUID}</code>	Query a VNF descriptor.

Method	Relative URL	Description
POST	/api/running/vnfd-catalog	<p>Onboard a VNF package to the catalog. The request body must include a gzipped tar file that contains the VNFD, images, and checksum.txt.</p> <p>When you onboard a VNF package, the orchestrator performs the following operations:</p> <ul style="list-style-type: none"> <li>• Extracts and validates the <code>tar</code> file contents and verifies the <code>checksum.txt</code> and mandatory contents</li> <li>• Uploads the images to the catalog</li> <li>• Responds to the REST interface with a transaction id, status set to <i>PENDING</i>, and image upload success message</li> <li>• Configures the VNFD</li> <li>• Changes the VNFD status to <i>READY</i>, which means that the VNFD is validated and ready for use</li> </ul> <p><b>To import</b> to the catalog, use the same POST call. In an import, the input <code>tgz</code> file contains (and onboards) multiple VNFDs in a single operation.</p>
PUT	/api/running/vnfd-catalog/vnfd/{UUID}	<p>Update a VNFD. The request body must include a gzipped tar file that contains the VNFD, images, and checksum.txt</p> <p>The orchestrator verifies that VNFD is not in use by the NSD or by a running instances of a VNF. Response status is <i>READY</i> if the image did not change, otherwise the status is <i>PENDING</i>.</p>
DELETE	/api/running/vnfd-catalog/vnfd/{UUID}	<p>Delete a VNF package.</p> <hr/> <p><b>Note:</b> The VNFD you want to delete cannot be in use by either the NSD or by a running instance of the VNF.</p> <hr/>

## Fields

Descriptor details for the Virtual Network Function (VNF).

ID	Type	Cardinality	Description
id	string	1	Identifier for the VNFD.
name	string	1	VNFD name.
short-name	string	1	VNFD short name to use as a label in the UI.
vendor	string	1	Provider of the VNFD.
logo	string	1	<p>File path of the vendor-specific logo. For example, <code>icons/mylogo.png</code></p> <p>The logo should be part of the VNF package.</p> <p>SVG format is preferred, but PNG is supported.</p> <p>Although there is no hard limit on size and dimension, a square image under 200px by 200px is preferred.</p>
description	string	1	Description of the VNFD.
version	string	1	Version of the VNFD.
vnf-configuration	container		<p>Information about the VNF configuration for the management interface.</p> <p>See <a href="#">"vnfd:vnf-configuration" on page 187</a>.</p>
config-parameter	container	1	<p>List of VNF configuration parameter requests and sources.</p> <p>See <a href="#">"vnfd:config-parameter" on page 194</a>.</p>

ID	Type	Cardinality	Description
mgmt-interface	container	1	Interface over which the VNF is managed. See <a href="#">"vnfd:mgmt-interface" on page 197</a> .
internal-vld	list	0..n	List of internal Virtual Link Descriptors (VLD). See <a href="#">"vnfd:internal-vld" on page 199</a> .
ip-profiles	list	0..n	List of IP profiles. An IP profile describes the IP characteristics for the virtual-link. See <a href="#">"vnfd:ip-profiles" on page 202</a> .
connection-point	list	0..n	The list for external connection points. See <a href="#">"vnfd:connection-point" on page 204</a> .
vdu	list	0..n	List of virtual deployment units, which are VMs that host the network function. See <a href="#">"vnfd:vdu" on page 205</a>
vdu-dependency	list	0..n	List of VDU dependencies. See <a href="#">"vnfd:vdu-dependency" on page 235</a> .
service-function-chain	enum	1	Type of node in service function chaining architecture. <b>Supported types:</b> <ul style="list-style-type: none"> <li>• UNAWARE (default)</li> <li>• CLASSIFIER</li> <li>• SF</li> <li>• SFF</li> </ul>



ID	Type	Cardinality	Description
service-function-type	string	1	Type of service function.  Note: This value needs to map to a service function type in the OpenDaylight platform to support VNFFG.
http-endpoint	list	0..n	List of http endpoints to be used by monitoring-param. See <a href="#">"vnfd:http-endpoint" on page 236</a> .
monitoring-param	list	0..n	List of monitoring parameters at the network service level.  See <a href="#">vnfd:monitoring-param</a> .
placement-groups	list	0..n	List of placement groups at VNF level. See <a href="#">"vnfd:placement-groups" on page 238</a> .

## MANO reference points

Os-Ma-nfvo and Or-Vnfm

### Schema

```

module vnfd
{
  namespace "urn:ietf:params:xml:ns:yang:nfvo:vnfd";
  prefix "vnfd";

  import mano-types {
    prefix "manotypes";
  }

  import rw-pb-ext {
    prefix "rwpb";
  }

  import ietf-yang-types {
    prefix "yang";
  }

  import ietf-inet-types {
    prefix "inet";
  }
}

```

```

}

revision 2015-09-10 {
  description
    "Initial revision. This YANG file defines
    the Virtual Network Function (VNF)";
  reference
    "Derived from earlier versions of base YANG files";
}

grouping common-connection-point {
  leaf name {
    description "Name of the connection point";
    type string;
  }

  leaf id {
    description "Identifier for the internal connection points";
    type string;
  }

  leaf short-name {
    description "Short name of the connection point";
    type string;
  }

  leaf type {
    description "Type of the connection point.";
    type manotypes:connection-point-type;
  }
}

grouping virtual-interface {
  container virtual-interface {
    description
      "Container for the virtual interface properties";

    leaf type {
      description
        "Specifies the type of virtual interface
        between VM and host.
        VIRTIO          : Use the traditional VIRTIO interface.
        PCI-PASSTHROUGH : Use PCI-PASSTHROUGH interface.
        SR-IOV          : Use SR-IOV interface.
        E1000           : Emulate E1000 interface.
        RTL8139         : Emulate RTL8139 interface.
        PCNET           : Emulate PCNET interface.
        OM-MGMT         : Used to specify openmano mgmt external-
connection type";

      type enumeration {
        enum OM-MGMT;
        enum PCI-PASSTHROUGH;
        enum SR-IOV;
        enum VIRTIO;
        enum E1000;
      }
    }
  }
}

```

```
        enum RTL8139;
        enum PCNET;
    }
    default "VIRTIO";
}

leaf vpci {
    description
        "Specifies the virtual PCI address. Expressed in
        the following format dddd:dd:dd.d. For example
        0000:00:12.0. This information can be used to
        pass as metadata during the VM creation.";
    type string;
}

leaf bandwidth {
    description
        "Aggregate bandwidth of the NIC.";
    type uint64;
}
}
}

container vnfd-catalog {

    description
        "Virtual Network Function Descriptor (VNFD).";

    list vnfd {
        key "id";

        leaf id {
            description "Identifier for the VNFD.";
            type string;
        }

        leaf name {
            description "VNFD name.";
            mandatory true;
            type string;
        }

        leaf short-name {
            description "VNFD short name.";
            type string;
        }

        leaf vendor {
            description "Vendor of the VNFD.";
            type string;
        }

        leaf logo {
            description
                "Vendor logo for the Virtual Network Function";
            type string;
        }
    }
}
```

```

}

leaf description {
  description "Description of the VNFD.";
  type string;
}

leaf version {
  description "Version of the VNFD";
  type string;
}

uses manotypes:vnf-configuration;

container mgmt-interface {
  description
    "Interface over which the VNF is managed.";

  choice endpoint-type {
    description
      "Indicates the type of management endpoint.";

    case ip {
      description
        "Specifies the static IP address for managing the VNF.";
      leaf ip-address {
        type inet:ip-address;
      }
    }

    case vdu-id {
      description
        "Use the default management interface on this VDU.";
      leaf vdu-id {
        type leafref {
          path "/vnfd:vnfd-catalog/vnfd:vnfd/vnfd:vdu/vnfd:id";
        }
      }
    }

    case cp {
      description
        "Use the ip address associated with this connection point.";
      leaf cp {
        type leafref {
          path "/vnfd:vnfd-catalog/vnfd:vnfd/vnfd:connection-
point/vnfd:name";
        }
      }
    }
  }
}

leaf port {
  description
    "Port for the management interface.";
  type inet:port-number;
}

```

```
}

container dashboard-params {
  description "Parameters for the VNF dashboard";

  leaf path {
    description "The HTTP path for the dashboard";
    type string;
  }

  leaf https {
    description "Pick HTTPS instead of HTTP , Default is false";
    type boolean;
  }

  leaf port {
    description "The HTTP port for the dashboard";
    type inet:port-number;
  }
}

list internal-vld {
  key "id";
  description
    "List of Internal Virtual Link Descriptors (VLD).
    The internal VLD describes the basic topology of
    the connectivity (e.g. E-LAN, E-Line, E-Tree)
    between internal VNF components of the system.";

  leaf id {
    description "Identifier for the VLD";
    type string;
  }

  leaf name {
    description "Name of the internal VLD";
    type string;
  }

  leaf short-name {
    description "Short name of the internal VLD";
    type string;
  }

  leaf description {
    type string;
  }

  leaf type {
    type manotypes:virtual-link-type;
  }

  leaf root-bandwidth {
    description
      "For ELAN this is the aggregate bandwidth.";
  }
}
```

```
    type uint64;
  }

  leaf leaf-bandwidth {
    description
      "For ELAN this is the bandwidth of branches.";
    type uint64;
  }

  list internal-connection-point {
    key "id-ref";
    description "List of internal connection points in this VLD";
    leaf id-ref {
      description "reference to the internal connection point id";
      type leafref {
        path "../..../vdu/internal-connection-point/id";
      }
    }
  }
}
uses manotypes:provider-network;
}

list connection-point {
  key "name";
  description
    "List for external connection points. Each VNF has one
    or more external connection points. As the name
    implies that external connection points are used for
    connecting the VNF to other VNFs or to external networks.
    Each VNF exposes these connection points to the
    orchestrator. The orchestrator can construct network
    services by connecting the connection points between
    different VNFs. The NFVO will use VLDs and VNFFGs at
    the network service level to construct network services.";

  uses common-connection-point;
}

list vdu {
  description "List of Virtual Deployment Units";
  key "id";

  leaf id {
    description "Unique id for the VDU";
    type string;
  }

  leaf name {
    description "Unique name for the VDU";
    type string;
  }

  leaf description {
    description "Description of the VDU.";
    type string;
  }
}
```

```
leaf count {
  description "Number of instances of VDU";
  type uint64;
}

leaf mgmt-vpci {
  description
    "Specifies the virtual PCI address. Expressed in
    the following format dddd:dd:dd.d. For example
    0000:00:12.0. This information can be used to
    pass as metadata during the VM creation.";
  type string;
}

uses manotypes:vm-flavor;
uses manotypes:guest-epa;
uses manotypes:vswitch-epa;
uses manotypes:hypervisor-epa;
uses manotypes:host-epa;

list alarm {
  key "alarm-id";

  uses manotypes:alarm;
}

uses manotypes:image-properties;

choice cloud-init-input {
  description
    "Indicates how the contents of cloud-init script are provided.
    There are 2 choices - inline or in a file";

  case inline {
    leaf cloud-init {
      description
        "Contents of cloud-init script, provided inline, in cloud-
config format";
      type string;
    }
  }

  case filename {
    leaf cloud-init-file {
      description
        "Name of file with contents of cloud-init script in cloud-
config format";
      type string;
    }
  }
}

list internal-connection-point {
  key "id";
  description
```

```
        "List for internal connection points. Each VNFC
        has zero or more internal connection points.
        Internal connection points are used for connecting
        the VNF components internal to the VNF. If a VNF
        has only one VNFC, it may not have any internal
        connection points.";

    uses common-connection-point;

    leaf internal-vld-ref {
        type leafref {
            path "../..../internal-vld/id";
        }
    }
}

list internal-interface {
    description
        "List of internal interfaces for the VNF";
    key name;

    leaf name {
        description
            "Name of internal interface. Note that this
            name has only local significance to the VDU.";
        type string;
    }

    leaf vdu-internal-connection-point-ref {
        type leafref {
            path "../..../internal-connection-point/id";
        }
    }
    uses virtual-interface;
}

list external-interface {
    description
        "List of external interfaces for the VNF.
        The external interfaces enable sending
        traffic to and from VNF.";
    key name;

    leaf name {
        description
            "Name of the external interface. Note that
            this name has only local significance.";
        type string;
    }

    leaf vnfd-connection-point-ref {
        description
            "Name of the external connection point.";
        type leafref {
            path "../..../connection-point/name";
        }
    }
}
```



```

    }
    uses virtual-interface;
  }

  list volumes {
    key "name";

    leaf name {
      description "Name of the disk-volumes, e.g. vda, vdb etc";
      type string;
    }

    uses manotypes:volume-info;
  }
}

list vdu-dependency {
  description
    "List of VDU dependencies.";

  key vdu-source-ref;
  leaf vdu-source-ref {
    type leafref {
      path "../vdu/id";
    }
  }

  leaf vdu-depends-on-ref {
    description
      "Reference to the VDU that
      source VDU depends.";
    type leafref {
      path "../vdu/id";
    }
  }
}

leaf service-function-chain {
  description "Type of node in Service Function Chaining
  Architecture";

  type enumeration {
    enum UNAWARE;
    enum CLASSIFIER;
    enum SF;
    enum SFF;
  }
  default "UNAWARE";
}

leaf service-function-type {
  description
    "Type of Service Function.
    NOTE: This needs to map with Service Function Type in ODL to
    support VNFFG. Service Function Type is mandatory param in ODL
    SFC. This is temporarily set to string for ease of use";

```

```
        type string;
    }

    uses manotypes:monitoring-param;

    list placement-groups {
        description "List of placement groups at VNF level";

        key "name";
        uses manotypes:placement-group-info;

        list member-vdus {

            description
                "List of VDUs that are part of this placement group";
            key "member-vdu-ref";

            leaf member-vdu-ref {
                type leafref {
                    path "../.../.../vdu/id";
                }
            }
        }
    }
}
}
```

## Examples

See ["API Examples" on page 369](#).

## vnfd:vnf-configuration

Information about the VNF configuration for the management interface.

Note: If the network service contains multiple instances of the same VNF, each VNF instance could have a different configuration.

### REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/vnf-configuration

### Fields

ID	Type	Cardinality	Description
netconf	container	1	Use NETCONF for configuring the VNF. See <a href="#">"vnfd:netconf" on page 188</a> .
rest	container	1	Use REST for configuring the VNF. See <a href="#">"vnfd:rest" on page 189</a> .
script	container	1	Use a custom script for configuring the VNF. This script will be executed in the orchestrator. All required dependencies for the script should be available in the orchestrator system. See <a href="#">"vnfd:script" on page 189</a> .
juju	container	1	Use Juju for configuring the VNF. See <a href="#">"vnfd:juju" on page 189</a> .
config-access	container	1	IP address to be used to configure this VNF. See <a href="#">"vnfd:config-access" on page 190</a> .

ID	Type	Cardinality	Description
config-attributes	container	1	Miscellaneous config attributes to be considered while processing the NSD to apply configuration. See " <a href="#">vnfd:config-attributes</a> " on page 190.
config-primitive	list	0..n	List of service primitives supported by the configuration agent for this VNF. See " <a href="#">vnfd:config-primitive</a> " on page 190.
initial-config-primitive	list	0..n	Initial set of configuration primitives. See " <a href="#">vnfd:initial-config-primitive</a> " on page 192.
config-template	string	1	Configuration template for each VNF.

### vnfd:netconf

/vnfd:vnfd-catalog/vnfd/STRING/vnf-configuration/netconf

ID	Type	Cardinality	Description
target	enum	1	NETCONF configuration target.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>RUNNING</li> <li>CANDIDATE</li> </ul>
protocol	enum	1	Protocol to use for NETCONF.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>NONE</li> <li>SSH</li> </ul>

ID	Type	Cardinality	Description
port	inet:port-number	1	Port for the NETCONF server.

**vnfd:rest**

/vnfd:vnfd-catalog/vnfd/STRING/vnf-configuration/rest

ID	Type	Cardinality	Description
port	inet_port-number	1	Port for the REST server

**vnfd:script**

/vnfd:vnfd-catalog/vnfd/STRING/vnf-configuration/script

ID	Type	Cardinality	Description
script-type	enum	1	Script type to use.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• BASH</li> <li>• EXPECT</li> </ul>

**vnfd:juju**

/vnfd:vnfd-catalog/vnfd/STRING/vnf-configuration/juju

ID	Type	Cardinality	Description
charm	string	1	Juju charm to use to use with the VNF.

**vnfd:config-access**

/vnfd:vnfd-catalog/vnfd/STRING/vnf-configuration/config-access

ID	Type	Cardinality	Description
mgmt-ip-address	union	1	IP address to be used to configure this VNF. <hr/> <b>Note:</b> This parameter is optional if it is possible to dynamically resolve the IP. <hr/>
username	string	1	User name for configuration.
password	string	1	Password for configuration access authentication.

**vnfd:config-attributes**

/vnfd:vnfd-catalog/vnfd/STRING/vnf-configuration/config-attributes

ID	Type	Cardinality	Description
config-priority	uint64	1	Order of configuration priority to be applied to each VNF in this network service.  A low number takes precedence over a high number.
config-delay	uint64	1	Wait time (in seconds) before applying the configuration to this VNF.

**vnfd:config-primitive**

/vnfd:vnfd-catalog/vnfd/STRING/vnf-configuration/config-primitive/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the service primitive.

ID	Type	Cardinality	Description
parameter	list	0..n	List of parameters to the service primitive. See " <a href="#">vnfd:config-primitive:parameter</a> " on page 191.
user-defined-script	string	1	A user-defined script. If a script is defined, the script will be executed using bash.

### vnfd:config-primitive:parameter

/vnfd:vnfd-catalog/vnfd/STRING/vnf-configuration/config-primitive/STRING/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of parameter
data-type	enum	1	Data type associated with the name. <b>Supported values:</b> <ul style="list-style-type: none"> <li>• STRING</li> <li>• INTEGER</li> <li>• BOOLEAN</li> </ul>
mandatory	boolean	1	[Default <i>false</i> ] Defines whether this field is mandatory.
default-value	string	1	The default value for the field. <hr/> <b>Note:</b> This value is required to set the read-only and hidden parameters. <hr/>
parameter-pool	string	1	NSD parameter pool name to use for this parameter.

ID	Type	Cardinality	Description
read-only	boolean	1	If set to <i>true</i> , the value is dimmed in the UI.  Note: This parameter can be set to true only on parameters that specify a default-value field.
hidden	boolean	1	If set to true, the value is hidden from view in the UI.  Note: This parameter can be set to true only on parameters that specify a default-value field.
out	boolean	1	Specifies if this is an output of the primitive execution.

### vnfd:initial-config-primitive

/vnfd:vnfd-catalog/vnfd/STRING/vnf-configuration/initial-config-primitive/0

ID	Type	Cardinality	Description
seq	uint64	1	Sequence number for the configuration primitive.
name	string	1	Name of the configuration primitive.
parameter	list	0..n	List of parameters to the configuration primitive. See " <a href="#">vnfd:initial-config-primitive:parameter</a> " on page 193.
user-defined-script	string	1	A user-defined script



ID	Type	Cardinality	Description
config-primitive-ref	leafref	1	Reference to a config primitive name. <hr/> Note: The referenced config primitive should have all the input parameters predefined either with default values or dependency references. <hr/>

### **vnfd:initial-config-primitive:parameter**

/vnfd:vnfd-catalog/vnfd/STRING/vnf-configuration/initial-config-primitive/0/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the parameter.
value	string	1	Value of the parameter.

## vnfd:config-parameter

List of VNF config parameter requests and sources

REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/config-parameter

### Fields

ID	Type	Cardinality	Description
config-parameter-source	list	1	List of parameters exposed by this VNF. See <a href="#">"vnfd:config-parameter-source" on page 194.</a>
config-parameter-request	list	1	List of requests for this VNF. See <a href="#">"vnfd:config-parameter-source:parameter" on page 195.</a>

## vnfd:config-parameter-source

/vnfd:vnfd-catalog/vnfd/STRING/config-parameter/config-parameter-source/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the source.
description	string	1	Description of the source.
attribute	string	1	Location of this source as a run-time attribute. For example, the value is ../.././mgmt-interface, ip-address which returns the ip-address assigned to the mgmt-interface after VNF instantiation.

ID	Type	Cardinality	Description
config-primitive-name-ref	leafref	1	A leafref to the configuration primitive.  Note: This refers to a config parameter in which output parameter is referenced in <code>out-parameter</code> .
parameter-ref	leafref	1	Name of the output parameter in the config primitive.
value	string	1	Predefined value to be used for this source.
parameter	list	0..n	List of parameters for this source.  See " <a href="#">vnfd:config-parameter-source:parameter</a> " on page 195.

### vnfd:config-parameter-source:parameter

/vnfd:vnfd-catalog/vnfd/STRING/config-parameter/config-parameter-source/STRING/parameter/STRING

ID	Type	Cardinality	Description
config-primitive-name-ref	leafref	1	Name of the configuration primitive where this source will used.
config-primitive-parameter-ref	leafref	1	Parameter name of the config primitive.

**vnfd:config-parameter-request**

/vnfd:vnfd-catalog/vnfd/STRING/config-parameter/config-parameter-request/STRING

ID	Type	Cardinality	Description
name	string	1	Name of this parameter request.
description	string	1	Description of this request.
parameter	list	0..n	List of parameters for this request. See " <a href="#">vnfd:config-parameter-request:parameter</a> " on page 196.

**vnfd:config-parameter-request:parameter**

/vnfd:vnfd-catalog/vnfd/STRING/config-parameter/config-parameter-request/STRING/parameter/STRING

ID	Type	Cardinality	Description
config-primitive-name-ref	leafref	1	Name of the configuration primitive where this request will used.
config-primitive-parameter-ref	leafref	1	Parameter name of the config primitive.

## vnfd:mgmt-interface

Interface over which the VNF is managed.

### REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/mgmt-interface

### Fields

ID	Type	Cardinality	Description
ip-address	union	1	Specifies the static IP address for managing the VNF.
vdu-id	leafref	1	Use the default management interface on this VDU. This is a leafref to path: <code>/vnfd:vnfd-catalog/vnfd:vnfd/vnfd:vdu/vnfd:id</code>
cp	leafref	1	Use the IP address for the VNFD associated with this connection point endpoint. This is a leafref to path: <code>/vnfd:vnfd-catalog/vnfd:vnfd/vnfd:connection-point/vnfd:name</code>
port	uint16	1	Port number for the management interface.
dashboard-params	container	1	Parameters for the VNF dashboard of the management interface. See " <a href="#">vnfd:dashboard-params</a> " on page 198.

**vnfd:dashboard-params**

/vnfd:vnfd-catalog/vnfd/STRING/mgmt-interface/dashboard-params

ID	Type	Cardinality	Description
path	string	1	The HTTP path for the dashboard.
https	boolean	1	[Default <i>false</i> ] Choose HTTPS instead of HTTP.
port	uint16	1	The HTTP port for the dashboard

## vnfd:internal-vld

List of internal Virtual Link Descriptors (VLDs). Internal VLDs describe the basic topology of the connectivity—such as E-LAN— between internal VNF Components (VNFC) within the system.

### REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/internal-vld/STRING

### Fields

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the internal VLD.
name	string	1	Name of the internal VLD.
short-name	string	1	Short name for the internal VLD to use as a label in the UI.
description	string	1	Description of the internal VLD.
type	enum	1	Type of virtual link.  <b>Supported values:</b> ELAN: A multipoint service that connects a set of VDUs.
root-bandwidth	uint64	1	For ELAN this is the aggregate bandwidth.
leaf-bandwidth	uint64	1	For ELAN this is the bandwidth of branches.
internal-connection-point	list	0..n	List of internal connection points in this VLD. See " <a href="#">vnfd:internal-connection-point</a> " on page 200.

ID	Type	Cardinality	Description
provider-network	container	1	Container for the provider network. See " <a href="#">vnfd:provider-network</a> " on page 200.
vim-network-name	string	1	Name of pre-provisioned network in the VIM (cloud) account.
ip-profile-ref	string	1	Named reference to an ip-profile object.

### vnfd:internal-connection-point

/vnfd:vnfd-catalog/vnfd/STRING/internal-vld/STRING/internal-connection-point/STRING

ID	Type	Cardinality	Description
id-ref	leafref	1	Reference to the internal connection point ID.

### vnfd:provider-network

/vnfd:vnfd-catalog/vnfd/STRING/internal-vld/STRING/provider-network

ID	Type	Cardinality	Description
physical-network	string	1	Name of the physical network on which the provider network is built.



ID	Type	Cardinality	Description
overlay-type	enum	1	<p>Identifies the type of the overlay network, which is a virtual network that is built on top of an existing network and is supported by its infrastructure.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• LOCAL — A network that can be realized on a single host only.</li> <li>• FLAT — The simplest networking environment in which each instance receives a fixed IP from the pool. All instances are attached to the same bridges.</li> <li>• VLAN — A network of computers in which the computers behaves as if they are connected to the same wire. However, the computers might be physically located on different segments of a LAN.</li> <li>• VXLAN — A proposed encapsulation protocol for running an overlay network on existing Layer 3 infrastructure</li> <li>• GRE — GRE tunnels encapsulate isolated Layer 2 network traffic in IP packets. Packets are routed between compute and networking nodes using the hosts' network connectivity and routing tables.</li> </ul>
segmentation-id	uint32	1	Segmentation ID

## vnfd:ip-profiles

List of IP profiles. IP profiles describe the IP characteristics for the virtual link.

### REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/ip-profiles/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the IP profile.
description	string	1	Description of the IP profile.
ip-profile-params	container	1	Information about the IP profile. See " <a href="#">vnfd:ip-profile-params</a> " on page 202

## vnfd:ip-profile-params

/vnfd:vnfd-catalog/vnfd/STRING/ip-profiles/STRING/ip-profile-params

ID	Type	Cardinality	Description
ip-version	enum	1	[Default IPv4] Version of the Internet Protocol used.
subnet-address	union	1	Subnet IP prefix associated with this IP profile.
gateway-address	union	1	IP address of the default gateway associated with this IP profile.
security-group	string	1	Name of the security group.

ID	Type	Cardinality	Description
dns-server	list	0..n	List of DNS servers associated with this IP profile. See " <a href="#">vnfd:dns-server</a> " on page 203.
dhcp-params	container	1	Container for DHCP parameters. See " <a href="#">vnfd:ip-profile-params</a> " on page 202.
subnet-prefix-pool	string	1	VIM-specific reference to pre-created subnet prefix.

### vnfd:dns-server

/vnfd:vnfd-catalog/vnfd/STRING/ip-profiles/STRING/ip-profile-params/dns-server/UNION\_VALUE

ID	Type	Cardinality	Description
address union	1	List of DNS servers associated with this IP profile.	

### vnfd:dhcp-params

/vnfd:vnfd-catalog/vnfd/STRING/ip-profiles/STRING/ip-profile-params/dhcp-params

ID	Type	Cardinality	Description
enabled	boolean	1	[Default <i>true</i> ] Indicates if DHCP is enabled.
start-address	union	1	Start IP address of the IP address range associated with DHCP domain.
count	uint32	1	Size of the DHCP pool associated with DHCP domain.

## vnfd:connection-point

List of external connection points, in which each VNF:

- Has one or more points that are used to connect a VNF to other VNFs or to external networks
- Exposes these connection points to the orchestrator (NFVO)

The orchestrator constructs network services by connecting the connection points between different VNFs.

The orchestrator uses VLDs and VNFFGs at the network service level to construct network services.

### REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/connection-point/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the connection point.
id	string	1	Unique identifier of the connection point
short-name	string	1	Short name of the connection point to use as a label in the UI.
type	enum	1	Type of connection point.  <b>Supported values:</b> VPORT: Virtual Port
port-security-enabled	boolean	1	Enables the port security for the port
static-ip-address	union	1	Static IP address for the connection point

## vnfd:vdu

A VDU is a basic part of VNF. VDUs are virtual machines that host the network function, such as:

- Virtual machine specification
- Computation properties (RAM size, disk size, memory page size, number of CPUs, number of cores per CPU, number of threads per core)
- Storage requirements
- Initiation and termination scripts
- High availability redundancy model
- Scale out/scale in limits

### REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING

### Fields

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the VDU.
name	string	1	Unique name for the VDU.
description	string	1	Description of the VDU.
count	uint64	1	Number of instances of the VDU.
mgmt-vpci	string	1	Specifies the virtual PCI address, expressed in the following format dddd:dd:dd.d. For example 0000:00:12.0.  This information can be used to pass as metadata during the VM creation.

ID	Type	Cardinality	Description
vm-flavor	container	1	Flavor of the virtual machine (VM) instance. See <a href="#">"vnfd:vm-flavor" on page 208</a> .
guest-epa	container	1	EPA attributes for the guest operating system. See <a href="#">"vnfd:guest-epa" on page 209</a> .
vswitch-epa	container	1	EPA attributes for Open vSwitch. See <a href="#">"vnfd:vswitch-epa" on page 214</a> .
hypervisor-epa	container	1	EPA attributes for the hypervisor. See <a href="#">"vnfd:hypervisor-epa" on page 215</a> .
host-epa	container	1	EPA attributes for the host operating system. See <a href="#">"vnfd:host-epa" on page 216</a> .
alarm	list	0..n	A list of alarms. See <a href="#">"vnfd:alarm" on page 221</a> .
image	string	1	Image name for the software image. If the image name is found within the VNF package it will be uploaded to all cloud accounts during the onboarding process. Otherwise, the image must be added to the cloud account with the same name as entered in this field.
image-checksum	string	1	Image md5sum for the software image. The md5sum, if provided, along with the image name, uniquely identifies an image uploaded to the CAL.
cloud-init	string	1	Contents of cloud-init script, provided inline, in cloud-config format

ID	Type	Cardinality	Description
cloud-init-file	string	1	Name of file with contents of cloud-init script in cloud-config format.
supplemental-boot-data	container	1	Container for custom VIM data. See <a href="#">"vnfd:supplemental-boot-data" on page 225.</a>
internal-connection-point	list	0..n	List for internal connection points. See <a href="#">"vnfd:internal-connection-point" on page 227.</a>
internal-interface	list	0..n	List of internal interfaces for the VNF. See <a href="#">"vnfd:internal-interface" on page 228.</a>
external-interface	list	0..n	List of external interfaces for the VNF. See <a href="#">"vnfd:external-interface" on page 230.</a>
volumes	list	0..n	List of disk-volumes to be attached to VDU. See <a href="#">"vnfd:volumes" on page 232.</a>

**vnfd:vm-flavor**

Flavor is an alternative term for a VM instance type.

**REST URI path**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/vm-flavor

**Fields**

ID	Type	Cardinality	Description
vpcu-count	uint16	1	Number of VCPUs for the VM.
memory-mb	uint64	1	Amount of memory in MB to allocate to the VM.
storage-gb	uint64	1	Amount of disk space in GB to allocate to the VM.



**vnfd:guest-epa**

EPA attributes for the guest operating system.

**REST URI path**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/guest-epa

**Fields**

ID	Type	Cardinality	Description
trusted-execution	boolean	1	If set to <i>true</i> , indicates this VM should be allocated from trusted pool.
mempage-size	enum	1	<p>Memory page allocation size.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>LARGE: Require hugepages (either 2MB or 1GB)</li> <li>SMALL: Doesn't require hugepages</li> <li>SIZE_2MB: Requires 2MB hugepages</li> <li>SIZE_1GB: Requires 1GB hugepages</li> <li>PREFER_LARGE: Application prefers hugepages</li> </ul> <p>Note: If a VM requires hugepages, choose LARGE or SIZE_2MB or SIZE_1GB. If the VM prefers hugepages, choose PREFER_LARGE.</p>
cpu-pinning-policy	enum	1	<p>Describes the association between virtual CPUs in the guest and the physical CPUs in the host.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>DEDICATED: Virtual CPUs are pinned to physical CPUs</li> <li>SHARED: Multiple VMs may share the same physical CPUs.</li> <li>ANY: (Default) Any policy is acceptable for the VM</li> </ul>

ID	Type	Cardinality	Description
cpu-thread-pinning-policy	enum	1	<p>Describes how to place the guest CPUs when the host supports hyper threads.</p> <p><b>Default values:</b></p> <ul style="list-style-type: none"> <li>• AVOID: Avoids placing a guest on a host with threads.</li> <li>• SEPARATE: Places vCPUs on separate cores, and avoids placing two vCPUs on two threads of same core.</li> <li>• ISOLATE: Places each vCPU on a different core, and places no vCPUs from a different guest on the same core.</li> <li>• PREFER: Attempts to place vCPUs on threads of the same core.</li> </ul>
pcie-device list		0..1	<p>List of PCIE passthrough devices.</p> <p>See <a href="#">"vnfd:pcie-device" on page 211</a></p>
numa-unaware	empty		<p>Details about the numa-node-policy are null.</p>
numa-node-policy	container	1	<p>Defines numa topology of the guest, specifying if the guest should run on a host with one numa node or multiple numa nodes.</p> <p><b>Example:</b> A guest might need 8 VCPUs and 4 GB of memory with the VCPUs and memory distributed across multiple NUMA nodes. In this scenario, NUMA node 1 could run with 6 VCPUs and 3GB, and NUMA node 2 could run with 2 vcpus and 1GB.</p> <p>See <a href="#">"vnfd:numa-node-policy" on page 211</a></p>

**vnfd:pcie-device**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/guest-epa/pcie-device/STRING

ID	Type	Cardinality	Description
device-id	string	1	Device identifier.
count	uint64	1	Number of devices to attach to the VM.

**vnfd:numa-node-policy**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/guest-epa/numa-node-policy

ID	Type	Cardinality	Description
node-cnt	uint16	1	Number of NUMA nodes to expose to the VM.
mem-policy	enum	1	Specifies how to allocate memory in a multi-node scenario.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• STRICT: The memory must be allocated from the memory attached to the NUMA node.</li> <li>• PREFERRED: The memory should be allocated from the memory attached to the NUMA node</li> </ul>
node	list	0..n	List of NUMA nodes.  See " <a href="#">vnfd:numa-node-policy:node</a> " on page 212.

**vnfd:numa-node-policy:node**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/guest-epa/numa-node-policy/node/0

ID	Type	Cardinality	Description
id	uint64	1	NUMA node identification. Typically 0 or 1.
vcpu	list	0..n	List of VCPUs to allocate on this NUMA node. See " <a href="#">vnfd:numa-node-policy:node:vcpu</a> " on page 212
memory-mb	uint64	1	Memory size in MB for this NUMA node.
num-cores	uint8	1	Number of cores.
paired-threads	container	1	Container for paired threads. See " <a href="#">vnfd:numa-node-policy:node:paired-threads</a> " on page 213.
num-threads	uint8	1	OpenMANO NUMA type selection.

**vnfd:numa-node-policy:node:vcpu**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/guest-epa/numa-node-policy/node/0/vcpu/0

ID	Type	Cardinality	Description
id	uint64	1	List of VCPUs IDs to allocate on this NUMA node.

**vnfd:numa-node-policy:node:paired-threads**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/guest-epa/numa-node-policy/node/0/paired-threads

ID	Type	Cardinality	Description
num-paired-threads	uint8	1	Number of paired-threads.
paired-thread-ids	list	0..n	List of thread paired to use in case of paired thread NUMA. See " <a href="#">vnfd:numa-node-policy:node:paired-threads:paired-thread-ids</a> " on page 213

**vnfd:numa-node-policy:node:paired-threads:paired-thread-ids**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/guest-epa/numa-node-policy/node/0/paired-threads/paired-thread-ids/0

ID	Type	Cardinality	Description
thread-a	uint8	1	Thread ID
thread-b	uint8	1	Thread ID

**vnfd:vswitch-epa**

EPA attributes for Open vSwitch.

**REST URI path**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/vswitch-epa

**Fields**

ID	Type	Cardinality	Description
ovs-acceleration	enum	1	<p>Specifies Open vSwitch acceleration mode.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"><li>• MANDATORY: OVS acceleration is required</li><li>• PREFERRED: OVS acceleration is preferred</li><li>• DISABLED: OVS acceleration is disabled.</li></ul>
ovs-offload	enum	1	<p>Specifies Open vSwitch hardware offload mode.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"><li>• MANDATORY: OVS offload is required</li><li>• PREFERRED: OVS offload is preferred</li><li>• DISABLED: OVS offload is disabled</li></ul>

**vnfd:hypervisor-epa**

EPA attributes for the hypervisor.

**REST URI path**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/hypervisor-epa

**Fields**

ID	Type	Cardinality	Description
type	enum	1	Specifies the type of hypervisor. For example, KVM, XEN.  Value can be: <ul style="list-style-type: none"><li>• KVM: KVM</li><li>• XEN: XEN</li></ul>
version	string	1	Version of the hypervisor.

**vnfd:host-epa**

Specifies the host-level EPA attributes.

**REST URI path**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/host-epa

**Fields**

ID	Type	Cardinality	Description
cpu-model	enum	1	Host CPU model.  <b>Supported values:</b> <ul style="list-style-type: none"><li>• PREFER_WESTMERE</li><li>• REQUIRE_WESTMERE</li><li>• PREFER_SANDYBRIDGE</li><li>• REQUIRE_SANDYBRIDGE</li><li>• PREFER_IVYBRIDGE</li><li>• REQUIRE_IVYBRIDGE</li><li>• PREFER_HASWELL</li><li>• REQUIRE_HASWELL</li><li>• PREFER_BROADWELL</li><li>• REQUIRE_BROADWELL</li><li>• PREFER_NEHALEM</li><li>• REQUIRE_NEHALEM</li><li>• PREFER_PENRYN</li><li>• REQUIRE_PENRYN</li><li>• PREFER_CONROE</li><li>• REQUIRE_CONROE</li><li>• PREFER_CORE2DUO</li><li>• REQUIRE_CORE2DUO</li></ul>



ID	Type	Cardinality	Description
cpu-arch	enum	1	Host CPU architecture.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• PREFER_X86</li> <li>• REQUIRE_X86</li> <li>• PREFER_X86_64</li> <li>• REQUIRE_X86_64</li> <li>• PREFER_I686</li> <li>• REQUIRE_I686</li> <li>• PREFER_IA64</li> <li>• REQUIRE_IA64</li> <li>• PREFER_ARMV7</li> <li>• REQUIRE_ARMV7</li> <li>• PREFER_ARMV8</li> <li>• REQUIRE_ARMV8</li> </ul>
cpu-vendor	enum	1	Host CPU vendor.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• PREFER_INTEL</li> <li>• REQUIRE_INTEL</li> <li>• PREFER_AMD</li> <li>• REQUIRE_AMD</li> </ul>
cpu-socket-count	uint64	1	Number of sockets on the host.
cpu-core-count	uint64	1	Number of cores on the host.
cpu-core-thread-count	uint64	1	Number of threads per cores on the host.

ID	Type	Cardinality	Description
cpu-feature	list	0..1	List of CPU features. See " <a href="#">vnfd:cpu-feature</a> " on page 218.
om-cpu-model-string	string	1	OpenMano CPU model string.
om-cpu-feature	list	0..n	OpenMano CPU features. See " <a href="#">vnfd:om-cpu-feature</a> " on page 220.

### **vnfd:cpu-feature**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/host-epa/cpu-feature/PREFER\_AES

ID	Type	Cardinality	Description
----	------	-------------	-------------

ID	Type	Cardinality	Description
----	------	-------------	-------------

feature enum 1

**Enumeration for CPU features:**

- AES: CPU supports advanced instruction set for AES (Advanced Encryption Standard).
- CAT: Cache Allocation Technology (CAT) allows an operating system, hypervisor, or similar system management agent to specify the amount of L3 cache (currently the last-level cache in most server and client platforms) space an application can fill.

**Note:** As a hint to hardware functionality, certain features, such as power management, may override CAT settings.

- CMT: Cache Monitoring Technology (CMT) allows an Operating System, Hypervisor, or similar system management agent to determine the usage of cache based on applications running on the platform. The implementation is directed at L3 cache monitoring (currently the last-level cache in most server and client platforms).
- DDIO: Intel Data Direct I/O (DDIO) enables Ethernet server NICs and controllers talk directly to the processor cache without a detour via system memory. This enumeration specifies if the VM requires a DDIO capable host.

**Supported values:**

- PREFER\_AES
- REQUIRE\_AES
- PREFER\_CAT
- REQUIRE\_CAT
- PREFER\_CMT
- REQUIRE\_CMT
- PREFER\_DDIO
- REQUIRE\_DDIO
- REQUIRE\_VME
- PREFER\_VME
- REQUIRE\_DE
- PREFER\_DE
- REQUIRE\_PSE
- PREFER\_PSE
- REQUIRE\_TSC
- PREFER\_TSC

**vnfd:om-cpu-feature**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/host-epa/om-cpu-feature/STRING

ID	Type	Cardinality	Description
feature	string	1	CPU feature.

**vnfd:alarm**

Information about alarms.

**REST URI path**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/alarm/STRING

**Fields**

ID	Type	Cardinality	Description
alarm-id	string	1	Reserved field for the identifier assigned by the VIM provider.
name	string	1	A human-readable string to identify the alarm.
description	string	1	Description of the alarm.
vdur-id	string	1	Identifier of the VDU record (VDUR) associated with this alarm.
actions	container	1	Actions related to the alarm. See " <a href="#">vnfd:actions</a> " on page 224.
repeat	boolean	1	[Default <i>true</i> ] Indicates whether the alarm should emit repeatedly after the associated threshold has been crossed.
enabled	boolean	1	[Default <i>true</i> ] Indicates whether the alarm has been enabled or disabled.

ID	Type	Cardinality	Description
severity	enum	1	<p>A measure of the important or urgency of the alarm.</p> <p><b>Supported types:</b></p> <ul style="list-style-type: none"><li>• LOW</li><li>• MODERATE</li><li>• CRITICAL</li></ul>
metric	enum	1	<p>Metric types that can be tracked by this alarm.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"><li>• CPU_UTILIZATION</li><li>• MEMORY_UTILIZATION</li><li>• STORAGE_UTILIZATION</li></ul>
statistic	enum	1	<p>Type of statistic to use to measure a metric, which determines threshold crossing for an alarm.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"><li>• AVERAGE</li><li>• MINIMUM</li><li>• MAXIMUM</li><li>• COUNT</li><li>• SUM</li></ul>

ID	Type	Cardinality	Description
operation	enum	1	<p>The relational operator used to define whether an alarm should be triggered when the metric statistic goes above or below a specified threshold value.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• GE — Greater than or equal to</li> <li>• LE — Less than or equal to</li> <li>• GT — Greater than</li> <li>• LT — Less than</li> <li>• EQ — Equal</li> </ul>
value	decimal164	1	Defines the threshold (up to 4 fraction digits) that, if crossed, will trigger the alarm.
period	uint32	1	Defines the length of time (seconds) for which metric data are collected to evaluate the chosen statistic.
evaluation	uint32	1	<p>Number of samples of the metric statistic used to evaluate threshold crossing.</p> <p>Each sample or evaluation is equal to the metric statistic obtained for a given period.</p> <hr/> <p><b>Note:</b> This value can be used to mitigate spikes in the metric that may skew the statistic of interest.</p> <hr/>

**vnfd:actions**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/alarm/STRING/actions

ID	Type	Cardinality	Description
ok	list	0..n	See "vnfd:actions" on page 224.
insufficient-data	list	0..n	See "vnfd:actions:insufficient-data" on page 224.
alarm	list	0..n	See "vnfd:actions:alarm" on page 224.

**vnfd:actions:ok**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/alarm/STRING/actions/ok/STRING

ID	Type	Cardinality	Description
url	string	1	

**vnfd:actions:insufficient-data**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/alarm/STRING/actions/insufficient-data/STRING

ID	Type	Cardinality	Description
url	string	1	

**vnfd:actions:alarm**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/alarm/STRING/actions/alarm/STRING

ID	Type	Cardinality	Description
url	string	1	



**vnfd:supplemental-boot-data**

Container for custom VIM data.

**REST URI path**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/supplemental-boot-data

**Fields**

ID	Type	Cardinality	Description
config-file	list	0..n	List of configuration files to be mounted onto an additional drive. See " <a href="#">vnfd:config-file</a> " on page 225.
custom-meta-data	list	0..n	List of metadata to be associated with the instance. See " <a href="#">vnfd:custom-meta-data</a> " on page 225.
boot-data-drive	boolean	1	[Default <i>false</i> ] Specifies whether the VIM should implement additional drives to host config-files or metadata.

**vnfd:config-file**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/supplemental-boot-data/config-file/STRING

ID	Type	Cardinality	Description
source	string	1	Name of the configuration file.
dest	string	1	Full path of the destination in the guest.

**vnfd:custom-meta-data**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/supplemental-boot-data/custom-meta-data/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the metadata parameter.
data-type	enum	1	Data type of the metadata parameter.
value	string	1	Value of the metadata parameter.

## vnfd:internal-connection-point

List for internal connection points. Each VNFC has zero or more internal connection points. Internal connection points are used for connecting the VNF components internal to the VNF. If a VNF has only one VNFC, it may not have any internal connection points.

### REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/internal-connection-point/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the connection point.
id	string	1	Identifier for the internal connection points.
short-name	string	1	Short name to use as a label in the UI.
type	enum	1	Type of connection point.  <b>Supported values:</b> VPORT: Virtual Port
port-security-enabled	boolean		Specifies whether to enable port security for the port.
static-ip-address	union	1	Static IP address for the connection point
internal-vld-ref	leafref	1	This is a leafref to path: ../..../internal-vld/id

**vnfd:internal-interface**

Internal interfaces enable traffic between virtual network functions.

REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/internal-interface/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the internal interface inside the VDU. <hr/> <b>Note:</b> This name has only local significance to the VDU. <hr/>
vdu-internal-connection-point-ref	leafref	1	Reference to an internal connection point. This is a leafref to path: .././internal-connection-point/id
virtual-interface	container	1	Container for the virtual interface properties. See " <a href="#">vnfd:virtual-interface</a> " on page 229.

**vnfd:virtual-interface**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/internal-interface/STRING/virtual-interface

ID	Type	Cardinality	Description
type	enum	1	<p>Specifies the type of virtual interface between VM and host.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• VIRTIO: [Default] Use the traditional VIRTIO interface</li> <li>• PCI-PASSTHROUGH: Use PCI-PASSTHROUGH interface</li> <li>• SR-IOV: Use SR-IOV interface</li> <li>• E1000 : Emulate E1000 interface</li> <li>• RTL8139 : Emulate RTL8139 interface</li> <li>• PCNET : Emulate PCNET interface</li> <li>• OM-MGMT: Used to specify OpenMANO management internal-connection type</li> </ul>
vpci	string	1	<p>Specifies the virtual PCI address in format dddd:dd:dd.d. For example:</p> <p>0000:00:12.0</p> <p>This information can be used to pass as metadata during the VM creation.</p>
bandwidth	uint64	1	Specifies the aggregate bandwidth requirement for the NIC.

**vnfd:external-interface**

External interfaces enable traffic between VNFs.

**REST URI path**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/external-interface/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the external interface inside the VDU. <hr/> <b>Note:</b> This name has only local significance to the VDU. <hr/>
vnfd-connection-point-ref	reference	1	Reference to an external connection point. This is a leafref to path: ../../connection-point/name
virtual-interface	container	1	Virtual interface properties. See " <a href="#">vnfd:virtual-interface</a> " on page 231.

**vnfd:virtual-interface**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/external-interface/STRING/virtual-interface

ID	Type	Cardinality	Description
type	enum	1	<p>Specifies the type of virtual interface between VM and host.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• VIRTIO: [Default] Use the traditional VIRTIO interface</li> <li>• PCI-PASSTHROUGH: Use PCI-PASSTHROUGH interface</li> <li>• SR-IOV: Use SR-IOV interface</li> <li>• E1000 : Emulate E1000 interface</li> <li>• RTL8139 : Emulate RTL8139 interface</li> <li>• PCNET : Emulate PCNET interface</li> <li>• OM-MGMT: Used to specify OpenMANO management internal-connection type</li> </ul>
vpci	string	1	<p>Specifies the virtual PCI address in format dddd:dd:dd.d. For example: 0000:00:12.0</p> <hr/> <p><b>Note:</b> This information can be used to pass as metadata during the VM creation.</p> <hr/>
bandwidth	uint64	1	Specifies the aggregate bandwidth requirement for the NIC.

**vnfd:volumes**

Defines disk volumes to be attached to the VDU, such as if a VNF requires multiple disks to boot the virtual machine.

**REST URI path**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/volumes/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the disk-volumes, such as vda, vdb.
description	string	1	Description for the volume.
size	uint64	1	Size of the disk, in GB.
ephemeral	empty		
image	string	1	Image name for the software image to be used.  If the image name is found within the VNF package it will be uploaded to all cloud accounts during the onboarding process. Otherwise, the image must be added to the cloud account with the same name as entered in this field.
image-checksum	string	1	Image md5sum for the software image. The md5sum, if provided, along with the image name, uniquely identifies an image uploaded to the CAL.
volume-ref	string	1	Reference to the pre-existing volume in VIM.
boot-volume	boolean	1	If set to <i>true</i> , indicates that this is a boot volume



ID	Type	Cardinality	Description
boot-priority	int32		Boot priority associated with volume.
device_bus	enum	1	Type of disk-bus on which this disk is exposed to the guest operating system.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• IDE</li> <li>• USB</li> <li>• VIRTIO</li> <li>• SCSI</li> </ul>
device_type	enum	1	Type of device as exposed to the guest operating system.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• DISK</li> <li>• CDROM</li> <li>• FLOPPY</li> <li>• LUN (logical unit number)</li> </ul>
custom-meta-data	list	0..n	List of metadata to be associated with the instance. See <a href="#">"vnfd:custom-meta-data" on page 234</a>

**vnfd:custom-meta-data**

/vnfd:vnfd-catalog/vnfd/STRING/vdu/STRING/volumes/STRING/custom-meta-data/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the metadata parameter.
data-type	enum	1	Data type of the metadata parameter.
value	string	1	Value of the metadata parameter.

## vnfd:vdu-dependency

List of virtual deployment unit (VDU) dependencies, from which the orchestrator determines the order of startup among the VDUs.

### REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/vdu-dependency/STRING

### Fields

ID	Type	Cardinality	Description
vdu-source-ref	leafref	1	Identifier of the VDU. This is a leafref to path: ../vdu/id
vdu-depends-on-ref	leafref	1	Reference to the VDU on which the source VDU depends. This is a leafref to path: ../vdu/id

## vnfd:http-endpoint

List of http endpoints to be used by monitoring parameters.

### REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/http-endpoint/STRING

### Fields

ID	Type	Cardinality	Description
path	string	1	The HTTP path on the management server.
https	boolean	1	[Default <i>false</i> ] Pick HTTPS instead of HTTP.
port	uint16	1	HTTP port to connect to.
username	string	1	HTTP basic auth user name.
password	string	1	HTTP basic auth password.
polling_interval_secs	uint8	1	[Default 2] HTTP polling interval in seconds.
method	enum	1	Method to be performed at the URI.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• GET (default)</li> <li>• POST</li> <li>• PUT</li> <li>• GET</li> <li>• DELETE</li> <li>• PATCH</li> <li>• OPTIONS</li> </ul>

ID	Type	Cardinality	Description
data	string	1	The data to be sent with POST.
headers	list	0..n	List of custom HTTP headers to put on the HTTP request. See <a href="#">"vnfd:headers" on page 237</a> .

### vnfd:headers

/vnfd:vnfd-catalog/vnfd/STRING/http-endpoint/STRING/headers/STRING

ID	Type	Cardinality	Description
key	string	1	HTTP header key.
value	string	1	HTTP header value.

## vnfd:placement-groups

List of placement groups at VNF level. The placement group construct defines the compute resource placement strategy in a cloud environment.

### REST URI path

/vnfd:vnfd-catalog/vnfd/STRING/placement-groups/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Placement group name.
requirement	string	1	Describes the intent/rationale behind this placement group. <hr/> <b>Note:</b> This free-text field is for human consumption only. <hr/>
strategy	enum	1	Strategy associated with this placement group.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• COLOCATION: [Default] Share the physical infrastructure (hypervisor/network) among all members of this group.</li> <li>• ISOLATION: Do not share the physical infrastructure (hypervisor/network) among the members of this group</li> </ul>
member-vdus	list	0..n	List of VDUs that are part of this placement group. See " <a href="#">vnfd:member-vdus</a> " on page 239.

**vnfd:member-vdus**

/vnfd:vnfd-catalog/vnfd/STRING/placement-groups/STRING/member-vdus/STRING

ID	Type	Cardinality	Description
member-vdu-ref	leafref	1	Reference to the VDU in the VNF. This is a leafref to path: ../../vdu/id

## VNF Lifecycle Management (vnfr:vnfr)

REST wrapper for the VNF lifecycle management service. Provides methods for querying a VNF and retrieving VNF records from the vnfr:vnfr-catalog.

### Methods and relative URLs

Method	Relative URL	Description
GET	/api/running/vnfr-catalog/vnfr{UUID}	Query a VNF.
GET	/api/running/vnfr-catalog/vnfr/	Retrieve a list of all VNF records from the catalog.

### Fields

ID	Type	Cardinality	Description
id	string	1	Identifier for the VNFR.
nsr-id-ref	string	1	NS instance identifier. This is a leafref to path: /nsr:ns-instance-config/nsr:nsr/nsr:id
member-vnf-index-ref	leafref	1	Path to member VNF index in the network service. /nsd:nsd-catalog/nsd:nsd/nsd:constituent-vnfd/nsd:member-vnf-index
dashboard-url	string	1	Dashboard URL.
name	string	1	VNFR name.



ID	Type	Cardinality	Description
short-name	string	1	Short name for the VNFR (for display on the UI).
vendor	string	1	Vendor/provider of the VNFR.
description	string	1	Description of the VNFR.
version	string	1	Version of the VNFR.
create-time	uint32	1	Creation timestamp of this VNF. The timestamp is expressed as seconds since unix epoch - 1970-01-01T00:00:00Z
uptime	uint32	1	Active period (in seconds) of this VNF.
vnfd	container	1	VNF descriptor used to instantiate this VNF. See <a href="#">"vnfr:vnfd" on page 254</a> .
vnfd-ref	leafref	1	Reference to a VNF descriptor. This is a leafref path to: <code>/vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id</code>
vnf-configuration	container	1	Container for the VNF configuration. <hr/> <b>Note:</b> If the NS contains multiple instances of the same VNF, each instance of the VNF may have different configuration. <hr/> See <a href="#">"vnfr:vnf-configuration" on page 314</a> .
mgmt-interface	container	1	Container for the management interface. See <a href="#">"vnfr:mgmt-interface" on page 321</a> .

ID	Type	Cardinality	Description
internal-vlr	list	0..n	List of references to virtual link records (VLR) in the VLR catalog. See <a href="#">"vnfr:internal-vlr" on page 322.</a>
connection-point	list	0..n	List of external connection points for VNFs. See <a href="#">"vnfr:connection-point" on page 323.</a>
vdur	list	0..n	List of virtual deployment units (VDU). See <a href="#">"vnfr:vdur" on page 325.</a>
http-endpoint	list	0..n	List of http endpoints to be used by monitoring-param. See <a href="#">"vnfr:http-endpoint" on page 358.</a>
monitoring-param	list	0..n	List of monitoring parameters at the network service level. See <a href="#">"vnfr:monitoring-param" on page 360.</a>
operational-status	enum	1	<p>The operational status of the VNFR instance init:</p> <ul style="list-style-type: none"> <li>• init : The VDU has just started</li> <li>• vm-init-phase : The VDUs in the VNF is being created in VIM</li> <li>• vm-alloc-pending : The VM alloc is pending in VIM</li> <li>• running : The VDU is active in VM</li> <li>• terminate : The VDU is being terminated</li> <li>• vm-terminate-phase: The VDU in the VNF is being terminated in VIM</li> <li>• terminated : The VDU is in the terminated state</li> <li>• failed : The VDU instantiation failed</li> </ul> <p>This element uses manotypes:monitoring-param</p>

ID	Type	Cardinality	Description
config-status	enum	1	The configuration status of the NS instance: <ul style="list-style-type: none"> <li>configuring: At least one of the VNFs in this instance is in configuring state</li> <li>configured: All the VNFs in this NS instance are configured or config-not-needed state</li> </ul>
placement-groups-info	list	0..n	Placement groups to which this VDU belongs and its cloud construct.  See <a href="#">"vnfr:placement-groups-info" on page 364</a> .
cloud-config	container	1	Container for cloud configuration information about public keys and users.  See <a href="#">"vnfr:cloud-config" on page 367</a> .

## MANO reference points

Or-Vnfm and Os-Ma-nfvo

### Schema

```

module vnfr
{
  namespace "urn:ietf:params:xml:ns:yang:nfvo:vnfr";
  prefix "vnfr";

  import mano-types {
    prefix "manotypes";
  }

  import rw-pb-ext {
    prefix "rwpb";
  }

  import vnfd {
    prefix "vnfd";
  }

  import nsd {
    prefix "nsd";
  }
}

```

```
import vlr {
  prefix "vlr";
}

import ietf-yang-types {
  prefix "yang";
}

import ietf-inet-types {
  prefix "inet";
}

grouping placement-group-info {
  list placement-groups-info {
    description
      "
        Placement groups to which this VDU belongs and its
        cloud construct
      ";
    key "name";
    uses manotypes:placement-group-info;
    uses manotypes:placement-group-input;
  }
}

grouping virtual-interface {
  container virtual-interface {
    description
      "Container for the virtual interface properties";

    leaf type {
      description
        "Specifies the type of virtual interface
        between VM and host.
        VIRTIO          : Use the traditional VIRTIO interface.
        PCI-PASSTHROUGH : Use PCI-PASSTHROUGH interface.
        SR-IOV          : Use SR-IOV interface.";
      type enumeration {
        enum VIRTIO;
        enum PCI-PASSTHROUGH;
        enum SR-IOV;
      }
    }

    leaf bandwidth {
      description
        "Aggregate bandwidth of the NIC.";
      type uint64;
    }

    leaf ovs-offload {
      description
        "Defines if the NIC supports OVS offload.
        MANDATORY : OVS offload support in the NIC is mandatory.
        PREFERRED  : OVS offload support in the NIC is preferred.";
    }
  }
}
```

```
    type enumeration {
      enum MANDATORY;
      enum PREFERRED;
    }
  }

  leaf vendor-id {
    description
      "Specifies the vendor specific id for
      the device. This is used when a NIC from
      specific HW vendor is required.";
    type string;
  }

  leaf datapath-library {
    description
      "Specifies the name and version of the datapath
      library the NIC is expected to support.";
    type string;
  }

  leaf provider-network-name {
    description
      "Name of the provider network to which this
      NIC is attached.";
    type string;
  }
}

container vnfr-catalog {
  config false;
  list vnfr {
    description
      "Virtual Network Function Record (VNFR).";
    key "id";
    unique "name";

    leaf id {
      description "Identifier for the VNFR.";
      type yang:uuid;
    }

    leaf nsr-id-ref {
      description
        "NS instance identifier.
        This is a leafref /nsr:ns-instance-config/nsr:nsr/nsr:id";
      type yang:uuid;
    }

    leaf member-vnf-index-ref {
      description "Reference to member VNF index in Network service.";
      type leafref {
        path "/nsd:nsd-catalog/nsd:nsd/nsd:constituent-vnfd/nsd:member-
vnf-index";
      }
    }
  }
}
```

```
}

leaf dashboard-url {
  description "Dashboard URL";
  type inet:uri;
}

leaf name {
  description "VNFR name.";
  type string;
}

leaf short-name {
  description "VNFR short name.";
  type string;
}

leaf vendor {
  description "Vendor of the VNFR.";
  type string;
}

leaf description {
  description "Description of the VNFR.";
  type string;
}

leaf version {
  description "Version of the VNFR";
  type string;
}

leaf create-time {
  description
    "Creation timestamp of this Virtual Network
    Function. The timestamp is expressed as
    seconds since unix epoch - 1970-01-01T00:00:00Z";

  type uint32;
}

leaf uptime {
  description
    "Active period of this Virtual Network Function.
    Uptime is expressed in seconds";

  type uint32;
}

container vnfd {
  description "VNF descriptor used to instantiate this VNF";
  uses vnfd:vnfd-descriptor;
}

leaf vnfd-ref {
  description "Reference to VNFD";
  type leafref {
```

```
    path "/vnfd:vnfd-catalog/vnfd:vnfd/vnfd:id";
  }
}

// Use parameters provided here to configure this VNF
uses manotypes:vnf-configuration;

// Mainly used by Mon-params & dashboard url
container mgmt-interface {
  leaf ip-address {
    type inet:ip-address;
  }
  leaf port {
    type inet:port-number;
  }
}

container ssh-key {
  description "SSH key pair used for this VNF";
  leaf public-key {
    description "Public key configured on this VNF";
    type string;
  }
  leaf private-key-file {
    description "Path to the private key file";
    type string;
  }
}
}

list internal-vlr {
  key "vlr-ref";

  leaf vlr-ref {
    description "Reference to a VLR record in the VLR catalog";
    type leafref {
      path "/vlr:vlr-catalog/vlr:vlr/vlr:id";
    }
  }

  leaf-list internal-connection-point-ref {
    type leafref {
      path "../../vdur/internal-connection-point/id";
    }
  }
}

list connection-point {
  key "name";
  description
    "List for external connection points. Each VNF has one
    or more external connection points. As the name
    implies that external connection points are used for
    connecting the VNF to other VNFs or to external networks.
    Each VNF exposes these connection points to the
    orchestrator. The orchestrator can construct network
    services by connecting the connection points between
```

```
        different VNFs. The NFVO will use VLDs and VNFFGs at
        the network service level to construct network services.";

uses vnf:common-connection-point;

leaf vlr-ref {
  description
    "Reference to the VLR associated with this connection point";
  type leafref {
    path "/vlr:vlr-catalog/vlr:vlr/vlr:id";
  }
}

leaf ip-address {
  description
    "IP address assigned to the external connection point";
  type inet:ip-address;
}

leaf mac-address {
  description
    "MAC address assigned to the external connection point";
  // type inet:mac-address;
  type string;
}

leaf connection-point-id {
  rwpb:field-inline "true";
  rwpb:field-string-max 64;
  type string;
}

}

list vdur {
  description "List of Virtual Deployment Units";
  key "id";
  unique "name";

  leaf id {
    description "Unique id for the VDU";
    type yang:uuid;
  }

  leaf name {
    description "name of the instantiated VDUR";
    type string;
  }

  leaf vdu-id-ref {
    type leafref {
      path "../..../vnfd/vdu/id";
    }
  }

  leaf vim-id {
    description "Allocated VM resource id";
    type string;
  }
}
```



```
leaf flavor-id {
  description "VIM assigned flavor id";
  type string;
}

leaf image-id {
  description "VIM assigned image id";
  type string;
}

leaf management-ip {
  description "Management IP address";
  type inet:ip-address;
}

leaf vm-management-ip {
  description "VM Private Management IP address";
  type inet:ip-address;
}

leaf console-url {
  description "Console URL for this VDU, if available";
  type inet:uri;
}

uses manotypes:vm-flavor;
uses manotypes:guest-epa;
uses manotypes:vswitch-epa;
uses manotypes:hypervisor-epa;
uses manotypes:host-epa;

uses manotypes:supplemental-boot-data;

list volumes {
  key "name";

  leaf name {
    description "Name of the disk-volumes, e.g. vda, vdb etc";
    type string;
  }

  leaf volume-id {
    description "VIM assigned volume id";
    type string;
  }

  uses manotypes:volume-info;
}

list alarms {
  description
    "A list of the alarms that have been created for this VDU";

  key "alarm-id";
  uses manotypes:alarm;
}
```

```

}

list internal-connection-point {
  key "id";
  description
    "List for internal connection points. Each VNFC
    has zero or more internal connection points.
    Internal connection points are used for connecting
    the VNF components internal to the VNF. If a VNF
    has only one VNFC, it may not have any internal
    connection points.";

  uses vnf:common-connection-point;

  leaf ip-address {
    description
      "IP address assigned to the internal connection point";
    type inet:ip-address;
  }
  leaf mac-address {
    description
      "MAC address assigned to the internal connection point";
    // type inet:mac-address;
    type string;
  }
}

list internal-interface {
  description
    "List of internal interfaces for the VNF";
  key name;

  leaf name {
    description
      "Name of internal interface. Note that this
      name has only local significance to the VDU.";
    type string;
  }

  leaf vdu-internal-connection-point-ref {
    type leafref {
      path "../..//internal-connection-point/id";
    }
  }
  uses virtual-interface;
}

list external-interface {
  description
    "List of external interfaces for the VNF.
    The external interfaces enable sending
    traffic to and from VNF.";
  key name;

  leaf name {
    description

```

```

        "Name of the external interface. Note that
        this name has only local significance.";
    type string;
}

leaf vnfd-connection-point-ref {
    description
        "Name of the external connection point.";
    type leafref {
        path "../..../connection-point/name";
    }
}
uses virtual-interface;
}
leaf operational-status {
    description
        "The operational status of the VDU
        init                : The VDU has just started.
        vm-init-phase       : The VDUs in the VNF is being created in
VIM.
        vm-alloc-pending    : The VM alloc is pending in VIM
        running             : The VDU is active in VM
        terminate           : The VDU is being terminated
        vm-terminate-phase  : The VDU in the VNF is being terminated
in VIM.
        terminated         : The VDU is in the terminated state.
        failed             : The VDU instantiation failed.
";

    type enumeration {
        rwpb:enum-type "VduOperationalStatus";
        enum init;
        enum vm-init-phase;
        enum vm-alloc-pending;
        enum running;
        enum terminate;
        enum vl-terminate-phase;
        enum terminated;
        enum failed;
    }
}
uses placement-group-info;
}

uses manotypes:monitoring-param;

leaf operational-status {
    description
        "The operational status of the VNFR instance
        init                : The VNF has just started.
        vl-init-phase       : The internal VLs in the VNF are being
instantiated.
        vm-init-phase       : The VMs for VDUs in the VNF are being
instantiated.
        running             : The VNF is in running state.
        terminate           : The VNF is being terminated.
";
};

```

```

        vm-terminate-phase : The VMs in the VNF are being terminated.
        vl-terminate-phase : The internal VLs in the VNF are being
terminated.
        terminated         : The VNF is in the terminated state.
        failed             : The VNF instantiation failed
    ";

    type enumeration {
        rwpb:enum-type "VnfrOperationalStatus";
        enum init;
        enum vl-init-phase;
        enum vm-init-phase;
        enum running;
        enum terminate;
        enum vm-terminate-phase;
        enum vl-terminate-phase;
        enum terminated;
        enum failed;
    }
}
leaf config-status {
    description
        "The configuration status of the NS instance
        configuring: At least one of the VNFs in this instance is in
configuring state
        configured: All the VNFs in this NS instance are configured or
config-not-needed state
    ";

    type enumeration {
        enum configuring {
            value 1;
        }
        enum configured {
            value 2;
        }
        enum failed {
            value 3;
        }
        enum config-not-needed {
            value 4;
        }
    }
}
uses placement-group-info;
container cloud-config {
    rwpb:msg-new VnfrCloudConfig;
    uses manotypes:cloud-config;
}
}
}

rpc create-alarm {
    description "Create an alert for a running VDU";
    input {
        leaf cloud-account {

```

```
    mandatory true;
    type string;
  }

  leaf vdur-id {
    mandatory true;
    type string;
  }

  container alarm {
    uses manotypes:alarm;
  }
}

output {
  leaf alarm-id {
    type string;
  }
}

rpc destroy-alarm {
  description "Destroy an alert that is associated with a running VDU";
  input {
    leaf cloud-account {
      mandatory true;
      type string;
    }

    leaf alarm-id {
      mandatory true;
      type string;
    }
  }
}
```

## Examples

See ["API Examples" on page 369](#).

**vnfr:vnfd**

VNF descriptor (VNFD) used to instantiate this VNF.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd

**Fields**

ID	Type	Cardinality	Description
id	string	1	Identifier for the VNFD.
name	string	1	VNFD name.
short-name	string	1	VNFD short name to use as a label in the UI.
vendor	string	1	Provider of the VNFD.
logo	string	1	<p>File path of the vendor-specific logo. For example, icons/mylogo.png</p> <p>The logo should be part of the VNF package.</p> <p>SVG format is preferred, but PNG is supported.</p> <p>Although there is no hard limit on size and dimension, a square image under 200px by 200px is preferred.</p>
description	string	1	Description of the VNFD.
version	string	1	Version of the VNFD.
vnf-configuration	container		<p>Information about the VNF configuration for the management interface.</p> <p>See "<a href="#">vnfr:vnf-configuration</a>" on page 257.</p>

ID	Type	Cardinality	Description
config-parameter	container	1	List of VNF configuration parameter requests and sources. See <a href="#">"vnfr:config-parameter" on page 264</a>
mgmt-interface	container	1	Interface over which the VNF is managed. See <a href="#">"vnfr:mgmt-interface" on page 267</a> .
internal-vld	list	0..n	List of Internal Virtual Link Descriptors (VLD). See <a href="#">"vnfr:internal-vld" on page 269</a> .
ip-profiles	list	0..n	List of IP profiles. An IP profile describes the IP characteristics for the virtual-link. See <a href="#">"vnfr:ip-profiles" on page 272</a> .
connection-point	list	0..n	The list for external connection points. See <a href="#">"vnfr:connection-point" on page 274</a> .
vdu	list	0..n	List of virtual deployment units, which are VMs that host the network function. See <a href="#">"vnfr:vdu" on page 275</a> .
vdu-dependency	list	0..n	List of VDU dependencies. See <a href="#">"vnfr:vdu-dependency" on page 305</a> .

ID	Type	Cardinality	Description
service-function-chain	enum	1	Type of node in service function chaining architecture.  <b>Supported types:</b> <ul style="list-style-type: none"> <li>• UNAWARE (default)</li> <li>• CLASSIFIER</li> <li>• SF</li> <li>• SFF</li> </ul>
service-function-type	string	1	Type of service function.  Note: This value needs to map to a service function type in the OpenDaylight platform to support VNFFG.
http-endpoint	list	0..n	List of http endpoints to be used by monitoring-param. See <a href="#">"vnfr:http-endpoint" on page 306</a> .
monitoring-param	list	0..n	List of monitoring parameters at the network service level. See <a href="#">vnfd:monitoring-param</a> .
placement-groups	list	0..n	List of placement groups at VNF level. See <a href="#">"vnfr:placement-groups" on page 312</a> .



**vnfr:vnf-configuration**

Information about the VNF configuration for the management interface.

Note: If the network service contains multiple instances of the same VNF, each VNF instance could have a different configuration.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vnf-configuration

**Fields**

ID	Type	Cardinality	Description
netconf	container	1	Use NETCONF for configuring the VNF. See <a href="#">"vnfr:vnf-configuration" on page .</a>
rest	container	1	Use REST for configuring the VNF. See <a href="#">"vnfr:rest" on page 259.</a>
script	container	1	Use a custom script for configuring the VNF. This script will be executed in the orchestrator. All required dependencies for the script should be available in the orchestrator system. See <a href="#">"vnfr:script" on page 259.</a>
juju	container	1	Use Juju for configuring the VNF. See <a href="#">"vnfr:juju" on page 260.</a>
config-access	container	1	IP address to be used to configure this VNF. See <a href="#">"vnfr:config-access" on page 260.</a>

ID	Type	Cardinality	Description
config-attributes	container	1	Miscellaneous config attributes to be considered while processing the NSD to apply configuration. See " <a href="#">vnfr:config-attributes</a> " on page 260.
config-primitive	list	0..n	List of service primitives supported by the configuration agent for this VNF. See " <a href="#">vnfr:config-primitive</a> " on page 261.
initial-config-primitive	list	0..n	Initial set of configuration primitives. See " <a href="#">vnfr:initial-config-primitive</a> " on page 263.
config-template	string	1	Configuration template for each VNF.

### vnfr:netconf

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vnf-configuration/netconf

ID	Type	Cardinality	Description
target	enum	1	NETCONF configuration target.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>RUNNING</li> <li>CANDIDATE</li> </ul>

ID	Type	Cardinality	Description
protocol	enum	1	Protocol to use for NETCONF.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>NONE</li> <li>SSH</li> </ul>
port	inet:port-number	1	Port for the NETCONF server.

**vnfr:rest**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vnf-configuration/rest

ID	Type	Cardinality	Description
port	inet_port-number	1	Port for the REST server

**vnfr:script**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vnf-configuration/script

ID	Type	Cardinality	Description
script-type	enum	1	Script type to use.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>BASH</li> <li>EXPECT</li> </ul>

**vnfr:juju**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vnf-configuration/juju

ID	Type	Cardinality	Description
charm	string	1	Juju charm to use to use with the VNF.

**vnfr:config-access**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vnf-configuration/config-access

ID	Type	Cardinality	Description
mgmt-ip-address	union	1	IP address to be used to configure this VNF. <hr/> Note: This parameter is optional if it is possible to dynamically resolve the IP. <hr/>
username	string	1	User name for configuration.
password	string	1	Password for configuration access authentication.

**vnfr:config-attributes**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vnf-configuration/config-attributes

ID	Type	Cardinality	Description
config-priority	uint64	1	Order of configuration priority to be applied to each VNF in this network service. A low number takes precedence over a high number.

ID	Type	Cardinality	Description
config-delay	uint64	1	Wait time (in seconds) before applying the configuration to this VNF.

### vnfr:config-primitive

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vnf-configuration/config-primitive/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the service primitive.
parameter	list	0..n	List of parameters to the service primitive. See " <a href="#">vnfr:config-primitive:parameter</a> " on page 261.
user-defined-script	string	1	A user-defined script. If a script is defined, the script will be executed using bash.

### vnfr:config-primitive:parameter

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vnf-configuration/config-primitive/STRING/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of parameter

ID	Type	Cardinality	Description
data-type	enum	1	Data type associated with the name.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• STRING</li> <li>• INTEGER</li> <li>• BOOLEAN</li> </ul>
mandatory	boolean	1	[Default <i>false</i> ] Defines whether this field is mandatory.
default-value	string	1	The default value for the field.  <b>Note:</b> This value is required to set the read-only and hidden parameters.
parameter-pool	string	1	NSD parameter pool name to use for this parameter.
read-only	boolean	1	If set to <i>true</i> , the value is dimmed in the UI.  <b>Note:</b> This parameter can be set to true only on parameters that specify a default-value field.
hidden	boolean	1	If set to true, the value is hidden from view in the UI.  <b>Note:</b> This parameter can be set to true only on parameters that specify a default-value field.
out	boolean	1	Specifies if this is an output of the primitive execution.

**vnfr:initial-config-primitive**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vnf-configuration/initial-config-primitive/0

ID	Type	Cardinality	Description
seq	uint64	1	Sequence number for the configuration primitive.
name	string	1	Name of the configuration primitive.
parameter	list	0..n	List of parameters to the configuration primitive. See " <a href="#">vnfr:initial-config-primitive:parameter</a> " on page 263.
user-defined-script	string	1	A user-defined script
config-primitive-ref	leafref	1	Reference to a config primitive name. <hr/> <b>Note:</b> The referenced config primitive should have all the input paramaters predefined either with default values or dependency references. <hr/>

**vnfr:initial-config-primitive:parameter**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vnf-configuration/initial-config-primitive/0/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the parameter.
value	string	1	Value of the parameter.

**vnfr:config-parameter**

List of VNF config parameter requests and sources.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/config-parameter

**Fields**

ID	Type	Cardinality	Description
config-parameter-source	list	1	List of parameters exposed by this VNF. See " <a href="#">vnfr:config-parameter-source</a> " on page 264.
config-parameter-request	list	1	List of requests for this VNF. See " <a href="#">vnfr:config-parameter-source:parameter</a> " on page 265.

**vnfr:config-parameter-source**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/config-parameter/config-parameter-source/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the source.
description	string	1	Description of the source.
attribute	string	1	Location of this source as a run-time attribute. For example, the value is ../.././mgmt-interface, ip-address which returns the ip-address assigned to the mgmt-interface after VNF instantiation.



ID	Type	Cardinality	Description
config-primitive-name-ref	leafref	1	A leafref to the configuration primitive.  Note: This refers to a config parameter in which output parameter is referenced in <code>out-parameter</code> .
parameter-ref	leafref	1	Name of the output parameter in the config primitive.
value	string	1	Predefined value to be used for this source.
parameter	list	0..n	List of parameters for this source.  See " <a href="#">vnfr:config-parameter-source:parameter</a> " on page 265

### vnfr:config-parameter-source:parameter

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/config-parameter/config-parameter-source/STRING/parameter/STRING

ID	Type	Cardinality	Description
config-primitive-name-ref	leafref	1	Name of the configuration primitive where this source will be used.
config-primitive-parameter-ref	leafref	1	Parameter name of the config primitive.

**vnfr:config-parameter-request**

ID	Type	Cardinality	Description
name	string	1	Name of this parameter request.
description	string	1	Description of this request.
parameter	list	0..n	List of parameters for this request. See " <a href="#">vnfr:config-parameter-request:parameter</a> " on page 266.

**vnfr:config-parameter-request:parameter**

ID	Type	Cardinality	Description
config-primitive-name-ref	leafref	1	Name of the configuration primitive where this request will used.
config-primitive-parameter-ref	leafref	1	Parameter name of the config primitive.

**vnfr:mgmt-interface**

Interface over which the VNF is managed.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/mgmt-interface

**Fields**

ID	Type	Cardinality	Description
ip-address	union	1	Specifies the static IP address for managing the VNF.
vdu-id	leafref	1	Use the default management interface on this VDU. This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd/vnfd:vdu/vnfd:id
cp	leafref	1	Use the IP address for the VNFD associated with this connection point endpoint. This is a leafref to path: /vnfd:vnfd-catalog/vnfd:vnfd/vnfd:connection-point/vnfd:name
port	uint16	1	Port number for the management interface.
dashboard-params	container	1	Parameters for the VNF dashboard of the management interface. See <a href="#">"vnfr:dashboard-params" on page 268</a> .

**vnfr:dashboard-params**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/mgmt-interface/dashboard-params

ID	Type	Cardinality	Description
path	string	1	The HTTP path for the dashboard.
https	boolean	1	[Default <i>false</i> ] Choose HTTPS instead of HTTP.
port	uint16	1	The HTTP port for the dashboard

**vnfr:internal-vld**

List of internal Virtual Link Descriptors (VLDs). Internal VLDs describe the basic topology of the connectivity—such as E-LAN— between internal VNF Components (VNFC) within the system.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/internal-vld/STRING

**Fields**

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the internal VLD.
name	string	1	Name of the internal VLD.
short-name	string	1	Short name for the internal VLD to use as a label in the UI.
description	string	1	Description of the internal VLD.
type	enum	1	Type of virtual link.  <b>Supported values:</b> ELAN: A multipoint service that connects a set of VDUs.
root-bandwidth	uint64	1	For ELAN this is the aggregate bandwidth.
leaf-bandwidth	uint64	1	For ELAN this is the bandwidth of branches.
internal-connection-point	list	0..n	List of internal connection points in this VLD. See " <a href="#">vnfr:internal-connection-point</a> " on page 270.

ID	Type	Cardinality	Description
provider-network	container	1	Container for the provider network. See " <a href="#">vnfr:provider-network</a> " on page 270.
vim-network-name	string	1	Name of pre-provisioned network in the VIM (cloud) account.
ip-profile-ref	string	1	Named reference to an ip-profile object.

### **vnfr:internal-connection-point**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/internal-vld/STRING/internal-connection-point/STRING

ID	Type	Cardinality	Description
id-ref	leafref	1	Reference to the internal connection point ID.

### **vnfr:provider-network**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/internal-vld/STRING/provider-network

ID	Type	Cardinality	Description
physical-network	string	1	Name of the physical network on which the provider network is built.

ID	Type	Cardinality	Description
overlay-type	enum	1	<p>Identifies the type of the overlay network, which is a virtual network that is built on top of an existing network and is supported by its infrastructure.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• LOCAL — A network that can be realized on a single host only.</li> <li>• FLAT — The simplest networking environment in which each instance receives a fixed IP from the pool. All instances are attached to the same bridges.</li> <li>• VLAN — A network of computers in which the computers behaves as if they are connected to the same wire. However, the computers might be physically located on different segments of a LAN.</li> <li>• VXLAN — A proposed encapsulation protocol for running an overlay network on existing Layer 3 infrastructure</li> <li>• GRE — GRE tunnels encapsulate isolated Layer 2 network traffic in IP packets. Packets are routed between compute and networking nodes using the hosts' network connectivity and routing tables.</li> </ul>
segmentation-id	uint32	1	Segmentation ID

**vnfr:ip-profiles**

List of IP profiles. IP profiles describe the IP characteristics for the virtual link.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/ip-profiles/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the IP profile.
description	string	1	Description of the IP profile.
ip-profile-params	container	1	Information about the IP profile. See " <a href="#">vnfr:ip-profile-params</a> " on page 272

**vnfr:ip-profile-params**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/ip-profiles/STRING/ip-profile-params

ID	Type	Cardinality	Description
ip-version	enum	1	[Default IPv4] Version of the Internet Protocol used.
subnet-address	union	1	Subnet IP prefix associated with this IP profile.
gateway-address	union	1	IP address of the default gateway associated with this IP profile.
security-group	string	1	Name of the security group.



ID	Type	Cardinality	Description
dns-server	list	0..n	List of DNS servers associated with this IP profile. See " <a href="#">vnfr:dns-server</a> " on page 273.
dhcp-params	container	1	Container for DHCP parameters. See " <a href="#">vnfr:ip-profile-params</a> " on page 272.
subnet-prefix-pool	string	1	VIM-specific reference to pre-created subnet prefix.

### vnfr:dns-server

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/ip-profiles/STRING/ip-profile-params

ID	Type	Cardinality	Description
address union		1	List of DNS servers associated with this IP profile.

### vnfr:dhcp-params

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/ip-profiles/STRING/ip-profile-params/dhcp-params

ID	Type	Cardinality	Description
enabled	boolean	1	[Default <i>true</i> ] Indicates if DHCP is enabled.
start-address	union	1	Start IP address of the IP address range associated with DHCP domain.
count	uint32	1	Size of the DHCP pool associated with DHCP domain.

**vnfr:connection-point**

List of external connection points, in which each VNF:

- Has one or more points that are used to connect a VNF to other VNFs or to external networks
- Exposes these connection points to the orchestrator (NFVO)

The orchestrator constructs network services by connecting the connection points between different VNFs.

The orchestrator uses VLDs and VNFFGs at the network service level to construct network services.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/connection-point/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the connection point.
id	string	1	Unique identifier of the connection point
short-name	string	1	Short name of the connection point to use as a label in the UI.
type	enum	1	Type of connection point. <b>Supported values:</b> VPORT: Virtual Port
port-security-enabled	boolean	1	Enables the port security for the port
static-ip-address	union	1	Static IP address for the connection point

**vnfr:vdv**

A VDU is a basic part of VNF. VDUs are virtual machines that host the network function, such as:

- Virtual machine specification
- Computation properties (RAM size, disk size, memory page size, number of CPUs, number of cores per CPU, number of threads per core)
- Storage requirements
- Initiation and termination scripts
- High availability redundancy model
- Scale out/scale in limits

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING

**Fields**

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the VDU.
name	string	1	Unique name for the VDU.
description	string	1	Description of the VDU.
count	uint64	1	Number of instances of the VDU.
mgmt-vpci	string	1	Specifies the virtual PCI address, expressed in the following format dddd:dd:dd.d. For example 0000:00:12.0.  This information can be used to pass as metadata during the VM creation.
vm-flavor	container	1	Flavor of the virtual machine (VM) instance.  See " <a href="#">vnfr:vm-flavor</a> " on page 278.

ID	Type	Cardinality	Description
guest-epa	container	1	EPA attributes for the guest operating system. See <a href="#">"vnfr:guest-epa" on page 278.</a>
vswitch-epa	container	1	EPA attributes for Open vSwitch. See <a href="#">"vnfr:vswitch-epa" on page 284</a>
hypervisor-epa	container	1	EPA attributes for the hypervisor. See <a href="#">"vnfr:hypervisor-epa" on page 285.</a>
host-epa	container	1	EPA attributes for the host operating system. See <a href="#">"vnfr:host-epa" on page 286.</a>
alarm	list	0..n	A list of alarms. See <a href="#">"vnfr:alarm" on page 291</a>
image	string	1	Image name for the software image.  If the image name is found within the VNF package it will be uploaded to all cloud accounts during the onboarding process. Otherwise, the image must be added to the cloud account with the same name as entered in this field.
image-checksum	string	1	Image md5sum for the software image. The md5sum, if provided, along with the image name, uniquely identifies an image uploaded to the CAL.
cloud-init	string	1	Contents of cloud-init script, provided inline, in cloud-config format
cloud-init-file	string	1	Name of file with contents of cloud-init script in cloud-config format.

ID	Type	Cardinality	Description
supplemental-boot-data	container	1	Container for custom VIM data. See <a href="#">"vnfr:supplemental-boot-data"</a> on page 296.
internal-connection-point	list	0..n	List for internal connection points. See <a href="#">"vnfr:internal-connection-point"</a> on page 298.
internal-interface	list	0..n	List of internal interfaces for the VNF. See <a href="#">"vnfr:internal-interface"</a> on page 299.
external-interface	list	0..n	List of external interfaces for the VNF. See <a href="#">"vnfr:external-interface"</a> on page 301.
volumes	list	0..n	List of disk-volumes to be attached to VDU. See <a href="#">"vnfr:volumes"</a> on page 303.

**vnfr:vm-flavor**

Flavor is an alternative term for a VM instance type.

REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/vm-flavor

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/vm-flavor

Fields

ID	Type	Cardinality	Description
vpcu-count	uint16	1	Number of VCPUs for the VM.
memory-mb	uint64	1	Amount of memory in MB to allocate to the VM.
storage-gb	uint64	1	Amount of disk space in GB to allocate to the VM.

**vnfr:guest-epa**

EPA attributes for the guest operating system.

REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/guest-epa

Fields

ID	Type	Cardinality	Description
trusted-execution	boolean	1	If set to <i>true</i> , indicates this VM should be allocated from trusted pool.

ID	Type	Cardinality	Description
mempage-size	enum	1	<p>Memory page allocation size.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• LARGE: Require hugepages (either 2MB or 1GB)</li> <li>• SMALL: Doesn't require hugepages</li> <li>• SIZE_2MB: Requires 2MB hugepages</li> <li>• SIZE_1GB: Requires 1GB hugepages</li> <li>• PREFER_LARGE: Application prefers hugepages</li> </ul> <hr/> <p><b>Note:</b> If a VM requires hugepages, choose LARGE or SIZE_2MB or SIZE_1GB. If the VM prefers hugepages, choose PREFER_LARGE.</p> <hr/>
cpu-pinning-policy	enum	1	<p>Describes the association between virtual CPUs in the guest and the physical CPUs in the host.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• DEDICATED: Virtual CPUs are pinned to physical CPUs</li> <li>• SHARED: Multiple VMs may share the same physical CPUs.</li> <li>• ANY: (Default) Any policy is acceptable for the VM</li> </ul>
cpu-thread-pinning-policy	enum	1	<p>Describes how to place the guest CPUs when the host supports hyper threads.</p> <p><b>Default values:</b></p> <ul style="list-style-type: none"> <li>• AVOID: Avoids placing a guest on a host with threads.</li> <li>• SEPARATE: Places vCPUs on separate cores, and avoids placing two vCPUs on two threads of same core.</li> <li>• ISOLATE: Places each vCPU on a different core, and places no vCPUs from a different guest on the same core.</li> <li>• PREFER: Attempts to place vCPUs on threads of the same core.</li> </ul>

ID	Type	Cardinality	Description
pcie-device	list	0..1	List of PCIE passthrough devices. See <a href="#">"vnfr:pcie-device" on page 281</a>
numa-unaware	empty		Details about the numa-node-policy are null.
numa-node-policy	container	1	Defines numa topology of the guest, specifying if the guest should run on a host with one numa node or multiple numa nodes.  <b>Example:</b> A guest might need 8 VCPUs and 4 GB of memory with the VCPUs and memory distributed across multiple NUMA nodes. In this scenario, NUMA node 1 could run with 6 VCPUs and 3GB, and NUMA node 2 could run with 2 vcpus and 1GB.  See <a href="#">"vnfr:numa-node-policy" on page 281</a>



**vnfr:pcie-device**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/guest-epa/pcie-device/STRING

ID	Type	Cardinality	Description
device-id	string	1	Device identifier.
count	uint64	1	Number of devices to attach to the VM.

**vnfr:numa-node-policy**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/guest-epa/numa-node-policy

ID	Type	Cardinality	Description
node-cnt	uint16	1	Number of NUMA nodes to expose to the VM.
mem-policy	enum	1	Specifies how to allocate memory in a multi-node scenario.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• STRICT: The memory must be allocated from the memory attached to the NUMA node.</li> <li>• PREFERRED: The memory should be allocated from the memory attached to the NUMA node</li> </ul>
node	list	0..n	List of NUMA nodes.  See " <a href="#">vnfr:numa-node-policy:node</a> " on page 282.

**vnfr:numa-node-policy:node**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/guest-epa/numa-node-policy/node/0

ID	Type	Cardinality	Description
id	uint64	1	NUMA node identification. Typically 0 or 1.
vcpu	list	0..n	List of VCPUs to allocate on this NUMA node. See " <a href="#">vnfr:numa-node-policy:node:vcpu</a> " on page 282
memory-mb	uint64	1	Memory size in MB for this NUMA node.
num-cores	uint8	1	Number of cores.
paired-threads	container	1	Container for paired threads. See " <a href="#">vnfr:numa-node-policy:node:paired-threads</a> " on page 283.
num-threads	uint8	1	OpenMANO NUMA type selection.

**vnfr:numa-node-policy:node:vcpu**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/guest-epa/numa-node-policy/node/0/vcpu/0

ID	Type	Cardinality	Description
id	uint64	1	List of VCPUs IDs to allocate on this NUMA node.

**vnfr:numa-node-policy:node:paired-threads**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/guest-epa/numa-node-policy/node/0/paired-threads

ID	Type	Cardinality	Description
num-paired-threads	uint8	1	Number of paired-threads.
paired-thread-ids	list	0..n	List of thread paired to use in case of paired thread NUMA. See " <a href="#">vnfr:numa-node-policy:node:paired-threads:paired-thread-ids</a> " on page 283

**vnfr:numa-node-policy:node:paired-threads:paired-thread-ids**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/guest-epa/numa-node-policy/node/0/paired-threads/paired-thread-ids/0

ID	Type	Cardinality	Description
thread-a	uint8	1	Thread ID
thread-b	uint8	1	Thread ID

**vnfr:vswitch-epa**

EPA attributes for Open vSwitch.

REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/vswitch-epa

Fields

ID	Type	Cardinality	Description
ovs-acceleration	enum	1	<p>Specifies Open vSwitch acceleration mode.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>MANDATORY: OVS acceleration is required</li> <li>PREFERRED: OVS acceleration is preferred</li> <li>DISABLED: OVS acceleration is disabled.</li> </ul>
ovs-offload	enum	1	<p>Specifies Open vSwitch hardware offload mode.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>MANDATORY: OVS offload is required</li> <li>PREFERRED: OVS offload is preferred</li> <li>DISABLED: OVS offload is disabled</li> </ul>

**vnfr:hypervisor-epa**

EPA attributes for the hypervisor.

REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/hypervisor-epa

Fields

ID	Type	Cardinality	Description
type	enum	1	Specifies the type of hypervisor. For example, KVM, XEN.  Value can be: <ul style="list-style-type: none"><li>• KVM: KVM</li><li>• XEN: XEN</li></ul>
version	string	1	Version of the hypervisor.

**vnfr:host-epa**

Specifies the host-level EPA attributes.

REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/host-epa

Fields

ID	Type	Cardinality	Description
cpu-model	enum	1	<p>Host CPU model.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• PREFER_WESTMERE</li> <li>• REQUIRE_WESTMERE</li> <li>• PREFER_SANDYBRIDGE</li> <li>• REQUIRE_SANDYBRIDGE</li> <li>• PREFER_IVYBRIDGE</li> <li>• REQUIRE_IVYBRIDGE</li> <li>• PREFER_HASWELL</li> <li>• REQUIRE_HASWELL</li> <li>• PREFER_BROADWELL</li> <li>• REQUIRE_BROADWELL</li> <li>• PREFER_NEHALEM</li> <li>• REQUIRE_NEHALEM</li> <li>• PREFER_PENRYN</li> <li>• REQUIRE_PENRYN</li> <li>• PREFER_CONROE</li> <li>• REQUIRE_CONROE</li> <li>• PREFER_CORE2DUO</li> <li>• REQUIRE_CORE2DUO</li> </ul>

ID	Type	Cardinality	Description
cpu-arch	enum	1	Host CPU architecture.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• PREFER_X86</li> <li>• REQUIRE_X86</li> <li>• PREFER_X86_64</li> <li>• REQUIRE_X86_64</li> <li>• PREFER_I686</li> <li>• REQUIRE_I686</li> <li>• PREFER_IA64</li> <li>• REQUIRE_IA64</li> <li>• PREFER_ARMV7</li> <li>• REQUIRE_ARMV7</li> <li>• PREFER_ARMV8</li> <li>• REQUIRE_ARMV8</li> </ul>
cpu-vendor	enum	1	Host CPU vendor.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• PREFER_INTEL</li> <li>• REQUIRE_INTEL</li> <li>• PREFER_AMD</li> <li>• REQUIRE_AMD</li> </ul>
cpu-socket-count	uint64	1	Number of sockets on the host.
cpu-core-count	uint64	1	Number of cores on the host.
cpu-core-thread-count	uint64	1	Number of threads per cores on the host.

ID	Type	Cardinality	Description
cpu-feature	list	0..1	List of CPU features. See " <a href="#">vnfr:cpu-feature</a> " on page 288.
om-cpu-model-string	string	1	OpenMano CPU model string.
om-cpu-feature	list	0..n	OpenMano CPU features. See " <a href="#">vnfd:om-cpu-feature</a> " on page 290.

### vnfr:cpu-feature

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/host-epa/cpu-feature/PREFER\_AES

ID	Type	Cardinality	Description
----	------	-------------	-------------



ID	Type	Cardinality	Description
feature enum 1			<p data-bbox="537 346 911 373"><b>Enumeration for CPU features:</b></p> <ul data-bbox="578 396 1414 657" style="list-style-type: none"> <li data-bbox="578 396 1414 457">• AES: CPU supports advanced instruction set for AES (Advanced Encryption Standard).</li> <li data-bbox="578 474 1414 657">• CAT: Cache Allocation Technology (CAT) allows an operating system, hypervisor, or similar system management agent to specify the amount of L3 cache (currently the last-level cache in most server and client platforms) space an application can fill.</li> </ul> <div data-bbox="597 680 1430 779" style="border: 1px dashed gray; padding: 5px;"> <p data-bbox="613 695 1377 766"><b>Note:</b> As a hint to hardware functionality, certain features, such as power management, may override CAT settings.</p> </div> <ul data-bbox="578 804 1414 1192" style="list-style-type: none"> <li data-bbox="578 804 1414 1024">• CMT: Cache Monitoring Technology (CMT) allows an Operating System, Hypervisor, or similar system management agent to determine the usage of cache based on applications running on the platform. The implementation is directed at L3 cache monitoring (currently the last-level cache in most server and client platforms).</li> <li data-bbox="578 1047 1414 1192">• DDIO: Intel Data Direct I/O (DDIO) enables Ethernet server NICs and controllers talk directly to the processor cache without a detour via system memory. This enumeration specifies if the VM requires a DDIO capable host.</li> </ul> <p data-bbox="537 1234 760 1262"><b>Supported values:</b></p> <ul data-bbox="578 1283 818 2074" style="list-style-type: none"> <li data-bbox="578 1283 781 1310">• PREFER_AES</li> <li data-bbox="578 1333 800 1360">• REQUIRE_AES</li> <li data-bbox="578 1383 781 1411">• PREFER_CAT</li> <li data-bbox="578 1434 800 1461">• REQUIRE_CAT</li> <li data-bbox="578 1484 792 1512">• PREFER_CMT</li> <li data-bbox="578 1535 810 1562">• REQUIRE_CMT</li> <li data-bbox="578 1585 800 1612">• PREFER_DDIO</li> <li data-bbox="578 1635 818 1663">• REQUIRE_DDIO</li> <li data-bbox="578 1686 810 1713">• REQUIRE_VME</li> <li data-bbox="578 1736 792 1764">• PREFER_VME</li> <li data-bbox="578 1787 784 1814">• REQUIRE_DE</li> <li data-bbox="578 1837 768 1864">• PREFER_DE</li> <li data-bbox="578 1887 797 1915">• REQUIRE_PSE</li> <li data-bbox="578 1938 781 1965">• PREFER_PSE</li> <li data-bbox="578 1988 797 2016">• REQUIRE_TSC</li> <li data-bbox="578 2039 781 2066">• PREFER_TSC</li> </ul>

**vnfd:om-cpu-feature**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/host-epa/om-cpu-feature/STRING

ID	Type	Cardinality	Description
feature	string	1	CPU feature.

**vnfr:alarm**

Information about alarms.

REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/alarm/STRING

Fields

ID	Type	Cardinality	Description
alarm-id	string	1	Reserved field for the identifier assigned by the VIM provider.
name	string	1	A human-readable string to identify the alarm.
description	string	1	Description of the alarm.
vdur-id	string	1	Identifier of the VDU record (VDUR) associated with this alarm.
actions	container	1	Actions related to the alarm. See " <a href="#">vnfr:actions</a> " on page 294.
repeat	boolean	1	[Default <i>true</i> ] Indicates whether the alarm should emit repeatedly after the associated threshold has been crossed.
enabled	boolean	1	[Default <i>true</i> ] Indicates whether the alarm has been enabled or disabled.

ID	Type	Cardinality	Description
severity	enum	1	<p>A measure of the important or urgency of the alarm.</p> <p><b>Supported types:</b></p> <ul style="list-style-type: none"><li>• LOW</li><li>• MODERATE</li><li>• CRITICAL</li></ul>
metric	enum	1	<p>Metric types that can be tracked by this alarm.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"><li>• CPU_UTILIZATION</li><li>• MEMORY_UTILIZATION</li><li>• STORAGE_UTILIZATION</li></ul>
statistic	enum	1	<p>Type of statistic to use to measure a metric, which determines threshold crossing for an alarm.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"><li>• AVERAGE</li><li>• MINIMUM</li><li>• MAXIMUM</li><li>• COUNT</li><li>• SUM</li></ul>

ID	Type	Cardinality	Description
operation	enum	1	<p>The relational operator used to define whether an alarm should be triggered when the metric statistic goes above or below a specified threshold value.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• GE — Greater than or equal to</li> <li>• LE — Less than or equal to</li> <li>• GT — Greater than</li> <li>• LT — Less than</li> <li>• EQ — Equal</li> </ul>
value	decimal164	1	Defines the threshold (up to 4 fraction digits) that, if crossed, will trigger the alarm.
period	uint32	1	Defines the length of time (seconds) for which metric data are collected to evaluate the chosen statistic.
evaluation	uint32	1	<p>Number of samples of the metric statistic used to evaluate threshold crossing.</p> <p>Each sample or evaluation is equal to the metric statistic obtained for a given period.</p> <hr/> <p><b>Note:</b> This value can be used to mitigate spikes in the metric that may skew the statistic of interest.</p> <hr/>

**vnfr:actions**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/alarm/STRING/actions

ID	Type	Cardinality	Description
ok	list	0..n	See "vnfr:actions" on page 294.
insufficient-data	list	0..n	See "vnfr:actions:insufficient-data" on page 294.
alarm	list	0..n	See "vnfr:actions:alarm" on page 295.

**vnfr:actions:ok**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/alarm/STRING/actions/ok/STRING

ID	Type	Cardinality	Description
url	string	1	

**vnfr:actions:insufficient-data**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/alarm/STRING/actions/insufficient-data/STRING

ID	Type	Cardinality	Description
url	string	1	

**vnfr:actions:alarm**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/alarm/STRING/actions/alarm/STRING

ID	Type	Cardinality	Description
url	string	1	

**vnfr:supplemental-boot-data**

Container for custom VIM data.

REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/supplemental-boot-data

Fields

ID	Type	Cardinality	Description
config-file	list	0..n	List of configuration files to be mounted onto an additional drive. See " <a href="#">vnfr:config-file</a> " on page 296.
custom-meta-data	list	0..n	List of metadata to be associated with the instance. See " <a href="#">vnfr:custom-meta-data</a> " on page 296.
boot-data-drive	boolean	1	[Default <i>false</i> ] Specifies whether the VIM should implement additional drives to host config-files or metadata.

**vnfr:config-file**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/supplemental-boot-data/config-file/STRING

ID	Type	Cardinality	Description
source	string	1	Name of the configuration file.
dest	string	1	Full path of the destination in the guest.

**vnfr:custom-meta-data**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/supplemental-boot-data/custom-meta-data/STRING



ID	Type	Cardinality	Description
name	string	1	Name of the metadata parameter.
data-type	enum	1	Data type of the metadata parameter.
value	string	1	Value of the metadata parameter.

**vnfr:internal-connection-point**

List for internal connection points. Each VNFC has zero or more internal connection points. Internal connection points are used for connecting the VNF components internal to the VNF. If a VNF has only one VNFC, it may not have any internal connection points.

REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/internal-connection-point/STRING

Fields

ID	Type	Cardinality	Description
name	string	1	Name of the connection point.
id	string	1	Identifier for the internal connection points.
short-name	string	1	Short name to use as a label in the UI.
type	enum	1	Type of connection point.  <b>Supported values:</b> VPORT: Virtual Port
port-security-enabled	boolean		Specifies whether to enable port security for the port.
static-ip-address	union	1	Static IP address for the connection point
internal-vld-ref	leafref	1	This is a leafref to path: ../../internal-vld/id

**vnfr:internal-interface**

Internal interfaces enable traffic between virtual network functions.

REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/internal-interface/STRING

## Fields

ID	Type	Cardinality	Description
name	string	1	Name of the internal interface inside the VDU. <hr/> <b>Note:</b> This name has only local significance to the VDU. <hr/>
vdu-internal-connection-point-ref	leafref	1	Reference to an internal connection point. This is a leafref to path: .././internal-connection-point/id
virtual-interface	container	1	Container for the virtual interface properties. See " <a href="#">vnfr:virtual-interface</a> " on page 300.

**vnfr:virtual-interface**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/internal-interface/STRING/virtual-interface

ID	Type	Cardinality	Description
type	enum	1	<p>Specifies the type of virtual interface between VM and host.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• VIRTIO: [Default] Use the traditional VIRTIO interface</li> <li>• PCI-PASSTHROUGH: Use PCI-PASSTHROUGH interface</li> <li>• SR-IOV: Use SR-IOV interface</li> <li>• E1000 : Emulate E1000 interface</li> <li>• RTL8139 : Emulate RTL8139 interface</li> <li>• PCNET : Emulate PCNET interface</li> <li>• OM-MGMT: Used to specify OpenMANO management internal-connection type</li> </ul>
vpci	string	1	<p>Specifies the virtual PCI address in format dddd:dd:dd.d. For example:</p> <p>0000:00:12.0</p> <p>This information can be used to pass as metadata during the VM creation.</p>
bandwidth	uint64	1	Specifies the aggregate bandwidth requirement for the NIC.

**vnfr:external-interface**

External interfaces enable traffic between VNFs.

REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/external-interface/STRING

Fields

ID	Type	Cardinality	Description
name	string	1	Name of the external interface inside the VDU. <hr/> <b>Note:</b> This name has only local significance to the VDU. <hr/>
vnfd-connection-point-ref	reference	1	Reference to an external connection point. This is a leafref to path: ../..../connection-point/name
virtual-interface	container	1	Virtual interface properties. See " <a href="#">vnfr:virtual-interface</a> " on page 302.

**vnfr:virtual-interface**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/external-interface/STRING/virtual-interface

ID	Type	Cardinality	Description
type	enum	1	<p>Specifies the type of virtual interface between VM and host.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• VIRTIO: [Default] Use the traditional VIRTIO interface</li> <li>• PCI-PASSTHROUGH: Use PCI-PASSTHROUGH interface</li> <li>• SR-IOV: Use SR-IOV interface</li> <li>• E1000 : Emulate E1000 interface</li> <li>• RTL8139 : Emulate RTL8139 interface</li> <li>• PCNET : Emulate PCNET interface</li> <li>• OM-MGMT: Used to specify OpenMANO management internal-connection type</li> </ul>
vpci	string	1	<p>Specifies the virtual PCI address in format dddd:dd:dd.d. For example: 0000:00:12.0</p> <hr/> <p><b>Note:</b> This information can be used to pass as metadata during the VM creation.</p> <hr/>
bandwidth	uint64	1	Specifies the aggregate bandwidth requirement for the NIC.

**vnfr:volumes**

Defines disk volumes to be attached to the VDU, such as if a VNF requires multiple disks to boot the virtual machine.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/volumes/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the disk-volumes, such as vda, vdb.
description	string	1	Description for the volume.
size	uint64	1	Size of the disk, in GB.
ephemeral	empty		
image	string	1	Image name for the software image to be used. If the image name is found within the VNF package it will be uploaded to all cloud accounts during the onboarding process. Otherwise, the image must be added to the cloud account with the same name as entered in this field.
image-checksum	string	1	Image md5sum for the software image. The md5sum, if provided, along with the image name, uniquely identifies an image uploaded to the CAL.
volume-ref	string	1	Reference to the pre-existing volume in VIM.
boot-volume	boolean	1	If set to <i>true</i> , indicates that this is a boot volume

ID	Type	Cardinality	Description
boot-priority	int32		Boot priority associated with volume.
device_bus	enum	1	Type of disk-bus on which this disk is exposed to the guest operating system.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• IDE</li> <li>• USB</li> <li>• VIRTIO</li> <li>• SCSI</li> </ul>
device_type	enum	1	Type of device as exposed to the guest operating system.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• DISK</li> <li>• CDROM</li> <li>• FLOPPY</li> <li>• LUN (logical unit number)</li> </ul>
custom-meta-data	list	0..n	List of metadata to be associated with the instance. See <a href="#">"vnfr:custom-meta-data" on page 305</a>



**vnfr:custom-meta-data**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu/STRING/volumes/STRING/custom-meta-data/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the metadata parameter.
data-type	enum	1	Data type of the metadata parameter.
value	string	1	Value of the metadata parameter.

**vnfr:vdu-dependency**

List of virtual deployment unit (VDU) dependencies, from which the orchestrator determines the order of startup among the VDUs.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/vdu-dependency/STRING

**Fields**

ID	Type	Cardinality	Description
vdu-source-ref	leafref	1	Identifier of the VDU. This is a leafref to path: ../vdu/id
vdu-depends-on-ref	leafref	1	Reference to the VDU on which the source VDU depends. This is a leafref to path: ../vdu/id

**vnfr:http-endpoint**

List of http endpoints to be used by monitoring parameters.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/http-endpoint/STRING

**Fields**

ID	Type	Cardinality	Description
path	string	1	The HTTP path on the management server.
https	boolean	1	[Default <i>false</i> ] Pick HTTPS instead of HTTP.
port	uint16	1	HTTP port to connect to.
username	string	1	HTTP basic auth user name.
password	string	1	HTTP basic auth password.
polling_interval_secs	uint8	1	[Default 2] HTTP polling interval in seconds.
method	enum	1	Method to be performed at the URI.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• GET (default)</li> <li>• POST</li> <li>• PUT</li> <li>• GET</li> <li>• DELETE</li> <li>• PATCH</li> <li>• OPTIONS</li> </ul>
data	string	1	The data to be sent with POST.

ID	Type	Cardinality	Description
headers	list	0..n	List of custom HTTP headers to put on the HTTP request. See " <a href="#">vnfr:headers</a> " on page 307.

### **vnfr:headers**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/http-endpoint/STRING/headers/STRING

ID	Type	Cardinality	Description
key	string	1	HTTP header key.
value	string	1	HTTP header value.

**vnfr:monitoring-param**

List of monitoring parameters at the network service level.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/monitoring-param/STRING

**Fields**

ID	Type	Cardinality	Description
id	string	1	Identifier for the monitoring parameter.
name	string	1	Name of the monitoring parameter.
http-endpoint-ref	leafref	1	Reference to the HTTP endpoint. This is a leafref path: ../..../http-endpoint/path See <a href="#">"vnfd:http-endpoint" on page 236</a> .
json-query-method	enum	1	The method to extract a value from a JSON response. <b>Supported values:</b> <ul style="list-style-type: none"> <li>NAMEKEY: [Default] Use the name as the key for a non-nested value.</li> <li>JSONPATH: Use jsonpath-rw implementation to extract a value.</li> <li>OBJECTPATH: Use objectpath implementation to extract a value.</li> </ul>
json-query-params	container	1	Object for JSON query parameters. See <a href="#">"vnfr:json-query-params" on page 310</a> .
description	string	1	Description of the monitoring parameter.

ID	Type	Cardinality	Description
group-tag	string	1	Tag to group monitoring parameters.
widget-type	enum	1	Type of the widget, typically used by the UI.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• HISTOGRAM</li> <li>• BAR</li> <li>• GAUGE</li> <li>• SLIDER</li> <li>• COUNTER</li> <li>• TEXTBOX</li> </ul>
units	string	1	Units for the monitoring parameter, such as megabits per second.
value-type	enum	1	The type of the parameter value.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• INT (default)</li> <li>• DECIMAL</li> <li>• STRING</li> </ul>
numeric-constraints	container	1	Constraints for the numbers. See <a href="#">"vnfr:numeric-constraints" on page 310.</a>
text-constraints	container	1	Constraints for the text strings. See <a href="#">"vnfr:text-constraints" on page 311.</a>
value-integer	int64	1	Current value for integer parameter.

ID	Type	Cardinality	Description
value-decimal	decimal164	1	Current value for decimal parameter, up to 4 fraction digits.
value-string	string	1	Current value for the string parameter.

### vnfr:json-query-params

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/monitoring-param/STRING/json-query-params

ID	Type	Cardinality	Description
json-path	string	1	The JSON path used to extract value from the JSON structure.
object-path	string	1	The object path to use to extract value form the JSON structure.

### vnfr:numeric-constraints

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/monitoring-param/STRING/numeric-constraints

ID	Type	Cardinality	Description
min-value	uint64	1	Minimum value for the parameter.
max-value	uint64	1	Maximum value for the parameter.

**vnfr:text-constraints**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/monitoring-param/STRING/text-constraints

ID	Type	Cardinality	Description
min-length	uint8	1	Minimum string length for the parameter.
max-length	uint8	1	Maximum string length for the parameter.

**vnfr:placement-groups**

List of placement groups at VNF level. The placement group construct defines the compute resource placement strategy in a cloud environment.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/placement-groups/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Placement group name.
requirement	string	1	Describes the intent/rationale behind this placement group. <b>Note:</b> This free-text field is for human consumption only.
strategy	enum	1	Strategy associated with this placement group.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• COLOCATION: [Default] Share the physical infrastructure (hypervisor/network) among all members of this group.</li> <li>• ISOLATION: Do not share the physical infrastructure (hypervisor/network) among the members of this group</li> </ul>
member-vdus	list	0..n	List of VDUs that are part of this placement group. See " <a href="#">vnfr:member-vdus</a> " on page 313.



**vnfr:member-vdus**

/vnfr:vnfr-catalog/vnfr/STRING/vnfd/placement-groups/STRING/member-vdus/STRING

ID	Type	Cardinality	Description
member-vdu-ref	leafref	1	Reference to the VDU in the VNF. This is a leafref to path: ../../vdu/id

## vnfr:vnf-configuration

Information about the VNF configuration for the management interface.

Note: If the network service contains multiple instances of the same VNF, each VNF instance could have a different configuration.

### REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vnf-configuration

### Fields

ID	Type	Cardinality	Description
netconf	container	1	Use NETCONF for configuring the VNF. See <a href="#">"vnfr:netconf" on page 315</a> .
rest	container	1	Use REST for configuring the VNF. See <a href="#">"vnfr:rest" on page 316</a> .
script	container	1	Use a custom script for configuring the VNF. This script will be executed in the orchestrator. All required dependencies for the script should be available in the orchestrator system. See <a href="#">"vnfr:script" on page 316</a> .
juju	container	1	Use Juju for configuring the VNF. See <a href="#">"vnfr:juju" on page 317</a> .
config-access	container	1	IP address to be used to configure this VNF. See <a href="#">"vnfr:config-access" on page 317</a> .

ID	Type	Cardinality	Description
config-attributes	container	1	Miscellaneous config attributes to be considered while processing the NSD to apply configuration. See " <a href="#">vnfr:config-attributes</a> " on page 317.
config-primitive	list	0..n	List of service primitives supported by the configuration agent for this VNF. See " <a href="#">vnfr:config-primitive</a> " on page 318.
initial-config-primitive	list	0..n	Initial set of configuration primitives. See " <a href="#">vnfr:initial-config-primitive</a> " on page 320.
config-template	string	1	Configuration template for each VNF.

### vnfr:netconf

/vnfr:vnfr-catalog/vnfr/STRING/vnf-configuration/netconf

ID	Type	Cardinality	Description
target	enum	1	NETCONF configuration target.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>RUNNING</li> <li>CANDIDATE</li> </ul>

ID	Type	Cardinality	Description
protocol	enum	1	Protocol to use for NETCONF.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>NONE</li> <li>SSH</li> </ul>
port	inet:port-number	1	Port for the NETCONF server.

**vnfr:rest**

/vnfr:vnfr-catalog/vnfr/STRING/vnf-configuration/rest

ID	Type	Cardinality	Description
port	inet_port-number	1	Port for the REST server

**vnfr:script**

/vnfr:vnfr-catalog/vnfr/STRING/vnf-configuration/script

ID	Type	Cardinality	Description
script-type	enum	1	Script type to use.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>BASH</li> <li>EXPECT</li> </ul>

**vnfr:juju**

/vnfr:vnfr-catalog/vnfr/STRING/vnf-configuration/juju

ID	Type	Cardinality	Description
charm	string	1	Juju charm to use to use with the VNF.

**vnfr:config-access**

/vnfr:vnfr-catalog/vnfr/STRING/vnf-configuration/config-access

ID	Type	Cardinality	Description
mgmt-ip-address	union	1	IP address to be used to configure this VNF. <hr/> Note: This parameter is optional if it is possible to dynamically resolve the IP. <hr/>
username	string	1	User name for configuration.
password	string	1	Password for configuration access authentication.

**vnfr:config-attributes**

/vnfr:vnfr-catalog/vnfr/STRING/vnf-configuration/config-attributes

ID	Type	Cardinality	Description
config-priority	uint64	1	Order of configuration priority to be applied to each VNF in this network service. A low number takes precedence over a high number.

ID	Type	Cardinality	Description
config-delay	uint64	1	Wait time (in seconds) before applying the configuration to this VNF.

### vnfr:config-primitive

/vnfr:vnfr-catalog/vnfr/STRING/vnf-configuration/config-primitive/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the service primitive.
parameter	list	0..n	List of parameters to the service primitive. See " <a href="#">vnfr:config-primitive:parameter</a> " on page 319.
user-defined-script	string	1	A user-defined script. If a script is defined, the script will be executed using bash.

**vnfr:config-primitive:parameter**

/vnfr:vnfr-catalog/vnfr/STRING/vnf-configuration/config-primitive/STRING

ID	Type	Cardinality	Description
name	string	1	Name of parameter
data-type	enum	1	Data type associated with the name.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• STRING</li> <li>• INTEGER</li> <li>• BOOLEAN</li> </ul>
mandatory	boolean	1	[Default <i>false</i> ] Defines whether this field is mandatory.
default-value	string	1	The default value for the field.  <b>Note:</b> This value is required to set the read-only and hidden parameters.
parameter-pool	string	1	NSD parameter pool name to use for this parameter.
read-only	boolean	1	If set to <i>true</i> , the value is dimmed in the UI.  <b>Note:</b> This parameter can be set to true only on parameters that specify a default-value field.
hidden	boolean	1	If set to true, the value is hidden from view in the UI.  <b>Note:</b> This parameter can be set to true only on parameters that specify a default-value field.
out	boolean	1	Specifies if this is an output of the primitive execution.

**vnfr:initial-config-primitive**

/vnfr:vnfr-catalog/vnfr/STRING/vnf-configuration/initial-config-primitive/0

ID	Type	Cardinality	Description
seq	uint64	1	Sequence number for the configuration primitive.
name	string	1	Name of the configuration primitive.
parameter	list	0..n	List of parameters to the configuration primitive. See " <a href="#">vnfr:initial-config-primitive:parameter</a> " on page 320.
user-defined-script	string	1	A user-defined script
config-primitive-ref	leafref	1	Reference to a config primitive name. <hr/> <b>Note:</b> The referenced config primitive should have all the input paramaters predefined either with default values or dependency references. <hr/>

**vnfr:initial-config-primitive:parameter**

/vnfr:vnfr-catalog/vnfr/STRING/vnf-configuration/initial-config-primitive/0/parameter/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the parameter.
value	string	1	Value of the parameter.



## vnfr:mgmt-interface

Interface over which the VNF is managed.

### REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/mgmt-interface

### Fields

ID	Type	Cardinality	Description
ip-address	union	1	Specifies the static IP address for managing the VNF.
port	uint16	1	Port number for the management interface.
ssh-key	container	1	SSH key pair used for this VNF. See " <a href="#">vnfr:ssh-key</a> " on page 321.

## vnfr:ssh-key

/vnfr:vnfr-catalog/vnfr/STRING/mgmt-interface/ssh-key

ID	Type	Cardinality	Description
public-key	string	1	Public key configured on this VNF.
private-key-file	string	1	Path to the private key file.

## vnfr:internal-vlr

References to a virtual link record (VLR) in the VLR catalog.

### REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/internal-vlr/STRING

### Fields

ID	Type	Cardinality	Description
vlr-ref	leafref	1	Reference to a virtual link record in the VLR catalog.
internal-connection-point	leafref	1	Reference to one or more internal connection points. This is a leadref path to: ../../vdur/internal-connection-point/id

## vnfr:connection-point

List of external connection points, in which each VNF:

- Has one or more points that are used to connect a VNF to other VNFs or to external networks
- Exposes these connection points to the orchestrator (NFVO)

The orchestrator constructs network services by connecting the connection points between different VNFs.

The orchestrator uses VLDs and VNFFGs at the network service level to construct network services.

### REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/connection-point/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the connection point.
id	string	1	Unique identifier of the connection points.
short-name	string	1	Short name of the connection point to use as a label in the UI.
type	enum	1	Type of connection point.  <b>Supported values:</b> VPORT: Virtual Port
port-security-enabled	boolean	1	Enables the port security for the port.
static-ip-address	union	1	Static IP address for the connection point

ID	Type	Cardinality	Description
vlr-ref	leafref	1	Reference to the VLR associated with this connection point.
ip-address	union	1	IP address assigned to the external connection point.
mac-address	string	1	MAC address assigned to the external connection point.
connection-point-id	string	1	Identifier for the connection point.

**vnfr:vdur**

List of virtual deployment units (VDUR).

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING

**Fields**

ID	Type	Cardinality	Description
id	string	1	Unique identifier for the VDU.
name	string	1	Unique name for the VDU.
vdu-id-ref	leafref	1	
vim-id	string	1	Allocated VM resource ID.
flavor-id	string	1	VIM assigned flavor ID.
image-id	string	1	VIM assigned flavor ID.
management-ip	union	1	Management IP address.
vm-management-ip	union	1	VM private management IP address.
console-url	string	1	Console URL for this VDU, if available.
vm-flavor	container	1	Flavor of the virtual machine (VM) instance. See " <a href="#">vnfr:vm-flavor</a> " on page 278.

ID	Type	Cardinality	Description
guest-epa	container	1	EPA attributes for the guest operating system. See <a href="#">"vnfr:guest-epa" on page 278.</a>
vswitch-epa	container	1	EPA attributes for Open vSwitch. See <a href="#">"vnfr:vswitch-epa" on page 284.</a>
hypervisor-epa	container	1	EPA attributes for the hypervisor. See <a href="#">"vnfr:hypervisor-epa" on page 285.</a>
host-epa	container	1	EPA attributes for the host operating system. See <a href="#">"vnfr:host-epa" on page 286.</a>
supplemental-boot-data	container	1	Container for custom VIM data. See .
volumes	list	0..n	List of disk-volumes to be attached to VDU. See <a href="#">"vnfd:volumes" on page 232.</a>
alarm	list	0..n	A list of alarms. See <a href="#">"vnfd:alarm" on page 221.</a>
internal-connection-point	list	0..n	List for internal connection points. See <a href="#">"vnfd:internal-connection-point" on page 227.</a>
internal-interface	list	0..n	List of internal interfaces for the VNF. See <a href="#">"vnfd:internal-interface" on page 228.</a>

ID	Type	Cardinality	Description
external-interface	list	0..n	List of external interfaces for the VNF. See " <a href="#">vnfd:external-interface</a> " on page 230.
operational-status	enum	1	<p>The operational status of the VNFR instance init:</p> <ul style="list-style-type: none"> <li>• init : The VDU has just started</li> <li>• vm-init-phase : The VDUs in the VNF is being created in VIM</li> <li>• vm-alloc-pending : The VM alloc is pending in VIM</li> <li>• running : The VDU is active in VM</li> <li>• terminate : The VDU is being terminated</li> <li>• vm-terminate-phase: The VDU in the VNF is being terminated in VIM</li> <li>• terminated : The VDU is in the terminated state</li> <li>• failed : The VDU instantiation failed</li> </ul> <p>This element uses manotypes:monitoring-param</p>
placement-groups-info	list	0..n	Placement groups to which this VDU belongs and its cloud construct

**vnfr:vm-flavor**

Flavor is an alternative term for a VM instance type.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/vm-flavor

**Fields**

ID	Type	Cardinality	Description
vpcu-count	uint16	1	Number of VCPUs for the VM.
memory-mb	uint64	1	Amount of memory in MB to allocate to the VM.
storage-gb	uint64	1	Amount of disk space in GB to allocate to the VM.



**vnfr:guest-epa**

EPA attributes for the guest operating system.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/guest-epa

**Fields**

ID	Type	Cardinality	Description
trusted-execution	boolean	1	If set to <i>true</i> , indicates this VM should be allocated from trusted pool.
mempage-size	enum	1	<p>Memory page allocation size.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>LARGE: Require hugepages (either 2MB or 1GB)</li> <li>SMALL: Doesn't require hugepages</li> <li>SIZE_2MB: Requires 2MB hugepages</li> <li>SIZE_1GB: Requires 1GB hugepages</li> <li>PREFER_LARGE: Application prefers hugepages</li> </ul> <p>Note: If a VM requires hugepages, choose LARGE or SIZE_2MB or SIZE_1GB. If the VM prefers hugepages, choose PREFER_LARGE.</p>
cpu-pinning-policy	enum	1	<p>Describes the association between virtual CPUs in the guest and the physical CPUs in the host.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>DEDICATED: Virtual CPUs are pinned to physical CPUs</li> <li>SHARED: Multiple VMs may share the same physical CPUs.</li> <li>ANY: (Default) Any policy is acceptable for the VM</li> </ul>

ID	Type	Cardinality	Description
cpu-thread-pinning-policy	enum	1	<p>Describes how to place the guest CPUs when the host supports hyper threads.</p> <p><b>Default values:</b></p> <ul style="list-style-type: none"> <li>• AVOID: Avoids placing a guest on a host with threads.</li> <li>• SEPARATE: Places vCPUs on separate cores, and avoids placing two vCPUs on two threads of same core.</li> <li>• ISOLATE: Places each vCPU on a different core, and places no vCPUs from a different guest on the same core.</li> <li>• PREFER: Attempts to place vCPUs on threads of the same core.</li> </ul>
pcie-device list		0..1	<p>List of PCIE passthrough devices.</p> <p>See <a href="#">"vnfr:pcie-device" on page 331</a></p>
numa-unaware	empty		<p>Details about the numa-node-policy are null.</p>
numa-node-policy	container	1	<p>Defines numa topology of the guest, specifying if the guest should run on a host with one numa node or multiple numa nodes.</p> <p><b>Example:</b> A guest might need 8 VCPUs and 4 GB of memory with the VCPUs and memory distributed across multiple NUMA nodes. In this scenario, NUMA node 1 could run with 6 VCPUs and 3GB, and NUMA node 2 could run with 2 vcpus and 1GB.</p> <p>See <a href="#">"vnfr:numa-node-policy" on page 331</a></p>

**vnfr:pcie-device**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/guest-epa/pcie-device/STRING

ID	Type	Cardinality	Description
device-id	string	1	Device identifier.
count	uint64	1	Number of devices to attach to the VM.

**vnfr:numa-node-policy**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/guest-epa/numa-node-policy

ID	Type	Cardinality	Description
node-cnt	uint16	1	Number of NUMA nodes to expose to the VM.
mem-policy	enum	1	Specifies how to allocate memory in a multi-node scenario.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• STRICT: The memory must be allocated from the memory attached to the NUMA node.</li> <li>• PREFERRED: The memory should be allocated from the memory attached to the NUMA node</li> </ul>
node	list	0..n	List of NUMA nodes.  See " <a href="#">vnfr:numa-node-policy:node</a> " on page 332.

**vnfr:numa-node-policy:node**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/guest-epa/numa-node-policy/node/0

ID	Type	Cardinality	Description
id	uint64	1	NUMA node identification. Typically 0 or 1.
vcpu	list	0..n	List of VCPUs to allocate on this NUMA node. See " <a href="#">vnfr:numa-node-policy:node:vcpu</a> " on page 332
memory-mb	uint64	1	Memory size in MB for this NUMA node.
num-cores	uint8	1	Number of cores.
paired-threads	container	1	Container for paired threads. See " <a href="#">vnfr:numa-node-policy:node:paired-threads</a> " on page 333.
num-threads	uint8	1	OpenMANO NUMA type selection.

**vnfr:numa-node-policy:node:vcpu**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/guest-epa/numa-node-policy/node/0/vcpu/0

ID	Type	Cardinality	Description
id	uint64	1	List of VCPUs IDs to allocate on this NUMA node.

**vnfr:numa-node-policy:node:paired-threads**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/guest-epa/numa-node-policy/node/0/paired-threads

ID	Type	Cardinality	Description
num-paired-threads	uint8	1	Number of paired-threads.
paired-thread-ids	list	0..n	List of thread paired to use in case of paired thread NUMA. See " <a href="#">vnfr:numa-node-policy:node:paired-threads:paired-thread-ids</a> " on page 333

**vnfr:numa-node-policy:node:paired-threads:paired-thread-ids**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/guest-epa/numa-node-policy/node/0/paired-threads/paired-thread-ids/0

ID	Type	Cardinality	Description
thread-a	uint8	1	Thread ID
thread-b	uint8	1	Thread ID

**vnfr:vswitch-epa**

EPA attributes for Open vSwitch.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/vswitch-epa

**Fields**

ID	Type	Cardinality	Description
ovs-acceleration	enum	1	<p>Specifies Open vSwitch acceleration mode.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"><li>• MANDATORY: OVS acceleration is required</li><li>• PREFERRED: OVS acceleration is preferred</li><li>• DISABLED: OVS acceleration is disabled.</li></ul>
ovs-offload	enum	1	<p>Specifies Open vSwitch hardware offload mode.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"><li>• MANDATORY: OVS offload is required</li><li>• PREFERRED: OVS offload is preferred</li><li>• DISABLED: OVS offload is disabled</li></ul>

**vnfr:hypervisor-epa**

EPA attributes for the hypervisor.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/hypervisor-epa

**Fields**

ID	Type	Cardinality	Description
type	enum	1	Specifies the type of hypervisor. For example, KVM, XEN.  Value can be: <ul style="list-style-type: none"><li>• KVM: KVM</li><li>• XEN: XEN</li></ul>
version	string	1	Version of the hypervisor.

**vnfr:host-epa**

Specifies the host-level EPA attributes.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/host-epa

**Fields**

ID	Type	Cardinality	Description
cpu-model	enum	1	Host CPU model.  <b>Supported values:</b> <ul style="list-style-type: none"><li>• PREFER_WESTMERE</li><li>• REQUIRE_WESTMERE</li><li>• PREFER_SANDYBRIDGE</li><li>• REQUIRE_SANDYBRIDGE</li><li>• PREFER_IVYBRIDGE</li><li>• REQUIRE_IVYBRIDGE</li><li>• PREFER_HASWELL</li><li>• REQUIRE_HASWELL</li><li>• PREFER_BROADWELL</li><li>• REQUIRE_BROADWELL</li><li>• PREFER_NEHALEM</li><li>• REQUIRE_NEHALEM</li><li>• PREFER_PENRYN</li><li>• REQUIRE_PENRYN</li><li>• PREFER_CONROE</li><li>• REQUIRE_CONROE</li><li>• PREFER_CORE2DUO</li><li>• REQUIRE_CORE2DUO</li></ul>



ID	Type	Cardinality	Description
cpu-arch	enum	1	Host CPU architecture.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• PREFER_X86</li> <li>• REQUIRE_X86</li> <li>• PREFER_X86_64</li> <li>• REQUIRE_X86_64</li> <li>• PREFER_I686</li> <li>• REQUIRE_I686</li> <li>• PREFER_IA64</li> <li>• REQUIRE_IA64</li> <li>• PREFER_ARMV7</li> <li>• REQUIRE_ARMV7</li> <li>• PREFER_ARMV8</li> <li>• REQUIRE_ARMV8</li> </ul>
cpu-vendor	enum	1	Host CPU vendor.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• PREFER_INTEL</li> <li>• REQUIRE_INTEL</li> <li>• PREFER_AMD</li> <li>• REQUIRE_AMD</li> </ul>
cpu-socket-count	uint64	1	Number of sockets on the host.
cpu-core-count	uint64	1	Number of cores on the host.
cpu-core-thread-count	uint64	1	Number of threads per cores on the host.

ID	Type	Cardinality	Description
cpu-feature	list	0..1	List of CPU features. See " <a href="#">vnfr:cpu-feature</a> " on page 338.
om-cpu-model-string	string	1	OpenMano CPU model string.
om-cpu-feature	list	0..n	OpenMano CPU features. See " <a href="#">vnfd:om-cpu-feature</a> " on page 340.

**vnfr:cpu-feature**

[/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/host-epa/cpu-feature/PREFER\\_AES](#)

ID	Type	Cardinality	Description
----	------	-------------	-------------

ID	Type	Cardinality	Description
feature enum 1			<p data-bbox="537 346 911 373"><b>Enumeration for CPU features:</b></p> <ul data-bbox="578 396 1414 657" style="list-style-type: none"><li data-bbox="578 396 1414 457">• AES: CPU supports advanced instruction set for AES (Advanced Encryption Standard).</li><li data-bbox="578 474 1414 657">• CAT: Cache Allocation Technology (CAT) allows an operating system, hypervisor, or similar system management agent to specify the amount of L3 cache (currently the last-level cache in most server and client platforms) space an application can fill.</li></ul> <div data-bbox="613 680 1377 772" style="border: 1px dashed gray; padding: 5px;"><p data-bbox="613 695 1377 772"><b>Note:</b> As a hint to hardware functionality, certain features, such as power management, may override CAT settings.</p></div> <ul data-bbox="578 804 1414 1192" style="list-style-type: none"><li data-bbox="578 804 1414 1024">• CMT: Cache Monitoring Technology (CMT) allows an Operating System, Hypervisor, or similar system management agent to determine the usage of cache based on applications running on the platform. The implementation is directed at L3 cache monitoring (currently the last-level cache in most server and client platforms).</li><li data-bbox="578 1047 1414 1192">• DDIO: Intel Data Direct I/O (DDIO) enables Ethernet server NICs and controllers talk directly to the processor cache without a detour via system memory. This enumeration specifies if the VM requires a DDIO capable host.</li></ul> <p data-bbox="537 1234 760 1262"><b>Supported values:</b></p> <ul data-bbox="578 1283 818 2074" style="list-style-type: none"><li data-bbox="578 1283 781 1310">• PREFER_AES</li><li data-bbox="578 1333 800 1360">• REQUIRE_AES</li><li data-bbox="578 1383 781 1411">• PREFER_CAT</li><li data-bbox="578 1434 800 1461">• REQUIRE_CAT</li><li data-bbox="578 1484 792 1512">• PREFER_CMT</li><li data-bbox="578 1535 810 1562">• REQUIRE_CMT</li><li data-bbox="578 1585 800 1612">• PREFER_DDIO</li><li data-bbox="578 1635 818 1663">• REQUIRE_DDIO</li><li data-bbox="578 1686 810 1713">• REQUIRE_VME</li><li data-bbox="578 1736 792 1764">• PREFER_VME</li><li data-bbox="578 1787 784 1814">• REQUIRE_DE</li><li data-bbox="578 1837 768 1864">• PREFER_DE</li><li data-bbox="578 1887 797 1915">• REQUIRE_PSE</li><li data-bbox="578 1938 776 1965">• PREFER_PSE</li><li data-bbox="578 1988 797 2016">• REQUIRE_TSC</li><li data-bbox="578 2039 776 2066">• PREFER_TSC</li></ul>

**vnfd:om-cpu-feature**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/host-epa/om-cpu-feature/STRING

ID	Type	Cardinality	Description
feature	string	1	CPU feature.

**vnfr:supplemental-boot-data**

Container for custom VIM data.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/supplemental-boot-data

**Fields**

ID	Type	Cardinality	Description
config-file	list	0..n	List of configuration files to be mounted onto an additional drive. See " <a href="#">vnfr:config-file</a> " on page 341.
custom-meta-data	list	0..n	List of metadata to be associated with the instance. See " <a href="#">vnfr:custom-meta-data</a> " on page 341.
boot-data-drive	boolean	1	[Default <i>false</i> ] Specifies whether the VIM should implement additional drives to host config-files or metadata.

**vnfr:config-file**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/supplemental-boot-data/config-file/STRING

ID	Type	Cardinality	Description
source	string	1	Name of the configuration file.
dest	string	1	Full path of the destination in the guest.

**vnfr:custom-meta-data**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/supplemental-boot-data/custom-meta-data/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the metadata parameter.
data-type	enum	1	Data type of the metadata parameter.
value	string	1	Value of the metadata parameter.

**vnfr:volumes**

Defines disk volumes to be attached to the VDU, such as if a VNF requires multiple disks to boot the virtual machine.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/volumes/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the disk-volumes, such as vda, vdb.
description	string	1	Description for the volume.
size	uint64	1	Size of the disk, in GB.
ephemeral	empty		
image	string	1	Image name for the software image to be used.  If the image name is found within the VNF package it will be uploaded to all cloud accounts during the onboarding process. Otherwise, the image must be added to the cloud account with the same name as entered in this field.
image-checksum	string	1	Image md5sum for the software image. The md5sum, if provided, along with the image name, uniquely identifies an image uploaded to the CAL.
volume-ref	string	1	Reference to the pre-existing volume in VIM.
boot-volume	boolean	1	If set to <i>true</i> , indicates that this is a boot volume

ID	Type	Cardinality	Description
boot-priority	int32		Boot priority associated with volume.
device_bus	enum	1	Type of disk-bus on which this disk is exposed to the guest operating system.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• IDE</li> <li>• USB</li> <li>• VIRTIO</li> <li>• SCSI</li> </ul>
device_type	enum	1	Type of device as exposed to the guest operating system.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• DISK</li> <li>• CDROM</li> <li>• FLOPPY</li> <li>• LUN (logical unit number)</li> </ul>
custom-meta-data	list	0..n	List of metadata to be associated with the instance. See " <a href="#">vnfr:custom-meta-data</a> " on page 344

**vnfr:custom-meta-data**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/volumes/STRING/custom-meta-data/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the metadata parameter.



ID	Type	Cardinality	Description
data-type	enum	1	Data type of the metadata parameter.
value	string	1	Value of the metadata parameter.

**vnfr:alarms**

A list of the alarms that have been created for this VDU.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/alarms/STRING

**Fields**

ID	Type	Cardinality	Description
alarm-id	string	1	Reserved field for the identifier assigned by the VIM provider.
name	string	1	A human-readable string to identify the alarm.
description	string	1	Description of the alarm.
vdur-id	string	1	Identifier of the VDU record (VDUR) associated with this alarm.
actions	container	1	Actions related to the alarm. See " <a href="#">vnfr:actions</a> " on page 348.
repeat	boolean	1	[Default <i>true</i> ] Indicates whether the alarm should emit repeatedly after the associated threshold has been crossed.
enabled	boolean	1	[Default <i>true</i> ] Indicates whether the alarm has been enabled or disabled.

ID	Type	Cardinality	Description
severity	enum	1	<p>A measure of the important or urgency of the alarm.</p> <p><b>Supported types:</b></p> <ul style="list-style-type: none"><li>• LOW</li><li>• MODERATE</li><li>• CRITICAL</li></ul>
metric	enum	1	<p>Metric types that can be tracked by this alarm.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"><li>• CPU_UTILIZATION</li><li>• MEMORY_UTILIZATION</li><li>• STORAGE_UTILIZATION</li></ul>
statistic	enum	1	<p>Type of statistic to use to measure a metric, which determines threshold crossing for an alarm.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"><li>• AVERAGE</li><li>• MINIMUM</li><li>• MAXIMUM</li><li>• COUNT</li><li>• SUM</li></ul>

ID	Type	Cardinality	Description
operation	enum	1	<p>The relational operator used to define whether an alarm should be triggered when the metric statistic goes above or below a specified threshold value.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• GE — Greater than or equal to</li> <li>• LE — Less than or equal to</li> <li>• GT — Greater than</li> <li>• LT — Less than</li> <li>• EQ — Equal</li> </ul>
value	decimal164	1	Defines the threshold (up to 4 fraction digits) that, if crossed, will trigger the alarm.
period	uint32	1	Defines the length of time (seconds) for which metric data are collected to evaluate the chosen statistic.
evaluation	uint32	1	<p>Number of samples of the metric statistic used to evaluate threshold crossing.</p> <p>Each sample or evaluation is equal to the metric statistic obtained for a given period.</p> <hr/> <p><b>Note:</b> This value can be used to mitigate spikes in the metric that may skew the statistic of interest.</p> <hr/>

### vnfr:actions

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/alarms/STRING/actions

ID	Type	Cardinality	Description
ok	list	0..n	See " <a href="#">"vnfr:actions"</a> on page 348.

ID	Type	Cardinality	Description
insufficient-data	list	0..n	See " <a href="#">vnfr:actions:insufficient-data</a> " on page 349.
alarm	list	0..n	See " <a href="#">vnfr:actions:alarm</a> " on page 349.

**vnfr:actions:ok**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/alarms/STRING/actions/ok/STRING

ID	Type	Cardinality	Description
url	string	1	

**vnfr:actions:insufficient-data**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/alarms/STRING/actions/insufficient-data/STRING

ID	Type	Cardinality	Description
url	string	1	

**vnfr:actions:alarm**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/alarms/STRING/actions/alarm/STRING

ID	Type	Cardinality	Description
url	string	1	

### vnfr:internal-connection-point

List for internal connection points. Each VNFC has zero or more internal connection points. Internal connection points are used for connecting the VNF components internal to the VNF. If a VNF has only one VNFC, it may not have any internal connection points.

#### REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/internal-connection-point/STRING

#### Fields

ID	Type	Cardinality	Description
name	string	1	Name of the connection point.
id	string	1	Identifier for the internal connection points.
short-name	string	1	Short name to use as a label in the UI.
type	enum	1	Type of connection point. <b>Supported values:</b> VPORT: Virtual Port
port-security-enabled	boolean		Specifies whether to enable port security for the port.
static-ip-address	union	1	Static IP address for the connection point
internal-vld-ref	leafref	1	This is a leafref to path: ../.././internal-vld/id

**vnfr:internal-interface**

Internal interfaces enable traffic between virtual network functions.

REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/internal-interface/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the internal interface inside the VDU.  Note: This name has only local significance to the VDU.
vdu-internal-connection-point-ref	leafref	1	Reference to an internal connection point.  This is a leafref to path: .././internal-connection-point/id
virtual-interface	container	1	Container for the virtual interface properties.  See " <a href="#">vnfr:virtual-interface</a> " on page 352.

**vnfr:virtual-interface**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/internal-interface/STRING/virtual-interface

ID	Type	Cardinality	Description
type	enum	1	<p>Specifies the type of virtual interface between VM and host.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• VIRTIO: [Default] Use the traditional VIRTIO interface</li> <li>• PCI-PASSTHROUGH: Use PCI-PASSTHROUGH interface</li> <li>• SR-IOV: Use SR-IOV interface</li> <li>• E1000 : Emulate E1000 interface</li> <li>• RTL8139 : Emulate RTL8139 interface</li> <li>• PCNET : Emulate PCNET interface</li> <li>• OM-MGMT: Used to specify OpenMANO management internal-connection type</li> </ul>
vpci	string	1	<p>Specifies the virtual PCI address in format dddd:dd:dd.d. For example:</p> <p>0000:00:12.0</p> <p>This information can be used to pass as metadata during the VM creation.</p>
bandwidth	uint64	1	Specifies the aggregate bandwidth requirement for the NIC.



**vnfr:external-interface**

External interfaces enable traffic between VNFs.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/external-interface/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Name of the external interface inside the VDU. <hr/> <b>Note:</b> This name has only local significance to the VDU. <hr/>
vnfd-connection-point-ref	reference	1	Reference to an external connection point. This is a leafref to path: ../../connection-point/name
virtual-interface	container	1	Virtual interface properties. See " <a href="#">vnfr:virtual-interface</a> " on page 354.

**vnfr:virtual-interface**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/external-interface/STRING/virtual-interface

ID	Type	Cardinality	Description
type	enum	1	<p>Specifies the type of virtual interface between VM and host.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• VIRTIO: [Default] Use the traditional VIRTIO interface</li> <li>• PCI-PASSTHROUGH: Use PCI-PASSTHROUGH interface</li> <li>• SR-IOV: Use SR-IOV interface</li> <li>• E1000 : Emulate E1000 interface</li> <li>• RTL8139 : Emulate RTL8139 interface</li> <li>• PCNET : Emulate PCNET interface</li> <li>• OM-MGMT: Used to specify OpenMANO management internal-connection type</li> </ul>
vpci	string	1	<p>Specifies the virtual PCI address in format dddd:dd:dd.d. For example: 0000:00:12.0</p> <hr/> <p><b>Note:</b> This information can be used to pass as metadata during the VM creation.</p> <hr/>
bandwidth	uint64	1	Specifies the aggregate bandwidth requirement for the NIC.

**vnfr:placement-groups-info**

Placement groups to which this VDU belongs and its cloud construct.

**REST URI path**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/placement-groups-info/STRING

**Fields**

ID	Type	Cardinality	Description
name	string	1	Placement group name.
requirement	string	1	<p>Describes the intent/rationale behind this placement group.</p> <hr/> <p><b>Note:</b> This free-text field is for human consumption only.</p> <hr/>
strategy	enum	1	<p>Strategy associated with this placement group.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• COLOCATION: [Default] Share the physical infrastructure (hypervisor/network) among all members of this group.</li> <li>• ISOLATION: Do not share the physical infrastructure (hypervisor/network) among the members of this group</li> </ul>

ID	Type	Cardinality	Description
cloud-type	enum	1	Cloud account type: <ul style="list-style-type: none"> <li>• aws</li> <li>• cloudsim</li> <li>• cloudsim_proxy</li> <li>• mock</li> <li>• openmano</li> <li>• openstack</li> <li>• vsphere</li> <li>• openvim</li> <li>• prop_cloud1</li> </ul>
availability-zone	container	1	Name of the availability zone. See <a href="#">"vnfr:placement-groups-info" on page .</a>
server-group	container	1	Name of the affinity/anti-affinity server group. See <a href="#">"vnfr:server-group" on page 357.</a>
host-aggregate	list	0..n	Name of the host aggregate. See <a href="#">"vnfr:host-aggregate" on page 357.</a>
aws-construct	empty		
openmano-construct	empty		
vsphere-construct	empty		
mock-construct	empty		

ID	Type	Cardinality	Description
cloudsim-construct	empty		

**vnfr:availability-zone**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/placement-groups-info/STRING/availability-zone

ID	Type	Cardinality	Description
name	string	1	Name of the availability zone.

**vnfr:server-group**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/placement-groups-info/STRING/server-group

ID	Type	Cardinality	Description
name	string	1	Name of the affinity/anti-affinity server group.

**vnfr:host-aggregate**

/vnfr:vnfr-catalog/vnfr/STRING/vdur/STRING/placement-groups-info/STRING/host-aggregate/STRING

ID	Type	Cardinality	Description
metadata-key	string	1	
metadata-value	string	1	

## vnfr:http-endpoint

List of http endpoints to be used by monitoring parameters.

### REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/http-endpoint/STRING

### Fields

ID	Type	Cardinality	Description
path	string	1	The HTTP path on the management server.
https	boolean	1	[Default <i>false</i> ] Pick HTTPS instead of HTTP.
port	uint16	1	HTTP port to connect to.
username	string	1	HTTP basic auth user name.
password	string	1	HTTP basic auth password.
polling_interval_secs	uint8	1	[Default 2] HTTP polling interval in seconds.
method	enum	1	Method to be performed at the URI.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• GET (default)</li> <li>• POST</li> <li>• PUT</li> <li>• GET</li> <li>• DELETE</li> <li>• PATCH</li> <li>• OPTIONS</li> </ul>

ID	Type	Cardinality	Description
data	string	1	The data to be sent with POST.
headers	list	0..n	List of custom HTTP headers to put on the HTTP request. See " <a href="#">vnfr:headers</a> " on page 359.

### vnfr:headers

/vnfr:vnfr-catalog/vnfr/STRING/http-endpoint/STRING/headers/STRING

ID	Type	Cardinality	Description
key	string	1	HTTP header key.
value	string	1	HTTP header value.

## vnfr:monitoring-param

List of monitoring parameters at the network service level.

### REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/monitoring-param/STRING

### Fields

ID	Type	Cardinality	Description
id	string	1	Identifier for the monitoring parameter.
name	string	1	Name of the monitoring parameter.
http-endpoint-ref	leafref	1	Reference to the HTTP endpoint. This is a leafref path: ../..../http-endpoint/path See <a href="#">"vnfd:http-endpoint" on page 236</a> .
json-query-method	enum	1	The method to extract a value from a JSON response.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>NAMEKEY: [Default] Use the name as the key for a non-nested value.</li> <li>JSONPATH: Use jsonpath-rw implementation to extract a value.</li> <li>OBJECTPATH: Use objectpath implementation to extract a value.</li> </ul>
json-query-params	container	1	Object for JSON query parameters. See <a href="#">"vnfr:json-query-params" on page 362</a> .



ID	Type	Cardinality	Description
description	string	1	Description of the monitoring parameter.
group-tag	string	1	Tag to group monitoring parameters.
widget-type	enum	1	Type of the widget, typically used by the UI.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• HISTOGRAM</li> <li>• BAR</li> <li>• GAUGE</li> <li>• SLIDER</li> <li>• COUNTER</li> <li>• TEXTBOX</li> </ul>
units	string	1	Units for the monitoring parameter, such as megabits per second.
value-type	enum	1	The type of the parameter value.  <b>Supported values:</b> <ul style="list-style-type: none"> <li>• INT (default)</li> <li>• DECIMAL</li> <li>• STRING</li> </ul>
numeric-constraints	container	1	Constraints for the numbers. See <a href="#">"vnfr:numeric-constraints" on page 362.</a>
text-constraints	container	1	Constraints for the text strings. See <a href="#">"vnfr:text-constraints" on page 363.</a>

ID	Type	Cardinality	Description
value-integer	int64	1	Current value for integer parameter.
value-decimal	decimal164	1	Current value for decimal parameter, up to 4 fraction digits.
value-string	string	1	Current value for the string parameter.

### vnfr:json-query-params

/vnfr:vnfr-catalog/vnfr/STRING/monitoring-param/STRING/json-query-params

ID	Type	Cardinality	Description
json-path	string	1	The JSON path used to extract value from the JSON structure.
object-path	string	1	The object path to use to extract value form the JSON structure.

### vnfr:numeric-constraints

/vnfr:vnfr-catalog/vnfr/STRING/monitoring-param/STRING/numeric-constraints

ID	Type	Cardinality	Description
min-value	uint64	1	Minimum value for the parameter.
max-value	uint64	1	Maximum value for the parameter.

**vnfr:text-constraints**

/vnfr:vnfr-catalog/vnfr/STRING/monitoring-param/STRING/text-constraints

ID	Type	Cardinality	Description
min-length	uint8	1	Minimum string length for the parameter.
max-length	uint8	1	Maximum string length for the parameter.

## vnfr:placement-groups-info

Placement groups to which this VDU belongs and its cloud construct.

### REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/placement-groups-info/STRING

### Fields

ID	Type	Cardinality	Description
name	string	1	Placement group name.
requirement	string	1	<p>Describes the intent/rationale behind this placement group.</p> <hr/> <p><b>Note:</b> This free-text field is for human consumption only.</p> <hr/>
strategy	enum	1	<p>Strategy associated with this placement group.</p> <p><b>Supported values:</b></p> <ul style="list-style-type: none"> <li>• COLOCATION: [Default] Share the physical infrastructure (hypervisor/network) among all members of this group.</li> <li>• ISOLATION: Do not share the physical infrastructure (hypervisor/network) among the members of this group</li> </ul>

ID	Type	Cardinality	Description
cloud-type	enum	1	Cloud account type: <ul style="list-style-type: none"> <li>• aws</li> <li>• cloudsim</li> <li>• cloudsim_proxy</li> <li>• mock</li> <li>• openmano</li> <li>• openstack</li> <li>• vsphere</li> <li>• openvim</li> <li>• prop_cloud1</li> </ul>
availability-zone	container	1	Name of the availability zone. See <a href="#">"vnfr:placement-groups-info" on page .</a>
server-group	container	1	Name of the affinity/anti-affinity server group. See <a href="#">"vnfr:server-group" on page 366.</a>
host-aggregate	list	0..n	Name of the host aggregate. See <a href="#">"vnfr:host-aggregate" on page 366.</a>
aws-construct	empty		
openmano-construct	empty		
vsphere-construct	empty		
mock-construct	empty		

ID	Type	Cardinality	Description
cloudsim-construct	empty		

**vnfr:availability-zone**

/vnfr:vnfr-catalog/vnfr/STRING/placement-groups-info/STRING/availability-zone

ID	Type	Cardinality	Description
name	string	1	Name of the availability zone.

**vnfr:server-group**

/vnfr:vnfr-catalog/vnfr/STRING/placement-groups-info/STRING/server-group

ID	Type	Cardinality	Description
name	string	1	Name of the affinity/anti-affinity server group.

**vnfr:host-aggregate**

/vnfr:vnfr-catalog/vnfr/STRING/placement-groups-info/STRING/host-aggregate/STRING

ID	Type	Cardinality	Description
metadata-key	string	1	
metadata-value	string	1	

## vnfr:cloud-config

List of public keys and users.

### REST URI path

/vnfr:vnfr-catalog/vnfr/STRING/cloud-config

### Fields

ID	Type	Cardinality	Description
key-pair	list	0..n	Used to configure the list of public keys to be injected as part of network service instantiation. See " <a href="#">vnfr:key-pair</a> " on page 367.
user	list	0..n	List of users to be added through cloud-config. See " <a href="#">vnfr:cloud-config</a> " on page .

## vnfr:key-pair

/vnfr:vnfr-catalog/vnfr/STRING/cloud-config/key-pair/STRING

ID	Type	Cardinality	Description
name	string	1	Name of this key pair.
key	string	1	Key associated with this key pair.

**vnfr:user**

/vnfr:vnfr-catalog/vnfr/STRING/cloud-config/user/STRING

ID	Type	Cardinality	Description
name	string	1	Name of the user.
user-info	string	1	The user's real name.
key-pair	string	1	Used to configure the list of public keys to be injected as part of metwprk service instantiation. See " <a href="#">vnfr:key-pair</a> " on page 368.

**vnfr:key-pair**

/vnfr:vnfr-catalog/vnfr/STRING/cloud-config/user/STRING/key-pair/STRING

ID	Type	Cardinality	Description
name	string	1	Name of this key pair.
key	string	1	Key associated with this key pair.



# API Examples

This section provides API examples for configuring a cloud account, uploading an image, descriptor configuration, onboarding descriptors and starting, monitoring, and terminating network services. It also provides examples for executing config primitives on a network service and working with scaling instances.

For some of the examples, you might want to refer to the following external resources:

- OpenStack Image Server APIs [version 1](#)
- OpenStack Image Server APIs [version 2](#)
- [OpenVIM Usage Guide](#)
- OpenVIM Northbound API ([PDF](#))
- [OpenVIIM Install Guide](#)
- [OpenVIM Compute Node Configuration](#)

## Configure Cloud Account

### Create cloud account

#### cURL

```
curl -i -X POST
https://<orchestrator_ip/fqdn>:8008/api/config/cloud/account/Grunt192.66.4.17
-u admin:admin --insecure -H "Accept: application/json" -d @/tmp/cloud.txt
```

#### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/cloud/account/{name}
```

#### Method

POST

#### HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

#### Payload

#### OpenStack data

The `auth_url` refers to your OpenStack system. The orchestrator must be able to reach this URL.

Supported versions of the Openstack Nova API are v2, v2.1, v3.

```
{
  "account": [
    {
      "name": "Grunt192.66.4.17",
      "account-type": "openstack",
      "openstack": {
        "admin": "false",
        "mgmt-network": "private",
        "dynamic-flavor-support": "true",
        "plugin-name": "rwcsl_openstack",
        "key": "",
        "tenant": "demo",
        "cert-validate": "false",
        "auth_url": "http://<keystone_url>/<version>",
        "secret": ""
      }
    }
  ]
}
```

## OpenVIM data

"host" is the IP address of the host on which OpenVIM is running.

```
{
  "account": [
    {
      "name": "Grunt192.66.4.36",
      "account-type": "openvim",
      "openvim": {
        "host": "192.66.4.36",
        "mgmt-network": "default",
        "tenant-name": "demo",
        "image-management": {
          "username": "",
          "password": ""
        }
      }
    }
  ]
}
```

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Delete cloud account

### cURL

```
curl -i -X DELETE
https://<orchestrator_ip/fqdn>:8008/api/config/cloud/account/Grunt192.66.4.17
-u admin:admin --insecure -H "Accept: application/json"
```

### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/cloud/account/{name}
```

### Method

DELETE

### HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

### Payload

None

### Response

On error: HTTP 405 with an error object

On success: HTTP 200 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Upload Image

Generate the MD5 checksum of the QCOW2 image and upload it to the cloud account from the ["Configure Cloud Account" on page 369](#) example.

### cURL

```
curl -X POST -H "Content-Type: application/vnd.yang.data+json" -H "Accept:
application/vnd.yang.data+json" -u admin:admin -d @/tmp/rpc2.txt --insecure
https://<orchestrator_ip/fqdn>:8008/api/operations/create-upload-job
```

### URL

```
https://<orchestrator_ip/fqdn>:8008/api/operations/create-upload-job
```

## Method

POST

## HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

## Payload

```
{
  "input": {
    "cloud-account": "Grunt192.66.4.36",
    "external-url": {
      "image-url": "http://www.example.com/XN65E06D499AA624.qcow2",
      "disk-format": "qcow2",
      "container-format": "bare",
      "image-name": "XN65E06D499AA624.qcow2",
      "image-checksum": "c9dd9dad03d944858c5228ed492398f3"
    }
  }
}
```

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## OpenStack Image Management

For more information, refer to the OpenStack Image Server API documentation, [version 1](#) and/or [version 2](#).

### Authentication

You must first obtain the Auth-Token.

### cURL

```
curl -i -H "Content-Type: application/json" -d @/tmp/authreq.txt
http://<keystone_url>:5000/v3/auth/tokens
```

## URL

```
http://<keystone_url>:5000/v3/auth/tokens
```

## HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
}
```

## Payload

```
{
  "auth": {
    "identity": {
      "methods": ["password"],
      "password": {
        "user": {
          "name": " ",
          "domain": { "id": "default" },
          "password": " "
        }
      }
    },
    "scope": {
      "project": {
        "name": "demo",
        "domain": { "id": "default" }
      }
    }
  }
}
```

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Create image

### cURL

```
curl -i -X POST -H 'x-image-meta-container_format: bare' -H 'X-Auth-Token: c1927a55f6f241fab1c8767ddb90157c' -H 'Content-Type: application/octet-stream' -H 'x-image-meta-disk_format: qcow2' -H 'x-image-meta-name: XN7F5709970052C7.qcow2' --data-binary @/tmp/XN7F5709970052C7.qcow2 http://<keystone_url>:9292/v1/images
```

## URL

```
http://<keystone_url>:9292/v1/images
```

## Method

POST

## HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/octet-stream",
  "x-image-meta-disk_format": "qcow2",
  "x-image-meta-name": "XN7F5709970052C7.qcow2",
  "Authorization": "X-Auth-Token: c1927a55f6f241fab1c8767ddb90157c"
}
```

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Delete image

## cURL

```
curl -i -X DELETE -H 'X-Auth-Token: c1927a55f6f241fab1c8767ddb90157c'
http://<keystone_url>:9292/v2/images?name= XN7F5709970052C7.qcow2
```

## URL

```
http://<keystone_url>:9292/v2/images?name={id}.qcow2
```

## Method

DELETE

## HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "X-Auth-Token: c1927a55f6f241fab1c8767ddb90157c"
}
```

## Payload

None

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## OpenVIM Image Management

For more information, refer to the the OpenVIM Northbound API ([PDF](#)).

### Get tenants

Obtain the tenant ID to use in create-image and delete-image APIs.

### cURL

```
curl -X GET -H "Content-Type: application/json"
http://192.66.4.36:9080/openvim/tenants
```

### URL

```
https://192.66.4.36:9080/api/config/cloud
```

### Method

GET

### HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

### Create image

1. Upload the image to the OpenVIM host:

```
scp -i ~/.ssh/id_grunt -o StrictHostKeyChecking=no -o
UserKnownHostsFile=/dev/null XN65E06D499AA624.qcow2
root@192.66.4.36:/opt/VNF/images/XN65E06D499AA624.qcow2
```

2. Create image on the OpenVIM controller:

```
curl -X POST -H "Content-Type: application/json"
http://192.66.4.36:9080/openvim/a9df2b10-3fc3-11e6-849e-001e6724811f/images
-d @/tmp/openvim.txt
```

```
{
  "image": {
    "path": "/opt/VNF/images/XN65E06D499AA624.qcow2",
    "name": "XN65E06D499AA624.qcow2"
  }
}
```

### Delete image

1. Run GET command to obtain the ID of the image to delete:

```
curl -X GET -H "Content-Type: application/json"
http://192.66.4.36:9080/openvim/a9df2b10-3fc3-11e6-849e-001e6724811f/images
```

2. Delete the image from the OpenVIM controller:

```
curl -X DELETE -H "Content-Type: application/json"
http://192.66.4.36:9080/openvim/a9df2b10-3fc3-11e6-849e-001e6724811f/images/7b0fdc1c-4856-11e6-849e-001e6724811f
```

3. Delete the image from the OpenVIM host:

```
ssh -i ~/.ssh/id_grunt -o StrictHostKeyChecking=no -o
UserKnownHostsFile=/dev/null root@192.66.4.36 rm -f
/opt/VNF/images/XN65E06D499AA624.qcow2
```

## Configure a VNF Descriptor

### Create VNFD

#### cURL

```
curl -i -X POST https://<orchestrator_ip/fqdn>:8008/api/config/vnfd-
catalog/vnfd/XN65E06D499AA624 -u admin:admin --insecure -H "Accept:
application/json" -d @/tmp/vnfd.txt
```

#### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/vnfd-catalog/vnfd/{id}
```

#### Method

POST

#### HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```



## Payload

```
{
  "vnfd": [
    {
      "vdu": [
        {
          "image": "XN65E06D499AA624.qcow2",
          "vm-flavor": {
            "vcpu-count": 2,
            "storage-gb": 32,
            "memory-mb": 4096
          },
          "id": "iovdv_0",
          "count": 1,
          "name": "iovdv_0"
        }
      ],
      "mgmt-interface": {
        "vdu-id": "iovdv_0"
      },
      "version": "1.0",
      "vendor": "",
      "id": "XN65E06D499AA624",
      "short-name": "XN65E06D499AA624",
      "name": "XN65E06D499AA624",
      "description": ""
    }
  ]
}
```

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Delete VNFD

### cURL

```
curl -i -X DELETE https://<orchestrator_ip/fqdn>:8008/api/config/vnfd-catalog/vnfd/XN65E06D499AA624 -u admin:admin --insecure -H "Accept: application/json"
```

### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/vnfd-catalog/vnfd/{id}
```

**Method**

DELETE

**HTTP headers**

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

**Payload**

None

**Response**

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Configure a Network Service Descriptor

### Create NSD

**cURL**

```
curl -i -X POST https://<orchestrator_ip/fqdn>:8008/api/config/nsd-catalog/nsd/XN65E06D499AA624_nsd -u admin:admin --insecure -H "Accept: application/json" -d @/tmp/nsd.txt
```

**URL**

```
https://<orchestrator_ip/fqdn>:8008/api/config/nsd-catalog/nsd/{id}
```

**Method**

POST

**HTTP headers**

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

**Payload**

```
{
  "nsd": [
    {
      "constituent-vnfd":
        [{
          "member-vnf-index": 1,
          "vnfd-id-ref": "XN65E06D499AA624"
        }],
      "vendor": "",
      "version": "1.0",
      "description": "",
      "short-name": "XN65E06D499AA624_nsd",
      "name": "XN65E06D499AA624_nsd",
      "id": "XN65E06D499AA624_nsd"
    }
  ]
}
```

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Delete NSD

### cURL

```
curl -i -X DELETE https://<orchestrator_ip/fqdn>:8008/api/config/nsd-catalog/nsd/XN65E06D499AA624_nsd -u admin:admin --insecure -H "Accept: application/json"
```

### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/nsd-catalog/nsd/{id}
```

### Method

DELETE

### HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

## Payload

None

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Instantiate the Network Service

### Create NSR

#### cURL

```
curl --insecure --request POST
'https://<orchestrator_ip/fqdn>:8008/api/config/ns-instance-
config/nsr/XN65E06D499AA624' -u 'admin:admin' -H
'Accept:application/vnd.yang.data+json' -H "Content-
type:application/vnd.yang.data+json" -d @/tmp/nsr.txt
```

#### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/ns-instance-config/{id}
```

#### Method

POST

#### HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

#### Payload

```
{
  "nsr": [
    {
      "id": "90b024f4-79a3-4acb-818a-c93728220b3d",
      "name": "TestXN65E06D499AA624",
      "short-name": "Test",
      "description": " ",
      "admin-status": "ENABLED",
      "cloud-account": "Grunt192.66.4.36",
    }
  ]
}
```

```

    "nsd": {
      "id": "XN65E06D499AA624.qcow2_nsd",
      "name": "XN65E06D499AA624.qcow2_nsd",
      "short-name": "XN65E06D499AA624.qcow2_nsd",
      "description": " ",
      "constituent-vnfd": [
        {
          "vnfd-id-ref": "XN65E06D499AA624.qcow2",
          "member-vnf-index": 1
        }
      ]
    }
  ]
}

```

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```

{
  "rpc-reply": {
    "ok": ""
  }
}

```

## Delete NSR

To obtain an NSR ID, GET the network service records, identify the record to remove, and then run DELETE.

### GET URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/ns-instance-config/nsr
```

### DELETE cURL

```
curl -i -X DELETE https://<orchestrator_ip/fqdn>:8008/api/config/nsd-catalog/nsd/XN65E06D499AA624_nsd -u admin:admin --insecure -H "Accept: application/json"
```

### DELETE URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/ns-instance-config/nsr/{id}
```

### HTTP headers

```

{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}

```

## Payload

None

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Manage the Network Service using Ping-Pong

The examples in this topic use the [Ping-Pong sample network service](#). Download the Ping-Pong package from <https://open.riftio.com/download/>.

### Associating a VIM account with your orchestrator instance

#### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/cloud
```

#### Method

POST

#### HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

#### Payload

```
{
  "account": [
    {
      "name": "MyOpenstackAccount",
      "account-type": "openstack",
      "params": [
        {
          "label": "Key",
          "ref": "key"
        },
        {
          "label": "Secret",
          "ref": "secret"
        }
      ]
    }
  ]
}
```

```
    },
    {
      "label": "Authentication URL",
      "ref": "auth_url"
    },
    {
      "label": "Tenant",
      "ref": "tenant"
    },
    {
      "label": "Management Network",
      "ref": "mgmt-network"
    },
    {
      "label": "Floating IP Pool",
      "ref": "floating-ip-pool",
      "optional": true
    }
  ],
  "openstack": {
    "key": "key",
    "secret": "secret",
    "auth_url": "http://192.66.4.18:5000/v3",
    "tenant": "demo",
    "mgmt-network": "private"
  }
}
]
```

**Note:** Change the `auth_url` to your OpenStack system. The orchestrator must be able to reach this URL. Supported versions of the Openstack Nova API are v2, v2.1, v3.

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Onboarding preconfigured VNF descriptors

### Part 1: Onboard the ping VNFD

This example shows how to onboard the preconfigured `ping` VNFD using the Ping-Pong network service package.

#### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/vnfd-catalog
```

#### Method

POST

#### HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

#### Payload

```
{
  "vnfd": {
    "description": "This is an example VNF",
    "name": "ping_vnfd",
    "vendor": "",
    "id": "7faf9e0e-f196-11e5-a1e9-6cb3113b406f",
    "vdu": [
      {
        "count": 1,
        "name": "iovdu_0",
        "guest-epa": {
          "cpu-pinning-policy": "ANY"
        },
        "image-checksum": "a6ffaa77f949a9e4ebb082c6147187cf",
        "external-interface": [
          {
            "name": "eth0",
            "virtual-interface": {
              "type": "VIRTIO"
            },
            "vnfd-connection-point-ref": "ping_vnfd/cp0"
          }
        ],
        "cloud-init": "#cloud-config\npassword: fedora\nchpasswd: {
expire: False }\nssh_pwauth: True\nruncmd:\n - [ systemctl, daemon-reload
]\n - [ systemctl, enable, ping.service ]\n - [ systemctl, start, --no-
block, ping.service ]\n - [ ifup, eth1 ]\n",
        "id": "7fb0223e-f196-11e5-a1e9-6cb3113b406f",
        "vm-flavor": {

```



```
        "memory-mb": 512,
        "vcpu-count": 1,
        "storage-gb": 4
    },
    "image": "Fedora-x86_64-20-20131211.1-sda-ping.qcow2"
}
],
"mgmt-interface": {
    "vdu-id": "7fb0223e-f196-11e5-a1e9-6cb3113b406f",
    "port": 18888,
    "dashboard-params": {
        "path": "/api/v1/ping/stats"
    }
},
"connection-point": [
    {
        "name": "ping_vnfd/cp0",
        "type": "VPORT"
    }
],
"short-name": "ping_vnfd",
"service-function-chain": "UNAWARE",
"version": 1,
"monitoring-param": [
    {
        "description": "number of ping requests",
        "value-type": "INT",
        "group-tag": "Group1",
        "units": "packets",
        "widget-type": "COUNTER",
        "name": "ping-request-tx-count",
        "json-query-method": "NAMEKEY",
        "id": 1,
        "http-endpoint-ref": "api/v1/ping/stats"
    },
    {
        "description": "number of ping responses",
        "value-type": "INT",
        "group-tag": "Group1",
        "units": "packets",
        "widget-type": "COUNTER",
        "name": "ping-response-rx-count",
        "json-query-method": "NAMEKEY",
        "id": 2,
        "http-endpoint-ref": "api/v1/ping/stats"
    }
],
"http-endpoint": [
    {
        "path": "api/v1/ping/stats",
        "https": "false",
        "method": "GET",
        "port": 18888,
        "polling_interval_secs": 2
    }
]
```

```
}  
}
```

Note: The image listed in the VNFD (Fedora-x86\_64-20-20131211.1-sda-ping.qcow2 in the above example) must already be uploaded to your OpenStack controller before you try to initiate the service.

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{  
  "rpc-reply": {  
    "ok": ""  
  }  
}
```

## Part 2: Onboard the pong VNFD

This example shows how to onboard the preconfigured `pong` VNFD using the Ping-Pong network service package.

### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/vnfd-catalog
```

### Method

POST

### HTTP headers

```
{  
  "Accept": "application/vnd.yang.data+json",  
  "Content-Type": "application/vnd.yang.data+json",  
  "Authorization": "Basic YWRtaW46YWRtaW4="  
}
```

### Payload

```
{  
  "vnfd": {  
    "description": "This is an example VNF",  
    "name": "pong_vnfd",  
    "vendor": "",  
    "id": "7fb05722-f196-11e5-a1e9-6cb3113b406f",  
    "vdu": [  
      {  
        "count": 1,  
        "name": "iovdu_0",  
      }  
    ]  
  }  
}
```

```

    "guest-epa": {
      "cpu-pinning-policy": "ANY"
    },
    "image-checksum": "977484d95575f80ef8399c9cf1d45ebd",
    "external-interface": [
      {
        "name": "eth0",
        "virtual-interface": {
          "type": "VIRTIO"
        },
        "vnfd-connection-point-ref": "pong_vnfd/cp0"
      }
    ],
    "cloud-init": "#cloud-config\npassword: fedora\nchpasswd: {
expire: False }\nssh_pwauth: True\nruncmd:\n - [ systemctl, daemon-reload
]\n - [ systemctl, enable, pong.service ]\n - [ systemctl, start, --no-
block, pong.service ]\n - [ ifup, eth1 ]\n",
    "id": "7fb0842c-f196-11e5-a1e9-6cb3113b406f",
    "vm-flavor": {
      "memory-mb": 512,
      "vcpu-count": 1,
      "storage-gb": 4
    },
    "image": "Fedora-x86_64-20-20131211.1-sda-pong.qcow2"
  }
],
"mgmt-interface": {
  "vdu-id": "7fb0842c-f196-11e5-a1e9-6cb3113b406f",
  "port": 18889,
  "dashboard-params": {
    "path": "/api/v1/pong/stats"
  }
},
"connection-point": [
  {
    "name": "pong_vnfd/cp0",
    "type": "VPORT"
  }
],
"short-name": "pong_vnfd",
"service-function-chain": "UNAWARE",
"version": 1,
"monitoring-param": [
  {
    "description": "number of pong requests",
    "value-type": "INT",
    "group-tag": "Group1",
    "units": "packets",
    "widget-type": "COUNTER",
    "name": "ping-request-rx-count",
    "json-query-method": "NAMEKEY",
    "id": 1,
    "http-endpoint-ref": "api/v1/pong/stats"
  },
  {
    "description": "number of pong responses",

```

```

        "value-type": "INT",
        "group-tag": "Group1",
        "units": "packets",
        "widget-type": "COUNTER",
        "name": "ping-response-tx-count",
        "json-query-method": "NAMEKEY",
        "id": 2,
        "http-endpoint-ref": "api/v1/pong/stats"
    }
],
"http-endpoint": [
    {
        "path": "api/v1/pong/stats",
        "https": "false",
        "method": "GET",
        "port": 18889,
        "polling_interval_secs": 2
    }
]
}

```

Note: The image listed in the VNFD (Fedora-x86\_64-20-20131211.1-sda-pong.qcow2 in the above example) must already be uploaded to your OpenStack controller before you try to initiate the service

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```

{
  "rpc-reply": {
    "ok": ""
  }
}

```

## Onboarding the preconfigured network service descriptor

This example shows how to onboard the Ping-Pong network service package, which has connectivity between the VNFs.

## URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/nsd-catalog
```

## Method

POST



```

        "vnfd-id-ref": "7faf9e0e-f196-11e5-a1e9-6cb3113b406f"
    },
    {
        "member-vnf-index": 2,
        "vnf-configuration": {
            "config-template": "\n#!/usr/bin/bash\n\n# Rest API
configuration\npong_mgmt_ip='<rw_mgmt_ip>'\npong_mgmt_port=18889\n#
username=<rw_username>\n# password=<rw_password>\n\n# VNF specific
configuration\npong_server_ip='<rw_connection_point_name
pong_vnfd/cp0>'\nserver_port=5555\n\n# Make Rest API calls to configure
VNF\nncurl -D /dev/stdout \\\n    -H \"Accept: application/vnd.yang.data+xml\"
\\\n    -H \"Content-Type: application/vnd.yang.data+json\" \\\n    -X POST
\\\n    -d \"{\\\"ip\\\":\\\"$pong_server_ip\\\", \\\"port\\\":$server_port}\" \\\n
http://${pong_mgmt_ip}:${pong_mgmt_port}/api/v1/pong/server\nrc=$?\nif [ $rc
-ne 0 ]\nthen\n    echo \"Failed to set server(own) info for pong!\" \n
exit $rc\nfi\nncurl -D /dev/stdout \\\n    -H \"Accept:
application/vnd.yang.data+xml\" \\\n    -H \"Content-Type:
application/vnd.yang.data+json\" \\\n    -X POST \\\n    -d
\"{\\\"enable\\\":true}\" \\\n
http://${pong_mgmt_ip}:${pong_mgmt_port}/api/v1/pong/adminstatus/state\nrc=$?
\nif [ $rc -ne 0 ]\nthen\n    echo \"Failed to enable pong service!\" \n
exit $rc\nfi\n\nexit 0\n    ",
            "script": {
                "script-type": "bash"
            },
            "config-type": "script",
            "input-params": {
                "config-priority": 1,
                "config-delay": 60
            }
        },
        "vnfd-id-ref": "7fb05722-f196-11e5-a1e9-6cb3113b406f"
    }
],
"config-primitive": [
    {
        "name": "ping config",
        "user-defined-script": "ping_config.py"
    }
],
"name": "ping_pong_nsd",
"vendor": "",
"id": "7fb09dea-f196-11e5-a1e9-6cb3113b406f",
"version": 1,
"vld": [
    {
        "description": "Toy VL",
        "vnfd-connection-point-ref": [
            {
                "vnfd-connection-point-ref": "ping_vnfd/cp0",
                "member-vnf-index-ref": 1,
                "vnfd-id-ref": "7faf9e0e-f196-11e5-a1e9-6cb3113b406f"
            },
            {
                "vnfd-connection-point-ref": "pong_vnfd/cp0",
                "member-vnf-index-ref": 2,
            }
        ]
    }
]

```

```

        "vnfd-id-ref": "7fb05722-f196-11e5-a1e9-6cb3113b406f"
      }
    ],
    "short-name": "ping_pong_vld",
    "name": "ping_pong_vld",
    "vendor": "",
    "id": "7fb0cd42-f196-11e5-a1e9-6cb3113b406f",
    "version": 1,
    "type": "ELAN"
  }
]
}

```

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```

{
  "rpc-reply": {
    "ok": ""
  }
}

```

## Instantiating the network service

### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/ns-instance-config
```

### Method

POST

### HTTP headers

```

{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}

```

### Payload

```

{
  "nsr": [
    {
      "id": "90b024f4-79a3-4acb-818a-c93728220b3d",
      "nsd-ref": "7fb09dea-f196-11e5-a1e9-6cb3113b406f",
      "name": "TestPingPongNS",
      "short-name": "TestPingPongNS",
      "description": "a description for 90b024f4-79a3-4acb-818a-c93728220b3d",
    }
  ]
}

```

```
    "admin-status": "ENABLED",
    "cloud-account": "MyOpenstackAccount"
  }
]
}
```

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Monitoring the instantiated network service

### URL

```
https://<orchestrator_ip/fqdn>:8008/api/operational/ns-instance-
opdata/nsr/<nsr_id>?deep
```

### Method

GET

### HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

### Payload

None

## Response

On error: HTTP 405 with an error object

On success: HTTP 200 with payload similar to the following.

```
{
  "nsr:nsr": {
    "config-status": "configuring",
    "create-time": 1458833812,
    "vlr": [
      {
        "vlr-ref": "0aa96ce8-ceb4-43f4-83f7-43aa52d7f3fd",
        "vnfr-connection-point-ref": [
          {

```



```

        "connection-point": "ping_vnfd/cp0",
        "vnfr-id": "759a43dc-4596-4628-817d-f9c882470cf5"
    },
    {
        "connection-point": "pong_vnfd/cp0",
        "vnfr-id": "c6196a63-e175-43b2-9bf6-74536c3bc3ed"
    }
]
}
],
"rw-nsr:nfvi-metrics": {
    "internal-ports": {
        "label": "INTERNAL PORTS",
        "total": 0
    },
    "storage": {
        "utilization": 0,
        "used": 0,
        "label": "STORAGE",
        "total": 8000000000
    },
    "vcpu": {
        "utilization": 0,
        "label": "VCPU",
        "total": 2
    },
    "network": {
        "incoming": {
            "bytes": 0,
            "packets": 0,
            "label": "INCOMING NETWORK TRAFFIC",
            "packet-rate": 0,
            "byte-rate": 0
        },
        "outgoing": {
            "bytes": 0,
            "packets": 0,
            "label": "OUTGOING NETWORK TRAFFIC",
            "packet-rate": 0,
            "byte-rate": 0
        },
        "label": "NETWORK TRAFFIC"
    },
    "external-ports": {
        "label": "EXTERNAL PORTS",
        "total": 2
    },
    "vm": {
        "inactive-vm": 0,
        "label": "VM",
        "active-vm": 2
    },
    "memory": {
        "utilization": 0,
        "used": 0,
        "label": "MEMORY",

```

```

    "total": 1024000000
  }
},
"scaling-group-record": [
  {
    "scaling-group-name-ref": "ping_group"
  }
],
"vnfr-monitoring-param": [
  {
    "vnfr-id-ref": "c6196a63-e175-43b2-9bf6-74536c3bc3ed",
    "monitoring-param": [
      {
        "description": "no of ping responses",
        "value-type": "INT",
        "group-tag": "Group1",
        "units": "packets",
        "widget-type": "COUNTER",
        "value-integer": 0,
        "name": "ping-response-tx-count",
        "json-query-method": "NAMEKEY",
        "id": 2,
        "http-endpoint-ref": "api/v1/ping/stats"
      },
      {
        "description": "no of ping requests",
        "value-type": "INT",
        "group-tag": "Group1",
        "units": "packets",
        "widget-type": "COUNTER",
        "value-integer": 0,
        "name": "ping-request-rx-count",
        "json-query-method": "NAMEKEY",
        "id": 1,
        "http-endpoint-ref": "api/v1/ping/stats"
      }
    ]
  },
  {
    "vnfr-id-ref": "759a43dc-4596-4628-817d-f9c882470cf5",
    "monitoring-param": [
      {
        "description": "no of ping responses",
        "value-type": "INT",
        "group-tag": "Group1",
        "units": "packets",
        "widget-type": "COUNTER",
        "value-integer": 0,
        "name": "ping-response-rx-count",
        "json-query-method": "NAMEKEY",
        "id": 2,
        "http-endpoint-ref": "api/v1/ping/stats"
      },
      {
        "description": "no of ping requests",
        "value-type": "INT",

```

```

        "group-tag": "Group1",
        "units": "packets",
        "widget-type": "COUNTER",
        "value-integer": 0,
        "name": "ping-request-tx-count",
        "json-query-method": "NAMEKEY",
        "id": 1,
        "http-endpoint-ref": "api/v1/ping/stats"
    }
  ]
}
],
"operational-status": "running",
"cloud-account": "MyOpenstackAccount",
"nsd-name-ref": "ping_pong_nsd",
"rw-nsr:operational-events": [
  {
    "id": 1,
    "description": "Instatiation Request Received NSR Id:90b024f4-79a3-4acb-818a-c93728220b3d",
    "event": "instantiating",
    "timestamp": 1458833812
  },
  {
    "id": 2,
    "description": "Fetched NSD with descriptor id 7fb09dea-f196-11e5-a1e9-6cb3113b406f",
    "event": "nsd-fetched",
    "timestamp": 1458833812
  },
  {
    "id": 3,
    "description": "Instantiating 1 external VLs for NSR id 90b024f4-79a3-4acb-818a-c93728220b3d",
    "event": "begin-external-vls-instantiation",
    "timestamp": 1458833812
  },
  {
    "id": 4,
    "description": "Finished instantiating 1 external VLs for NSR id 90b024f4-79a3-4acb-818a-c93728220b3d",
    "event": "end-external-vls-instantiation",
    "timestamp": 1458833815
  },
  {
    "id": 5,
    "description": "Instantiating 2 VNFS for NSR id 90b024f4-79a3-4acb-818a-c93728220b3d",
    "event": "begin-vnf-instantiation",
    "timestamp": 1458833815
  },
  {
    "id": 6,
    "description": "Finished instantiating 2 VNFs for NSR id 90b024f4-79a3-4acb-818a-c93728220b3d",
    "event": "end-vnf-instantiation",

```

```

      "timestamp": 1458833815
    },
    {
      "id": 7,
      "description": "NSR in running state for NSR id 90b024f4-79a3-4acb-818a-c93728220b3d",
      "event": "ns-running",
      "timestamp": 1458833815
    }
  ],
  "constituent-vnfr-ref": [
    {
      "vnfr-id": "c6196a63-e175-43b2-9bf6-74536c3bc3ed"
    },
    {
      "vnfr-id": "759a43dc-4596-4628-817d-f9c882470cf5"
    }
  ],
  "ns-instance-config-ref": "90b024f4-79a3-4acb-818a-c93728220b3d",
  "name-ref": "TestPingPongNS"
}
}

```

## Monitoring underlying VNFs

### URL

```
https://<orchestrator_ip/fqdn>:8008/api/operational/vnfr-catalog/vnfr?deep
```

### Method

GET

### HTTP headers

```

{
  "Accept": "application/vnd.yang.collection+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}

```

### Payload

None

### Response

On error: HTTP 405 with an error object

On success: HTTP 200 with payload-like:

```

{
  "collection": {
    "vnfr:vnfr": [
      {
        "description": "This is an example VNF",

```

```

    "vnf-configuration": {
      "config-access": {
        "mgmt-ip-address": "10.66.218.250"
      },
      "config-template": "\n#!/usr/bin/bash\n\n# Rest API
configuration\npong_mgmt_ip='<rw_mgmt_ip>'\npong_mgmt_port=18889\n#
username=<rw_username>\n# password=<rw_password>\n\n# VNF specific
configuration\npong_server_ip='<rw_connection_point_name
pong_vnfd/cp0>'\nserver_port=5555\n\n# Make Rest API calls to configure
VNF\nncurl -D /dev/stdout \\\n      -H \"Accept: application/vnd.yang.data+xml\"
\\\n      -H \"Content-Type: application/vnd.yang.data+json\" \\\n      -X POST
\\\n      -d \"{\"ip\": \"${pong_server_ip}\", \"port\": ${server_port}}\" \\\n
http://${pong_mgmt_ip}:${pong_mgmt_port}/api/v1/pong/server\nrc=$?\nif [ $rc
-ne 0 ]\nthen\n  echo \"Failed to set server(own) info for pong!\"\n\n
exit $rc\nfi\nncurl -D /dev/stdout \\\n      -H \"Accept:
application/vnd.yang.data+xml\" \\\n      -H \"Content-Type:
application/vnd.yang.data+json\" \\\n      -X POST \\\n      -d
\"{\"enable\": true}\" \\\n
http://${pong_mgmt_ip}:${pong_mgmt_port}/api/v1/pong/adminstatus/state\nrc=$?
\nif [ $rc -ne 0 ]\nthen\n  echo \"Failed to enable pong service!\"\n\n
exit $rc\nfi\n\nexit 0\n      ",
      "script": {
        "script-type": "bash"
      },
      "config-type": "script",
      "input-params": {
        "config-priority": 1,
        "config-delay": 60
      }
    },
    "config-status": "configuring",
    "connection-point": [
      {
        "name": "pong_vnfd/cp0",
        "ip-address": "11.0.0.2",
        "vlr-ref": "0aa96ce8-ceb4-43f4-83f7-43aa52d7f3fd",
        "connection-point-id": "3c6ffdad-d450-4f3a-9a7d-9499cec9bb9e"
      }
    ],
    "vendor": "",
    "id": "c6196a63-e175-43b2-9bf6-74536c3bc3ed",
    "mgmt-interface": {
      "ip-address": "10.66.218.250",
      "port": 18889
    },
    "name": "TestPingPongNS..pong_vnfd.2",
    "vnfd-ref": "7fb05722-f196-11e5-a1e9-6cb3113b406f",
    "vdur": [
      {
        "vm-management-ip": "10.0.218.233",
        "guest-epa": {
          "cpu-pinning-policy": "ANY"
        },
        "management-ip": "10.66.218.250",
        "vdu-id-ref": "7fb0842c-f196-11e5-a1e9-6cb3113b406f",
        "external-interface": [

```

```

        {
            "name": "pong_vnfd/cp0",
            "vnfd-connection-point-ref": "pong_vnfd/cp0"
        }
    ],
    "id": "a186ec29-598d-4eef-baa4-70fb69baf490",
    "flavor-id": "500d30e6-41ce-40d4-ad7d-fe14b113e6bf",
    "vim-id": "2f51cela-0c3a-43ea-878b-21c8efce8217",
    "vm-flavor": {
        "memory-mb": 512,
        "vcpu-count": 1,
        "storage-gb": 4
    },
    "operational-status": "running",
    "image-id": "d96eda6d-4a48-4f9d-bd8c-3a5a26a64b71"
}
],
"short-name": "pong_vnfd",
"operational-status": "running",
"cloud-account": "MyOpenstackAccount",
"dashboard-url": "http://10.66.218.250:80/api/v1/pong/stats",
"version": 1,
"member-vnf-index-ref": 2,
"monitoring-param": [
    {
        "description": "no of ping requests",
        "value-type": "INT",
        "group-tag": "Group1",
        "units": "packets",
        "widget-type": "COUNTER",
        "value-integer": 0,
        "name": "ping-request-rx-count",
        "json-query-method": "NAMEKEY",
        "id": 1,
        "http-endpoint-ref": "api/v1/pong/stats"
    },
    {
        "description": "no of ping responses",
        "value-type": "INT",
        "group-tag": "Group1",
        "units": "packets",
        "widget-type": "COUNTER",
        "value-integer": 0,
        "name": "ping-response-tx-count",
        "json-query-method": "NAMEKEY",
        "id": 2,
        "http-endpoint-ref": "api/v1/pong/stats"
    }
]
},
{
    "description": "This is an example VNF",
    "vnf-configuration": {
        "config-access": {
            "mgmt-ip-address": "10.66.218.251"
        }
    },
}

```

```

    "config-template": "\n#!/usr/bin/bash\n\n# Rest API
config\nping_mgmt_ip='<rw_mgmt_ip>'\nping_mgmt_port=18888\n\n# VNF specific
configuration\npong_server_ip='<rw_connection_point_name
pong_vnfd/cp0>'\nping_rate=5\nserver_port=5555\n\n# Make rest API calls to
configure VNF\nncurl -D /dev/stdout \\\n    -H \"Accept:
application/vnd.yang.data+xml\" \\\n    -H \"Content-Type:
application/vnd.yang.data+json\" \\\n    -X POST \\\n    -d
\"{\n\"ip\": \"\${ping_mgmt_ip}\", \"port\": \${server_port}\"}\" \\\n
http://\${ping_mgmt_ip}:\${ping_mgmt_port}/api/v1/ping/server\nrc=?\nif [ $rc
-ne 0 ]\nthen\n    echo \"Failed to set server info for ping!\"\n    exit
$rc\nfi\nncurl -D /dev/stdout \\\n    -H \"Accept:
application/vnd.yang.data+xml\" \\\n    -H \"Content-Type:
application/vnd.yang.data+json\" \\\n    -X POST \\\n    -d
\"{\n\"rate\": \${ping_rate}\"}\" \\\n
http://\${ping_mgmt_ip}:\${ping_mgmt_port}/api/v1/ping/rate\nrc=?\nif [ $rc -
ne 0 ]\nthen\n    echo \"Failed to set ping rate!\"\n    exit
$rc\nfi\n\noutput=$(curl -D /dev/stdout \\\n    -H \"Accept:
application/vnd.yang.data+xml\" \\\n    -H \"Content-Type:
application/vnd.yang.data+json\" \\\n    -X POST \\\n    -d
\"{\n\"enable\": true}\") \\\n
http://\${ping_mgmt_ip}:\${ping_mgmt_port}/api/v1/ping/adminstatus/state)\nif
[[ $output == *\"Internal Server Error\"* ]]\nthen\n    echo $output\n
exit 3\nelse\n    echo $output\nfi\n\n\nnext 0\n    ",
    "script": {
        "script-type": "bash"
    },
    "config-type": "script",
    "input-params": {
        "config-priority": 2,
        "config-delay": 0
    }
},
"config-status": "configuring",
"connection-point": [
    {
        "name": "ping_vnfd/cp0",
        "ip-address": "11.0.0.3",
        "vlr-ref": "0aa96ce8-ceb4-43f4-83f7-43aa52d7f3fd",
        "connection-point-id": "114b5015-6006-4cd0-8e29-683fd886ae1a"
    }
],
"vendor": "",
"id": "759a43dc-4596-4628-817d-f9c882470cf5",
"mgmt-interface": {
    "ip-address": "10.66.218.251",
    "port": 18888
},
"name": "TestPingPongNS._.ping_vnfd.1",
"vnfd-ref": "7faf9e0e-f196-11e5-a1e9-6cb3113b406f",
"vdur": [
    {
        "vm-management-ip": "10.0.218.236",
        "guest-epa": {
            "cpu-pinning-policy": "ANY"
        },
        "management-ip": "10.66.218.251",

```

```

    "vdu-id-ref": "7fb0223e-f196-11e5-a1e9-6cb3113b406f",
    "external-interface": [
      {
        "name": "ping_vnfd/cp0",
        "vnfd-connection-point-ref": "ping_vnfd/cp0"
      }
    ],
    "id": "a6e5c57d-890c-469f-82d7-5808ed523c31",
    "flavor-id": "500d30e6-41ce-40d4-ad7d-fe14b113e6bf",
    "vim-id": "aaf88b0e-8577-4b09-b8c0-c3316010e36c",
    "vm-flavor": {
      "memory-mb": 512,
      "vcpu-count": 1,
      "storage-gb": 4
    },
    "operational-status": "running",
    "image-id": "1b38b7d1-1146-424e-a831-eb765bc89a07"
  }
],
"short-name": "ping_vnfd",
"operational-status": "running",
"cloud-account": "MyOpenstackAccount",
"dashboard-url": "http://10.66.218.251:80/api/v1/ping/stats",
"version": 1,
"member-vnf-index-ref": 1,
"monitoring-param": [
  {
    "description": "no of ping requests",
    "value-type": "INT",
    "group-tag": "Group1",
    "units": "packets",
    "widget-type": "COUNTER",
    "value-integer": 0,
    "name": "ping-request-tx-count",
    "json-query-method": "NAMEKEY",
    "id": 1,
    "http-endpoint-ref": "api/v1/ping/stats"
  },
  {
    "description": "no of ping responses",
    "value-type": "INT",
    "group-tag": "Group1",
    "units": "packets",
    "widget-type": "COUNTER",
    "value-integer": 0,
    "name": "ping-response-rx-count",
    "json-query-method": "NAMEKEY",
    "id": 2,
    "http-endpoint-ref": "api/v1/ping/stats"
  }
]
}
]
}
}
}

```



## Terminating the Ping-Pong NS

### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/ns-instance-  
config/nsr/<nsr_id>
```

### Method

DELETE

### HTTP request headers

```
{  
  "Accept": "application/vnd.yang.data+json",  
  "Authorization": "Basic YWRtaW46YWRtaW4="  
}
```

### Payload

None

### HTTP response headers

On error: HTTP 405 with an error object

On success: HTTP 200 with following payload:

```
{  
  "rpc-reply": {  
    "ok": ""  
  }  
}
```

## Trigger Config Primitives on Network Service

If your network services have configuration primitives defined in the descriptor, you can trigger those primitives with the RPC API described in this topic.

**Note:** Primitives can be triggered only after the initial configuration has completed. Check the status by looking at the "config-status" parameter. See the response payload for "Monitoring the instantiated network service" in ["Manage the Network Service using Ping-Pong" on page 382](#).

### URL

```
https://<orchestrator_ip/fqdn>:8008/api/operations/exec-ns-config-primitive
```

### Method

POST

### HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Authorization": "Basic YWRtaW46YWRtaW4="
}
```

### Payload

Example to update IMS network service configuration through configuration primitives:

```
{
  "input": {
    "name": "Update Domain",
    "nsr_id_ref": "07497feb-4f01-411b-a0da-bc258ce6a30b",
    "vnf-list": [
      {
        "member_vnf_index_ref": "1",
        "vnfr-id-ref": "e8c65cc4-5e81-40b2-b2b0-87092defeb3d",
        "vnf-primitive": [
          {
            "name": "config",
            "index": "0",
            "parameter": [
              {
                "name": "base number",
                "value": "1234567890"
              },
              {
                "name": "home_domain",
                "value": "abc.com"
              }
            ]
          }
        ]
      }
    ]
  }
}
```

```

        "name": "number_count",
        "value": "1000"
      },
      {
        "name": "password",
        "value": "cw-aio"
      }
    ]
  }
]
}
}
}

```

## Response

On error: HTTP 405 with an error object

On success: HTTP 200 with the following payload:

```

{
  "rpc-reply": {
    "ok": ""
  }
}

```

## Manage Scaling Group Instance

This topic describes how to use API calls to create and delete a scaling instance for a VNF. For more information, see [Scaling Group Descriptor](#) and [NFV Scaling](#).

### Creating a scaling group instance

#### URL

```

https://<orchestrator_ip/fqdn>:8008/api/config/ns-instance-config/nsr/<nsr-id>/scaling-group/<scaling_group_name>/instance HTTP/1.1

```

#### Method

POST

#### HTTP headers

```

{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Connection: keep-alive",
  "Cache-Control: no-cache"
  "Authorization": "Basic YWRtaW46YWRtaW4=",
}

```

#### Payload

```
{
  "instance": [
    {
      "index": <instance_index_number>
    }
  ]
}
```

## Response

On error: HTTP 405 with an error object

On success: HTTP 201 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

## Deleting a scaled instance

### URL

```
https://<orchestrator_ip/fqdn>:8008/api/config/ns-instance-config/nsr/<nsr-id>/scaling-group/<scaling_group_name>/instance/<instance_index_number>
HTTP/1.1
```

### Method

DELETE

### HTTP headers

```
{
  "Accept": "application/vnd.yang.data+json",
  "Content-Type": "application/vnd.yang.data+json",
  "Connection: keep-alive",
  "Cache-Control: no-cache"
  "Authorization": "Basic YWRtaW46YWRtaW4=",
}
```

### Payload

None

## Response

On error: HTTP 405 with an error object

On success: HTTP 200 with following payload:

```
{
  "rpc-reply": {
    "ok": ""
  }
}
```

```
}  
}
```